

Machine Type	Komatsu PW160	Equipment	2.00m + 3.47m + 2.10m
Issue Date	17/03/2016	Reference	RRK13207
System Type	PME RAIL	Additional Info.	Triple

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Minimum Loads)	Tool Pin	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.43	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.50	3.77	3.22	-	-	-	-	-	-	-
6.00	-	-	-	-	-	4.47	3.76	3.22	2.80	2.45	-	-	-	-	-
5.00	-	-	-	5.36a	5.32	4.38	3.69	3.17	2.76	2.43	2.16	-	-	-	-
4.00	-	-	-	6.42	5.07	4.21	3.57	3.08	2.70	2.39	2.13	1.91	-	-	-
3.00	-	-	8.15a	6.26	4.89	4.00	3.43	2.98	2.63	2.33	2.09	1.88	1.70	-	-
2.00	-	-	4.07a	4.09a	4.44a	3.87	3.30	2.89	2.55	2.28	2.05	1.85	1.68	-	-
1.00	-	3.34a	3.30a	3.46a	3.55a	3.78	3.24	2.82	2.50	2.23	2.01	1.82	1.66	-	-
0.00	4.61a	3.80a	3.43a	3.35a	3.42a	3.76	3.21	2.79	2.46	2.20	1.98	1.80	1.65	-	-
-1.00	6.28a	5.57a	5.16a	5.19a	4.55	3.76	3.20	2.78	2.45	2.19	1.98	1.80	-	-	-
-2.00	9.33a	9.13a	7.74	5.78	4.59	3.78	3.22	2.79	2.46	2.20	1.99	-	-	-	-
-3.00	10.00	10.00	7.83	5.87	4.66	3.85	3.27	2.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Maximum Loads)	Tool Pin	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.44	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.51	3.79	3.23	-	-	-	-	-	-	-
6.00	-	-	-	-	-	4.49	3.80	3.27	2.83	2.46	-	-	-	-	-
5.00	-	-	-	5.37a	5.36	4.44	3.76	3.26	2.86	2.49	2.18	-	-	-	-
4.00	-	-	-	6.59	5.27	4.37	3.72	3.23	2.84	2.50	2.19	1.93	-	-	-
3.00	-	-	8.55	6.48	5.20	4.32	3.69	3.21	2.83	2.48	2.18	1.92	1.71	-	-
2.00	-	-	8.51	6.44	5.16	4.29	3.67	3.20	2.79	2.45	2.15	1.90	1.69	-	-
1.00	-	4.31a	8.24	6.30	5.07	4.23	3.60	3.12	2.73	2.40	2.11	1.87	1.67	-	-
0.00	6.42a	7.69a	8.08	6.14	4.94	4.12	3.51	3.05	2.68	2.34	2.07	1.84	1.65	-	-
-1.00	9.84a	10.00	8.02	6.07	4.87	4.06	3.46	3.00	2.60	2.29	2.03	1.81	-	-	-
-2.00	10.00	10.00	8.01	6.05	4.84	4.03	3.40	2.93	2.54	2.24	2.00	-	-	-	-
-3.00	10.00	10.00	8.05	6.05	4.79	3.96	3.35	2.88	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.44	3.72	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.41	3.70	3.18	2.75	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.30	3.63	3.12	2.72	2.40	2.13	-	-	-	-
4.00	-	-	5.00	5.00	4.97	4.14	3.51	3.04	2.66	2.36	2.10	1.88	-	-	-
3.00	-	-	5.00	5.00	4.85	3.93	3.38	2.94	2.59	2.30	2.06	1.86	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	3.85	3.27	2.86	2.52	2.25	2.02	1.83	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	3.80	3.22	2.81	2.48	2.21	1.99	1.80	-	-	-
0.00	5.00	5.00	4.56a	4.14a	3.82a	3.77	3.20	2.78	2.45	2.19	1.97	1.79	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.60	3.78	3.20	2.78	2.44	2.18	1.97	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.62	3.80	3.22	2.79	2.46	2.20	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.69	3.87	3.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.46	3.73	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.44	3.76	3.23	2.77	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.39	3.73	3.23	2.80	2.44	2.13	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.33	3.69	3.20	2.81	2.44	2.14	1.88	-	-	-
3.00	-	-	5.00	5.00	5.00	4.29	3.66	3.18	2.79	2.42	2.12	1.88	-	-	-
2.00	-	-	5.00	5.00	5.00	4.27	3.65	3.15	2.75	2.39	2.09	1.85	-	-	-
1.00	-	-	5.00	5.00	5.00	4.18	3.55	3.08	2.70	2.34	2.06	1.83	-	-	-
0.00	5.00	5.00	5.00	5.00	4.90	4.08	3.48	3.01	2.62	2.29	2.02	1.80	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.85	4.03	3.43	2.94	2.55	2.24	1.99	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.82	3.97	3.35	2.88	2.50	2.21	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.75	3.92	3.31	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Minimum Loads)	Hitch	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.90	3.34	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	3.87	3.32	2.88	2.54	2.25	-	-	-	-
5.00	-	-	-	-	-	4.49	3.78	3.25	2.83	2.50	2.23	1.99	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.31	3.66	3.15	2.76	2.44	2.18	1.96	1.77	-	-
3.00	-	5.00	4.82a	5.00	4.89	4.09	3.49	3.03	2.67	2.37	2.13	1.92	1.74	1.59	-
2.00	2.62a	2.65a	2.84a	3.01a	4.59	3.88	3.34	2.92	2.58	2.30	2.07	1.88	1.71	1.56	-
1.00	3.96a	3.04a	2.70a	2.65a	4.27a	3.75	3.23	2.82	2.50	2.24	2.02	1.84	1.68	1.54	-
0.00	4.58a	3.67a	3.06a	3.80a	4.45	3.70	3.17	2.77	2.46	2.20	1.99	1.81	1.66	-	-
-1.00	5.00	5.00	5.00	5.00	4.45	3.69	3.15	2.75	2.43	2.18	1.97	1.79	1.65	-	-
-2.00	5.00	5.00	5.00	5.00	4.47	3.71	3.16	2.75	2.43	2.18	1.97	1.80	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.53	3.75	3.19	2.77	2.45	2.20	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	4.67	3.88	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AU (Maximum Loads)	Hitch	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.90	3.36a	2.90	-	-	-	-	-	-
6.00	-	-	-	-	-	-	3.88	3.35	2.93	2.57	2.26	-	-	-	-
5.00	-	-	-	-	-	4.51	3.83	3.31	2.91	2.58	2.27	2.01	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.42	3.76	3.27	2.88	2.57	2.27	2.01	1.78	-	-
3.00	-	5.00	5.00	5.00	5.00	4.34	3.70	3.23	2.85	2.55	2.25	1.99	1.77	1.59	-
2.00	4.65a	5.00	5.00	5.00	5.00	4.28	3.67	3.20	2.83	2.53	2.22	1.96	1.75	1.57	-
1.00	4.86a	5.00	5.00	5.00	5.00	4.27	3.65	3.17	2.78	2.47	2.17	1.92	1.71	1.54	-
0.00	5.00	5.00	5.00	5.00	4.96	4.14	3.54	3.08	2.72	2.39	2.11	1.87	1.68	-	-
-1.00	5.00	5.00	5.00	5.00	4.85	4.05	3.46	3.02	2.64	2.31	2.05	1.83	1.65	-	-
-2.00	5.00	5.00	5.00	5.00	4.80	4.00	3.42	2.93	2.55	2.25	2.00	1.80	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.76	3.92	3.32	2.86	2.50	2.22	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	4.69	3.88	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Minimum Loads)	Tool Pin	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.16	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.32	2.69	2.22	-	-	-	-	-	-	-
6.00	-	-	-	-	-	3.29	2.68	2.22	1.88	1.60	-	-	-	-	-
5.00	-	-	-	5.36a	4.03	3.18	2.59	2.17	1.84	1.58	1.37	-	-	-	-
4.00	-	-	-	5.01	3.73	2.99	2.46	2.07	1.77	1.53	1.34	1.17	-	-	-
3.00	-	-	7.24	4.81	3.52	2.75	2.31	1.96	1.69	1.47	1.29	1.14	1.01	-	-
2.00	-	-	4.07a	4.09a	3.35	2.60	2.16	1.86	1.61	1.41	1.25	1.11	0.99	-	-
1.00	-	3.34a	3.30a	3.46a	3.20	2.49	2.09	1.78	1.55	1.36	1.21	1.08	0.97	-	-
0.00	4.61a	3.80a	3.43a	3.35a	3.12	2.47	2.05	1.75	1.51	1.33	1.18	1.06	0.95	-	-
-1.00	6.28a	5.57a	5.16a	4.19	3.12	2.48	2.05	1.74	1.50	1.32	1.17	1.06	-	-	-
-2.00	9.33a	9.13a	6.18	4.22	3.16	2.50	2.07	1.75	1.51	1.33	1.19	-	-	-	-
-3.00	10.00	10.00	6.31	4.33	3.25	2.58	2.13	1.81	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Maximum Loads)	Tool Pin	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.16	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.33	2.72	2.23	-	-	-	-	-	-	-
6.00	-	-	-	-	-	3.31	2.72	2.28	1.91	1.61	-	-	-	-	-
5.00	-	-	-	5.37a	4.08	3.25	2.68	2.26	1.94	1.64	1.39	-	-	-	-
4.00	-	-	-	5.22	3.97	3.18	2.63	2.23	1.93	1.65	1.40	1.19	-	-	-
3.00	-	-	7.26	5.08	3.88	3.12	2.59	2.21	1.92	1.63	1.39	1.18	1.02	-	-
2.00	-	-	7.21	5.03	3.84	3.09	2.57	2.20	1.88	1.60	1.36	1.17	1.00	-	-
1.00	-	4.31a	6.84	4.86	3.73	3.01	2.49	2.11	1.81	1.55	1.32	1.13	0.98	-	-
0.00	6.42a	7.69a	6.64	4.67	3.58	2.89	2.40	2.04	1.75	1.48	1.27	1.10	0.96	-	-
-1.00	9.84a	10.00	6.55	4.57	3.49	2.81	2.34	1.98	1.66	1.42	1.23	1.07	-	-	-
-2.00	10.00	10.00	6.54	4.55	3.46	2.79	2.28	1.90	1.60	1.37	1.20	-	-	-	-
-3.00	10.00	10.00	6.60	4.55	3.41	2.71	2.21	1.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.26	2.63	-	-	-	-	-	-	-	-
6.00	-	-	-	-	4.09	3.22	2.61	2.17	1.83	-	-	-	-	-	-
5.00	-	-	5.00	5.00	3.92	3.10	2.53	2.11	1.80	1.54	1.33	-	-	-	-
4.00	-	-	5.00	4.88	3.61	2.91	2.40	2.02	1.73	1.50	1.31	1.14	-	-	-
3.00	-	-	5.00	4.75	3.47	2.67	2.25	1.92	1.65	1.44	1.26	1.12	-	-	-
2.00	-	-	4.03a	4.03a	3.35	2.58	2.13	1.82	1.58	1.38	1.22	1.08	-	-	-
1.00	-	-	4.01a	3.90a	3.24	2.52	2.07	1.77	1.53	1.34	1.18	1.06	-	-	-
0.00	5.00	5.00	4.56a	4.14a	3.19	2.49	2.05	1.74	1.50	1.31	1.16	1.04	-	-	-
-1.00	5.00	5.00	5.00	4.27	3.17	2.50	2.05	1.73	1.49	1.31	1.16	-	-	-	-
-2.00	5.00	5.00	5.00	4.28	3.20	2.52	2.07	1.75	1.51	1.32	-	-	-	-	-
-3.00	5.00	5.00	5.00	4.38	3.29	2.61	2.15	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.28	2.65	-	-	-	-	-	-	-	-
6.00	-	-	-	-	4.10	3.26	2.68	2.23	1.85	-	-	-	-	-	-
5.00	-	-	5.00	5.00	4.01	3.20	2.64	2.23	1.88	1.58	1.34	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.13	2.60	2.21	1.89	1.59	1.34	1.14	-	-	-
3.00	-	-	5.00	5.00	3.84	3.08	2.56	2.18	1.87	1.57	1.33	1.13	-	-	-
2.00	-	-	5.00	5.00	3.81	3.06	2.55	2.15	1.83	1.54	1.30	1.11	-	-	-
1.00	-	-	5.00	4.78	3.67	2.95	2.44	2.07	1.77	1.49	1.26	1.08	-	-	-
0.00	5.00	5.00	5.00	4.63	3.54	2.84	2.36	2.00	1.68	1.42	1.22	1.05	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.47	2.78	2.30	1.91	1.61	1.37	1.18	-	-	-	-
-2.00	5.00	5.00	5.00	4.53	3.44	2.72	2.21	1.84	1.55	1.34	-	-	-	-	-
-3.00	5.00	5.00	5.00	4.48	3.35	2.66	2.17	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Minimum Loads)	Hitch	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.79	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.83	2.35	1.98	-	-	-	-	-	-
6.00	-	-	-	-	-	-	2.80	2.33	1.98	1.69	1.46	-	-	-	-
5.00	-	-	-	-	-	3.32	2.70	2.26	1.92	1.66	1.44	1.26	-	-	-
4.00	-	5.00	5.00	5.00	3.91	3.11	2.56	2.15	1.84	1.59	1.39	1.23	1.08	-	-
3.00	-	5.00	4.82a	4.47	3.52	2.85	2.37	2.02	1.74	1.52	1.33	1.18	1.05	0.94	-
2.00	2.62a	2.65a	2.84a	3.01a	3.17	2.61	2.20	1.89	1.64	1.44	1.27	1.14	1.02	0.92	-
1.00	3.96a	3.04a	2.70a	2.65a	3.03	2.47	2.08	1.79	1.56	1.37	1.22	1.09	0.98	0.89	-
0.00	4.58a	3.67a	3.06a	3.80a	3.00	2.41	2.02	1.73	1.50	1.33	1.18	1.06	0.96	-	-
-1.00	5.00	5.00	5.00	3.99	3.00	2.40	1.99	1.70	1.48	1.30	1.16	1.05	0.95	-	-
-2.00	5.00	5.00	5.00	4.03	3.03	2.41	2.00	1.70	1.48	1.30	1.16	1.05	-	-	-
-3.00	5.00	5.00	5.00	4.12	3.10	2.46	2.03	1.73	1.50	1.33	-	-	-	-	-
-4.00	-	5.00	5.00	4.32	3.26	2.61	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BU (Maximum Loads)	Hitch	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.80	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.84	2.38	2.00	-	-	-	-	-	-
6.00	-	-	-	-	-	-	2.81	2.37	2.03	1.73	1.47	-	-	-	-
5.00	-	-	-	-	-	3.33	2.75	2.33	2.00	1.75	1.49	1.28	-	-	-
4.00	-	5.00	5.00	5.00	4.03	3.23	2.68	2.28	1.97	1.73	1.49	1.28	1.10	-	-
3.00	-	5.00	5.00	5.00	3.89	3.14	2.61	2.23	1.94	1.71	1.47	1.26	1.08	0.94	-
2.00	4.65a	5.00	5.00	4.97	3.81	3.08	2.57	2.20	1.92	1.68	1.43	1.23	1.06	0.92	-
1.00	4.86a	5.00	5.00	4.95	3.79	3.06	2.55	2.17	1.87	1.62	1.38	1.18	1.02	0.89	-
0.00	5.00	5.00	5.00	4.68	3.60	2.91	2.43	2.07	1.79	1.54	1.31	1.13	0.99	-	-
-1.00	5.00	5.00	5.00	4.53	3.47	2.81	2.34	2.00	1.70	1.45	1.25	1.08	0.95	-	-
-2.00	5.00	5.00	5.00	4.47	3.41	2.76	2.29	1.90	1.61	1.38	1.20	1.05	-	-	-
-3.00	5.00	5.00	5.00	4.49	3.36	2.66	2.18	1.83	1.56	1.35	-	-	-	-	-
-4.00	-	5.00	5.00	4.37	3.29	2.61	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Minimum Loads)	Tool Pin	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.16	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.32	2.69	2.22	-	-	-	-	-	-	-
6.00	-	-	-	-	-	3.29	2.68	2.22	1.88	1.60	-	-	-	-	-
5.00	-	-	-	5.36a	4.03	3.18	2.59	2.17	1.84	1.58	1.37	-	-	-	-
4.00	-	-	-	5.01	3.73	2.99	2.46	2.07	1.77	1.53	1.34	1.17	-	-	-
3.00	-	-	7.24	4.81	3.52	2.75	2.31	1.96	1.69	1.47	1.29	1.14	1.01	-	-
2.00	-	-	4.07a	4.09a	3.35	2.60	2.16	1.86	1.61	1.41	1.25	1.11	0.99	-	-
1.00	-	3.34a	3.30a	3.46a	3.20	2.49	2.09	1.78	1.55	1.36	1.21	1.08	0.97	-	-
0.00	4.61a	3.80a	3.43a	3.35a	3.12	2.47	2.05	1.75	1.51	1.33	1.18	1.06	0.95	-	-
-1.00	6.28a	5.57a	5.16a	4.19	3.12	2.48	2.05	1.74	1.50	1.32	1.17	1.06	-	-	-
-2.00	9.33a	9.13a	6.18	4.22	3.16	2.50	2.07	1.75	1.51	1.33	1.19	-	-	-	-
-3.00	10.00	10.00	6.31	4.33	3.25	2.58	2.13	1.81	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Maximum Loads)	Tool Pin	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.16	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.33	2.72	2.23	-	-	-	-	-	-	-
6.00	-	-	-	-	-	3.31	2.72	2.28	1.91	1.61	-	-	-	-	-
5.00	-	-	-	5.37a	4.08	3.25	2.68	2.26	1.94	1.64	1.39	-	-	-	-
4.00	-	-	-	5.22	3.97	3.18	2.63	2.23	1.93	1.65	1.40	1.19	-	-	-
3.00	-	-	7.26	5.08	3.88	3.12	2.59	2.21	1.92	1.63	1.39	1.18	1.02	-	-
2.00	-	-	7.21	5.03	3.84	3.09	2.57	2.20	1.88	1.60	1.36	1.17	1.00	-	-
1.00	-	4.31a	6.84	4.86	3.73	3.01	2.49	2.11	1.81	1.55	1.32	1.13	0.98	-	-
0.00	6.42a	7.69a	6.64	4.67	3.58	2.89	2.40	2.04	1.75	1.48	1.27	1.10	0.96	-	-
-1.00	9.84a	10.00	6.55	4.57	3.49	2.81	2.34	1.98	1.66	1.42	1.23	1.07	-	-	-
-2.00	10.00	10.00	6.54	4.55	3.46	2.79	2.28	1.90	1.60	1.37	1.20	-	-	-	-
-3.00	10.00	10.00	6.60	4.55	3.41	2.71	2.21	1.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.26	2.63	-	-	-	-	-	-	-	-
6.00	-	-	-	-	4.09	3.22	2.61	2.17	1.83	-	-	-	-	-	-
5.00	-	-	5.00	5.00	3.92	3.10	2.53	2.11	1.80	1.54	1.33	-	-	-	-
4.00	-	-	5.00	4.88	3.61	2.91	2.40	2.02	1.73	1.50	1.31	1.14	-	-	-
3.00	-	-	5.00	4.75	3.47	2.67	2.25	1.92	1.65	1.44	1.26	1.12	-	-	-
2.00	-	-	4.03a	4.03a	3.35	2.58	2.13	1.82	1.58	1.38	1.22	1.08	-	-	-
1.00	-	-	4.01a	3.90a	3.24	2.52	2.07	1.77	1.53	1.34	1.18	1.06	-	-	-
0.00	5.00	5.00	4.56a	4.14a	3.19	2.49	2.05	1.74	1.50	1.31	1.16	1.04	-	-	-
-1.00	5.00	5.00	5.00	4.27	3.17	2.50	2.05	1.73	1.49	1.31	1.16	-	-	-	-
-2.00	5.00	5.00	5.00	4.28	3.20	2.52	2.07	1.75	1.51	1.32	-	-	-	-	-
-3.00	5.00	5.00	5.00	4.38	3.29	2.61	2.15	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.28	2.65	-	-	-	-	-	-	-	-
6.00	-	-	-	-	4.10	3.26	2.68	2.23	1.85	-	-	-	-	-	-
5.00	-	-	5.00	5.00	4.01	3.20	2.64	2.23	1.88	1.58	1.34	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.13	2.60	2.21	1.89	1.59	1.34	1.14	-	-	-
3.00	-	-	5.00	5.00	3.84	3.08	2.56	2.18	1.87	1.57	1.33	1.13	-	-	-
2.00	-	-	5.00	5.00	3.81	3.06	2.55	2.15	1.83	1.54	1.30	1.11	-	-	-
1.00	-	-	5.00	4.78	3.67	2.95	2.44	2.07	1.77	1.49	1.26	1.08	-	-	-
0.00	5.00	5.00	5.00	4.63	3.54	2.84	2.36	2.00	1.68	1.42	1.22	1.05	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.47	2.78	2.30	1.91	1.61	1.37	1.18	-	-	-	-
-2.00	5.00	5.00	5.00	4.53	3.44	2.72	2.21	1.84	1.55	1.34	-	-	-	-	-
-3.00	5.00	5.00	5.00	4.48	3.35	2.66	2.17	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Minimum Loads)	Hitch	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.79	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.83	2.35	1.98	-	-	-	-	-	-
6.00	-	-	-	-	-	-	2.80	2.33	1.98	1.69	1.46	-	-	-	-
5.00	-	-	-	-	-	3.32	2.70	2.26	1.92	1.66	1.44	1.26	-	-	-
4.00	-	5.00	5.00	5.00	3.91	3.11	2.56	2.15	1.84	1.59	1.39	1.23	1.08	-	-
3.00	-	5.00	4.82a	4.47	3.52	2.85	2.37	2.02	1.74	1.52	1.33	1.18	1.05	0.94	-
2.00	2.62a	2.65a	2.84a	3.01a	3.17	2.61	2.20	1.89	1.64	1.44	1.27	1.14	1.02	0.92	-
1.00	3.96a	3.04a	2.70a	2.65a	3.03	2.47	2.08	1.79	1.56	1.37	1.22	1.09	0.98	0.89	-
0.00	4.58a	3.67a	3.06a	3.80a	3.00	2.41	2.02	1.73	1.50	1.33	1.18	1.06	0.96	-	-
-1.00	5.00	5.00	5.00	3.99	3.00	2.40	1.99	1.70	1.48	1.30	1.16	1.05	0.95	-	-
-2.00	5.00	5.00	5.00	4.03	3.03	2.41	2.00	1.70	1.48	1.30	1.16	1.05	-	-	-
-3.00	5.00	5.00	5.00	4.12	3.10	2.46	2.03	1.73	1.50	1.33	-	-	-	-	-
-4.00	-	5.00	5.00	4.32	3.26	2.61	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CU (Maximum Loads)	Hitch	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.80	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.84	2.38	2.00	-	-	-	-	-	-
6.00	-	-	-	-	-	-	2.81	2.37	2.03	1.73	1.47	-	-	-	-
5.00	-	-	-	-	-	3.33	2.75	2.33	2.00	1.75	1.49	1.28	-	-	-
4.00	-	5.00	5.00	5.00	4.03	3.23	2.68	2.28	1.97	1.73	1.49	1.28	1.10	-	-
3.00	-	5.00	5.00	5.00	3.89	3.14	2.61	2.23	1.94	1.71	1.47	1.26	1.08	0.94	-
2.00	4.65a	5.00	5.00	4.97	3.81	3.08	2.57	2.20	1.92	1.68	1.43	1.23	1.06	0.92	-
1.00	4.86a	5.00	5.00	4.95	3.79	3.06	2.55	2.17	1.87	1.62	1.38	1.18	1.02	0.89	-
0.00	5.00	5.00	5.00	4.68	3.60	2.91	2.43	2.07	1.79	1.54	1.31	1.13	0.99	-	-
-1.00	5.00	5.00	5.00	4.53	3.47	2.81	2.34	2.00	1.70	1.45	1.25	1.08	0.95	-	-
-2.00	5.00	5.00	5.00	4.47	3.41	2.76	2.29	1.90	1.61	1.38	1.20	1.05	-	-	-
-3.00	5.00	5.00	5.00	4.49	3.36	2.66	2.18	1.83	1.56	1.35	-	-	-	-	-
-4.00	-	5.00	5.00	4.37	3.29	2.61	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Minimum Loads)	Tool Pin	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.75a	3.71a	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.27a	3.57a	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.12a	3.56a	3.61a	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.46b	3.70a	3.43a	3.84a	3.46a	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.91b	4.13b	4.06a	4.09a	3.43a	3.63a	-	-
1.00	-	1.51a	3.30a	3.46a	3.55a	3.89a	5.84b	5.40b	5.30b	4.21a	4.31a	4.30a	4.03a	-	-
0.00	2.15a	1.74a	3.43a	3.35a	3.42a	5.98a	7.67b	6.88b	5.88a	5.08a	4.38a	4.19a	3.96a	-	-
-1.00	3.04a	2.67a	5.16a	5.19a	6.27a	9.29a	8.82b	7.91b	7.12b	6.08a	5.34a	5.09	-	-	-
-2.00	4.65a	4.55a	9.27a	9.90a	10.00	8.58b	7.89b	7.10b	6.39b	5.64b	4.87b	-	-	-	-
-3.00	7.39a	7.72a	10.00	10.00	10.00	8.54b	7.29b	6.36b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Maximum Loads)	Tool Pin	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.27a	4.88a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.35a	5.36a	5.20a	4.62a	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.98a	5.94b	5.63b	5.37b	4.99a	-	-	-	-
4.00	-	-	-	10.00	9.87b	8.37b	7.36b	6.66b	6.11b	5.71b	5.41b	5.07a	-	-	-
3.00	-	-	8.84a	10.00	10.00	10.00	8.49b	7.49b	6.69b	6.15b	5.68b	5.21	4.29a	-	-
2.00	-	-	10.00	10.00	10.00	10.00	9.43b	8.14b	7.22b	6.51b	5.83	5.20	4.63	-	-
1.00	-	2.03a	8.49a	10.00	10.00	10.00	9.71b	8.48b	7.50b	6.60	5.83	5.17	4.61	-	-
0.00	3.12a	3.80a	10.00	10.00	10.00	10.00	9.74b	8.51b	7.55b	6.64b	5.82	5.13	4.58	-	-
-1.00	4.92a	5.87a	10.00	10.00	10.00	10.00	9.82b	8.59b	7.63b	6.63	5.77	5.10	-	-	-
-2.00	7.12a	8.58a	10.00	10.00	10.00	10.00	10.00	8.73b	7.50b	6.35b	5.06b	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	10.00	10.00	8.84b	7.06b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.99a	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.79a	3.69a	3.98a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.84b	3.73a	3.99a	3.96a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.92b	4.24a	4.07a	4.11a	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	4.43b	4.66b	4.63a	4.86a	4.66a	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	5.00	5.00	4.95a	4.99a	5.00	4.78a	-	-	-
0.00	3.48a	2.53a	4.56a	4.14a	3.82a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	4.15a	3.67a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.35a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	3.96a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
0.00	3.84a	4.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Minimum Loads)	Hitch	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.45a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.16b	2.48a	2.65a	2.65a	-	-
3.00	-	2.55a	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.50b	3.13b	2.80a	2.70a	2.84a	2.60a	-
2.00	1.20a	1.23a	2.84a	3.01a	4.92a	5.00	4.49b	3.92b	3.47b	3.26a	2.95a	2.94a	2.94a	2.87a	-
1.00	1.86a	1.38a	2.70a	2.65a	4.27a	5.00	4.60b	4.34b	4.32b	3.59a	3.21a	3.54a	3.36a	3.05a	-
0.00	2.18a	1.71a	3.06a	3.80a	5.00	5.00	5.00	5.00	5.00	4.15a	4.03a	3.95a	3.52a	-	-
-1.00	2.83a	2.64a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.78a	4.12a	-	-
-2.00	3.87a	3.87a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85b	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DU (Maximum Loads)	Hitch	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	4.13a	3.80a	3.15a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.80a	4.71a	4.50a	4.08a	3.41a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.94a	4.27a	3.34a	-	-
3.00	-	4.09a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.19a	2.60a	-
2.00	2.31a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.66	3.11a	-
1.00	2.38a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.64	3.33a	-
0.00	3.47a	4.48a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.61	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.12a	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85b	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Minimum Loads)	Tool Pin	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.75a	3.71a	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.27a	3.57a	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.12a	3.56a	3.22	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.46b	3.70a	3.43a	3.18	2.84	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.91b	4.13b	4.06	3.55	3.14	2.81	-	-
1.00	-	1.51a	3.30a	3.46a	3.55a	3.89a	5.84b	5.40b	4.64	4.00	3.50	3.11	2.79	-	-
0.00	2.15a	1.74a	3.43a	3.35a	3.42a	5.98a	6.67	5.44	4.59	3.96	3.47	3.09	2.77	-	-
-1.00	3.04a	2.67a	5.16a	5.19a	6.27a	8.59	6.66	5.43	4.57	3.94	3.46	3.08	-	-	-
-2.00	4.65a	4.55a	9.27a	9.90a	10.00	8.58b	6.69	5.45	4.59	3.96	3.48	-	-	-	-
-3.00	7.39a	7.72a	10.00	10.00	10.00	8.54b	6.78	5.53	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Maximum Loads)	Tool Pin	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.27a	4.88a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.35a	5.36a	5.06	4.29	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.98a	5.94b	5.04b	4.33	3.72	-	-	-	-
4.00	-	-	-	10.00	9.87b	8.37b	7.25	5.94	5.00	4.32	3.73	3.25	-	-	-
3.00	-	-	8.84a	10.00	10.00	9.12	7.17	5.88b	4.97	4.30	3.71	3.23	2.85	-	-
2.00	-	-	10.00	10.00	10.00	9.07	7.13	5.86	4.96	4.28	3.68	3.21	2.83	-	-
1.00	-	2.03a	8.49a	10.00	10.00	9.09	7.14	5.87	4.96	4.22	3.63	3.17	2.80	-	-
0.00	3.12a	3.80a	10.00	10.00	10.00	9.15b	7.15	5.83	4.89	4.15	3.58	3.13	2.78	-	-
-1.00	4.92a	5.87a	10.00	10.00	10.00	9.09	7.07	5.75	4.78	4.07	3.53	3.10	-	-	-
-2.00	7.12a	8.58a	10.00	10.00	10.00	9.05	6.98	5.64	4.69	4.01	3.49	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	10.00	8.93	6.89	5.57	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.99a	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.79a	3.69a	3.66	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.84b	3.73a	3.62	3.19	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.92b	4.09	3.57	3.15	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	4.43b	4.66b	4.02	3.52	3.12	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	5.00	5.00	4.61	3.97	3.48	3.08	-	-	-
0.00	3.48a	2.53a	4.56a	4.14a	3.82a	5.00	5.00	5.00	4.57	3.94	3.45	3.07	-	-	-
-1.00	4.15a	3.67a	5.00	5.00	5.00	5.00	5.00	5.00	4.56	3.93	3.45	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.58	3.95	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.26	3.66	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.97	4.27	3.67	3.19	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.95	4.25	3.65	3.18	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.95	4.21	3.61	3.15	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.91	4.15	3.57	3.12	-	-	-
0.00	3.84a	4.45a	5.00	5.00	5.00	5.00	5.00	5.00	4.80	4.07	3.52	3.08	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.71	4.01	3.47	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.64	3.97	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Minimum Loads)	Hitch	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.45a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.16b	2.48a	2.65a	2.65a	-	-
3.00	-	2.55a	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.50b	3.13b	2.80a	2.70a	2.84a	2.60	-
2.00	1.20a	1.23a	2.84a	3.01a	4.92a	5.00	4.49b	3.92b	3.47b	3.26a	2.95a	2.94a	2.85	2.57	-
1.00	1.86a	1.38a	2.70a	2.65a	4.27a	5.00	4.60b	4.34b	4.32b	3.59a	3.21a	3.13	2.81	2.54	-
0.00	2.18a	1.71a	3.06a	3.80a	5.00	5.00	5.00	5.00	4.58	3.95	3.47	3.09	2.78	-	-
-1.00	2.83a	2.64a	5.00	5.00	5.00	5.00	5.00	5.00	4.54	3.93	3.45	3.08	2.77	-	-
-2.00	3.87a	3.87a	5.00	5.00	5.00	5.00	5.00	5.00	4.54	3.92	3.45	3.08	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.57	3.95	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EU (Maximum Loads)	Hitch	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	4.13a	3.80a	3.15a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.80a	4.71a	4.37	3.80	3.33	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.36	3.80	3.33	2.93	-	-
3.00	-	4.09a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.32	3.79	3.31	2.92	2.60	-
2.00	2.31a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	4.96	4.31	3.75	3.27	2.90	2.58	-
1.00	2.38a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	4.96	4.29	3.70	3.23	2.85	2.55	-
0.00	3.47a	4.48a	5.00	5.00	5.00	5.00	5.00	5.00	4.94	4.20	3.63	3.17	2.81	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.83	4.10	3.55	3.12	2.77	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.71	4.02	3.50	3.08	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.65	3.98	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Minimum Loads)	Tool Pin	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.75a	3.71a	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.27a	3.57a	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.12a	3.56a	3.61a	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.46b	3.70a	3.43a	3.84a	3.46a	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.91b	4.13b	4.06a	4.09a	3.43a	3.63a	-	-
1.00	-	1.51a	3.30a	3.46a	3.55a	3.89a	5.84b	5.40b	5.30b	4.21a	4.31a	4.30a	4.03a	-	-
0.00	2.15a	1.74a	3.43a	3.35a	3.42a	5.98a	7.67b	6.88b	5.88a	5.08a	4.38a	4.19a	3.96a	-	-
-1.00	3.04a	2.67a	5.16a	5.19a	6.27a	9.29a	8.82b	7.91b	7.12b	6.08a	5.34a	5.09	-	-	-
-2.00	4.65a	4.55a	9.27a	9.90a	10.00	8.58b	7.89b	7.10b	6.39b	5.64b	4.87b	-	-	-	-
-3.00	7.39a	7.72a	10.00	10.00	10.00	8.54b	7.29b	6.36b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Maximum Loads)	Tool Pin	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.27a	4.88a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.35a	5.36a	5.20a	4.62a	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.98a	5.94b	5.63b	5.37b	4.99a	-	-	-	-
4.00	-	-	-	10.00	9.87b	8.37b	7.36b	6.66b	6.11b	5.71b	5.41b	5.07a	-	-	-
3.00	-	-	8.84a	10.00	10.00	10.00	8.49b	7.49b	6.69b	6.15b	5.68b	5.21	4.29a	-	-
2.00	-	-	10.00	10.00	10.00	10.00	9.43b	8.14b	7.22b	6.51b	5.83	5.20	4.63	-	-
1.00	-	2.03a	8.49a	10.00	10.00	10.00	9.71b	8.48b	7.50b	6.60	5.83	5.17	4.61	-	-
0.00	3.12a	3.80a	10.00	10.00	10.00	10.00	9.74b	8.51b	7.55b	6.64b	5.82	5.13	4.58	-	-
-1.00	4.92a	5.87a	10.00	10.00	10.00	10.00	9.82b	8.59b	7.63b	6.63	5.77	5.10	-	-	-
-2.00	7.12a	8.58a	10.00	10.00	10.00	10.00	10.00	8.73b	7.50b	6.35b	5.06b	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	10.00	10.00	8.84b	7.06b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.99a	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.79a	3.69a	3.98a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.84b	3.73a	3.99a	3.96a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.92b	4.24a	4.07a	4.11a	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	4.43b	4.66b	4.63a	4.86a	4.66a	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	5.00	5.00	4.95a	4.99a	5.00	4.78a	-	-	-
0.00	3.48a	2.53a	4.56a	4.14a	3.82a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	4.15a	3.67a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.35a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	3.96a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
0.00	3.84a	4.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Minimum Loads)	Hitch	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.45a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.16b	2.48a	2.65a	2.65a	-	-
3.00	-	2.55a	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.50b	3.13b	2.80a	2.70a	2.84a	2.60a	-
2.00	1.20a	1.23a	2.84a	3.01a	4.92a	5.00	4.49b	3.92b	3.47b	3.26a	2.95a	2.94a	2.94a	2.87a	-
1.00	1.86a	1.38a	2.70a	2.65a	4.27a	5.00	4.60b	4.34b	4.32b	3.59a	3.21a	3.54a	3.36a	3.05a	-
0.00	2.18a	1.71a	3.06a	3.80a	5.00	5.00	5.00	5.00	5.00	4.15a	4.03a	3.95a	3.52a	-	-
-1.00	2.83a	2.64a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.78a	4.12a	-	-
-2.00	3.87a	3.87a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85b	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1AL (Maximum Loads)	Hitch	ROAD	+/- 10° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	4.13a	3.80a	3.15a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.80a	4.71a	4.50a	4.08a	3.41a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.94a	4.27a	3.34a	-	-
3.00	-	4.09a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.19a	2.60a	-
2.00	2.31a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.66	3.11a	-
1.00	2.38a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.64	3.33a	-
0.00	3.47a	4.48a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.61	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.12a	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85b	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Minimum Loads)	Tool Pin	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.61	3.09	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.07	2.67	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.01	2.63	2.32	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.39	2.94	2.58	2.29	2.04	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.86	3.30	2.87	2.53	2.25	2.02	-	-
1.00	-	3.34a	3.30a	3.46a	3.55a	3.89a	4.51	3.77	3.23	2.82	2.48	2.22	1.99	-	-
0.00	2.15a	3.80a	3.43a	3.35a	3.42a	5.56	4.47	3.73	3.19	2.78	2.46	2.20	1.98	-	-
-1.00	3.04a	5.57a	5.16a	5.19a	6.27a	5.57	4.46	3.72	3.18	2.77	2.45	2.19	-	-	-
-2.00	4.65a	9.13a	9.27a	9.90a	7.41	5.60	4.49	3.73	3.19	2.78	2.46	-	-	-	-
-3.00	7.39a	10.00	10.00	10.00	7.53	5.70	4.56	3.80	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Maximum Loads)	Tool Pin	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.24	4.30	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.25	4.34	3.65	3.10	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.20	4.32	3.68	3.13	2.69	-	-	-	-
4.00	-	-	-	10.00	8.32	6.37	5.13	4.28	3.66	3.14	2.70	2.35	-	-	-
3.00	-	-	8.84a	10.00	8.20	6.29	5.08	4.25	3.64	3.12	2.69	2.33	2.05	-	-
2.00	-	-	10.00	10.00	8.15	6.25	5.05	4.24	3.61	3.09	2.65	2.32	2.03	-	-
1.00	-	4.31a	8.49a	10.00	8.16	6.24	5.01	4.16	3.53	3.03	2.61	2.28	2.01	-	-
0.00	3.12a	7.69a	10.00	10.00	7.97	6.08	4.89	4.07	3.46	2.95	2.56	2.24	1.98	-	-
-1.00	4.92a	10.00	10.00	10.00	7.85	5.99	4.82	4.00	3.36	2.88	2.51	2.21	-	-	-
-2.00	7.12a	10.00	10.00	10.00	7.81	5.96	4.74	3.91	3.29	2.83	2.47	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	7.74	5.86	4.66	3.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.56	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.52	3.02	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.44	2.97	2.60	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.35	2.90	2.55	2.26	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	3.82	3.27	2.84	2.50	2.23	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	4.49	3.75	3.21	2.79	2.46	2.20	-	-	-
0.00	3.48a	5.00	4.56a	4.14a	3.82a	5.00	4.47	3.72	3.17	2.76	2.44	2.18	-	-	-
-1.00	4.15a	5.00	5.00	5.00	5.00	5.00	4.47	3.71	3.17	2.76	2.44	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.49	3.73	3.18	2.77	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.59	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	4.29	3.58	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	4.28	3.62	3.07	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	4.25	3.62	3.07	2.64	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	4.22b	3.60	3.05	2.63	2.28	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	4.20	3.55	3.01	2.59	2.26	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	4.94	4.11	3.48	2.96	2.55	2.23	-	-	-
0.00	3.84a	5.00	5.00	5.00	5.00	5.00	4.85	4.02	3.39	2.89	2.50	2.19	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.77	3.93	3.30	2.83	2.46	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.67	3.84	3.24	2.80	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.62	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Minimum Loads)	Hitch	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.42	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.08	2.48a	2.39	2.13	-	-
3.00	-	5.00	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.45	2.99	2.63	2.33	2.09	1.88	-
2.00	1.20a	2.65a	2.84a	3.01a	4.92a	5.00	4.49b	3.90	3.33	2.90	2.56	2.28	2.05	1.86	-
1.00	1.86a	3.04a	2.70a	2.65a	4.27a	5.00	4.51	3.78	3.24	2.83	2.50	2.23	2.02	1.83	-
0.00	2.18a	3.67a	3.06a	3.80a	5.00	5.00	4.43	3.71	3.18	2.78	2.46	2.20	1.99	-	-
-1.00	2.83a	5.00	5.00	5.00	5.00	5.00	4.40	3.67	3.15	2.75	2.44	2.19	1.98	-	-
-2.00	3.87a	5.00	5.00	5.00	5.00	5.00	4.41	3.67	3.15	2.75	2.44	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.45	3.71	3.18	2.78	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1BL (Maximum Loads)	Hitch	ROAD	+/- 10° - +/- 45° Over Osc End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	3.76	3.22	2.78	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.39	3.74	3.24	2.80	2.44	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.33	3.70	3.23	2.80	2.44	2.14	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.27	3.66	3.21	2.78	2.42	2.12	1.88	-
2.00	2.31a	5.00	5.00	5.00	5.00	5.00	5.00	4.24	3.64	3.18	2.74	2.39	2.10	1.86	-
1.00	2.38a	5.00	5.00	5.00	5.00	5.00	5.00	4.22	3.59	3.11	2.68	2.33	2.06	1.83	-
0.00	3.47a	5.00	5.00	5.00	5.00	5.00	4.92	4.11	3.51	3.02	2.61	2.28	2.02	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	4.82	4.03	3.41	2.92	2.53	2.23	1.98	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.76	3.91	3.30	2.84	2.48	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	3.82	3.24	2.80	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Minimum Loads)	Tool Pin	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.61	3.09	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.07	2.67	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.01	2.63	2.32	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.39	2.94	2.58	2.29	2.04	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.86	3.30	2.87	2.53	2.25	2.02	-	-
1.00	-	3.34a	3.30a	3.46a	3.55a	3.89a	4.51	3.77	3.23	2.82	2.48	2.22	1.99	-	-
0.00	2.15a	3.80a	3.43a	3.35a	3.42a	5.56	4.47	3.73	3.19	2.78	2.46	2.20	1.98	-	-
-1.00	3.04a	5.57a	5.16a	5.19a	6.27a	5.57	4.46	3.72	3.18	2.77	2.45	2.19	-	-	-
-2.00	4.65a	9.13a	9.27a	9.90a	7.41	5.60	4.49	3.73	3.19	2.78	2.46	-	-	-	-
-3.00	7.39a	10.00	10.00	10.00	7.53	5.70	4.56	3.80	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Maximum Loads)	Tool Pin	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.24	4.30	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.25	4.34	3.65	3.10	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.20	4.32	3.68	3.13	2.69	-	-	-	-
4.00	-	-	-	10.00	8.32	6.37	5.13	4.28	3.66	3.14	2.70	2.35	-	-	-
3.00	-	-	8.84a	10.00	8.20	6.29	5.08	4.25	3.64	3.12	2.69	2.33	2.05	-	-
2.00	-	-	10.00	10.00	8.15	6.25	5.05	4.24	3.61	3.09	2.65	2.32	2.03	-	-
1.00	-	4.31a	8.49a	10.00	8.16	6.24	5.01	4.16	3.53	3.03	2.61	2.28	2.01	-	-
0.00	3.12a	7.69a	10.00	10.00	7.97	6.08	4.89	4.07	3.46	2.95	2.56	2.24	1.98	-	-
-1.00	4.92a	10.00	10.00	10.00	7.85	5.99	4.82	4.00	3.36	2.88	2.51	2.21	-	-	-
-2.00	7.12a	10.00	10.00	10.00	7.81	5.96	4.74	3.91	3.29	2.83	2.47	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	7.74	5.86	4.66	3.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.56	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.52	3.02	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.44	2.97	2.60	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.35	2.90	2.55	2.26	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	3.82	3.27	2.84	2.50	2.23	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	4.49	3.75	3.21	2.79	2.46	2.20	-	-	-
0.00	3.48a	5.00	4.56a	4.14a	3.82a	5.00	4.47	3.72	3.17	2.76	2.44	2.18	-	-	-
-1.00	4.15a	5.00	5.00	5.00	5.00	5.00	4.47	3.71	3.17	2.76	2.44	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.49	3.73	3.18	2.77	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.59	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	4.29	3.58	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	4.28	3.62	3.07	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	4.25	3.62	3.07	2.64	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	4.22b	3.60	3.05	2.63	2.28	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	4.20	3.55	3.01	2.59	2.26	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	4.94	4.11	3.48	2.96	2.55	2.23	-	-	-
0.00	3.84a	5.00	5.00	5.00	5.00	5.00	4.85	4.02	3.39	2.89	2.50	2.19	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.77	3.93	3.30	2.83	2.46	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.67	3.84	3.24	2.80	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.62	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Minimum Loads)	Hitch	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.42	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.08	2.48a	2.39	2.13	-	-
3.00	-	5.00	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.45	2.99	2.63	2.33	2.09	1.88	-
2.00	1.20a	2.65a	2.84a	3.01a	4.92a	5.00	4.49b	3.90	3.33	2.90	2.56	2.28	2.05	1.86	-
1.00	1.86a	3.04a	2.70a	2.65a	4.27a	5.00	4.51	3.78	3.24	2.83	2.50	2.23	2.02	1.83	-
0.00	2.18a	3.67a	3.06a	3.80a	5.00	5.00	4.43	3.71	3.18	2.78	2.46	2.20	1.99	-	-
-1.00	2.83a	5.00	5.00	5.00	5.00	5.00	4.40	3.67	3.15	2.75	2.44	2.19	1.98	-	-
-2.00	3.87a	5.00	5.00	5.00	5.00	5.00	4.41	3.67	3.15	2.75	2.44	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.45	3.71	3.18	2.78	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1CL (Maximum Loads)	Hitch	ROAD	+/- 45° - +/- 135°		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	3.76	3.22	2.78	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.39	3.74	3.24	2.80	2.44	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.33	3.70	3.23	2.80	2.44	2.14	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.27	3.66	3.21	2.78	2.42	2.12	1.88	-
2.00	2.31a	5.00	5.00	5.00	5.00	5.00	5.00	4.24	3.64	3.18	2.74	2.39	2.10	1.86	-
1.00	2.38a	5.00	5.00	5.00	5.00	5.00	5.00	4.22	3.59	3.11	2.68	2.33	2.06	1.83	-
0.00	3.47a	5.00	5.00	5.00	5.00	5.00	4.92	4.11	3.51	3.02	2.61	2.28	2.02	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	4.82	4.03	3.41	2.92	2.53	2.23	1.98	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.76	3.91	3.30	2.84	2.48	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	3.82	3.24	2.80	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Minimum Loads)	Tool Pin	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.61	3.09	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.07	2.67	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.01	2.63	2.32	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.39	2.94	2.58	2.29	2.04	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.86	3.30	2.87	2.53	2.25	2.02	-	-
1.00	-	3.34a	3.30a	3.46a	3.55a	3.89a	4.51	3.77	3.23	2.82	2.48	2.22	1.99	-	-
0.00	2.15a	3.80a	3.43a	3.35a	3.42a	5.56	4.47	3.73	3.19	2.78	2.46	2.20	1.98	-	-
-1.00	3.04a	5.57a	5.16a	5.19a	6.27a	5.57	4.46	3.72	3.18	2.77	2.45	2.19	-	-	-
-2.00	4.65a	9.13a	9.27a	9.90a	7.41	5.60	4.49	3.73	3.19	2.78	2.46	-	-	-	-
-3.00	7.39a	10.00	10.00	10.00	7.53	5.70	4.56	3.80	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Maximum Loads)	Tool Pin	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.24	4.30	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.25	4.34	3.65	3.10	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.20	4.32	3.68	3.13	2.69	-	-	-	-
4.00	-	-	-	10.00	8.32	6.37	5.13	4.28	3.66	3.14	2.70	2.35	-	-	-
3.00	-	-	8.84a	10.00	8.20	6.29	5.08	4.25	3.64	3.12	2.69	2.33	2.05	-	-
2.00	-	-	10.00	10.00	8.15	6.25	5.05	4.24	3.61	3.09	2.65	2.32	2.03	-	-
1.00	-	4.31a	8.49a	10.00	8.16	6.24	5.01	4.16	3.53	3.03	2.61	2.28	2.01	-	-
0.00	3.12a	7.69a	10.00	10.00	7.97	6.08	4.89	4.07	3.46	2.95	2.56	2.24	1.98	-	-
-1.00	4.92a	10.00	10.00	10.00	7.85	5.99	4.82	4.00	3.36	2.88	2.51	2.21	-	-	-
-2.00	7.12a	10.00	10.00	10.00	7.81	5.96	4.74	3.91	3.29	2.83	2.47	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	7.74	5.86	4.66	3.84	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.56	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.52	3.02	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.44	2.97	2.60	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.35	2.90	2.55	2.26	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	3.82	3.27	2.84	2.50	2.23	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	4.49	3.75	3.21	2.79	2.46	2.20	-	-	-
0.00	3.48a	5.00	4.56a	4.14a	3.82a	5.00	4.47	3.72	3.17	2.76	2.44	2.18	-	-	-
-1.00	4.15a	5.00	5.00	5.00	5.00	5.00	4.47	3.71	3.17	2.76	2.44	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.49	3.73	3.18	2.77	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.59	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	4.29	3.58	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	4.28	3.62	3.07	2.63	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	4.25	3.62	3.07	2.64	2.29	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	4.22b	3.60	3.05	2.63	2.28	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	4.20	3.55	3.01	2.59	2.26	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	4.94	4.11	3.48	2.96	2.55	2.23	-	-	-
0.00	3.84a	5.00	5.00	5.00	5.00	5.00	4.85	4.02	3.39	2.89	2.50	2.19	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.77	3.93	3.30	2.83	2.46	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.67	3.84	3.24	2.80	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.62	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Minimum Loads)	Hitch	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.42	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.08	2.48a	2.39	2.13	-	-
3.00	-	5.00	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.45	2.99	2.63	2.33	2.09	1.88	-
2.00	1.20a	2.65a	2.84a	3.01a	4.92a	5.00	4.49b	3.90	3.33	2.90	2.56	2.28	2.05	1.86	-
1.00	1.86a	3.04a	2.70a	2.65a	4.27a	5.00	4.51	3.78	3.24	2.83	2.50	2.23	2.02	1.83	-
0.00	2.18a	3.67a	3.06a	3.80a	5.00	5.00	4.43	3.71	3.18	2.78	2.46	2.20	1.99	-	-
-1.00	2.83a	5.00	5.00	5.00	5.00	5.00	4.40	3.67	3.15	2.75	2.44	2.19	1.98	-	-
-2.00	3.87a	5.00	5.00	5.00	5.00	5.00	4.41	3.67	3.15	2.75	2.44	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.45	3.71	3.18	2.78	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1DL (Maximum Loads)	Hitch	ROAD	+/- 135° - +/- 160° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	3.76	3.22	2.78	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.39	3.74	3.24	2.80	2.44	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.33	3.70	3.23	2.80	2.44	2.14	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	5.00	4.27	3.66	3.21	2.78	2.42	2.12	1.88	-
2.00	2.31a	5.00	5.00	5.00	5.00	5.00	5.00	4.24	3.64	3.18	2.74	2.39	2.10	1.86	-
1.00	2.38a	5.00	5.00	5.00	5.00	5.00	5.00	4.22	3.59	3.11	2.68	2.33	2.06	1.83	-
0.00	3.47a	5.00	5.00	5.00	5.00	5.00	4.92	4.11	3.51	3.02	2.61	2.28	2.02	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	4.82	4.03	3.41	2.92	2.53	2.23	1.98	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.76	3.91	3.30	2.84	2.48	2.19	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	3.82	3.24	2.80	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Minimum Loads)	Tool Pin	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.47a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	4.58a	4.08a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18a	4.76b	4.07b	3.75a	3.71a	-	-	-	-	-
5.00	-	-	-	5.36a	5.67a	5.56b	4.70b	4.04b	3.51b	3.27a	3.57a	-	-	-	-
4.00	-	-	-	8.19b	6.56b	5.44b	4.61b	3.98b	3.48b	3.12a	3.56a	3.22	-	-	-
3.00	-	-	8.15a	7.19a	6.41b	5.33b	4.54b	3.93b	3.46b	3.70a	3.43a	3.18	2.84	-	-
2.00	-	-	4.07a	4.09a	4.44a	5.08a	4.50b	3.91b	4.13b	4.06	3.55	3.14	2.81	-	-
1.00	-	1.51a	3.30a	3.46a	3.55a	3.89a	5.84b	5.40b	4.64	4.00	3.50	3.11	2.79	-	-
0.00	2.15a	1.74a	3.43a	3.35a	3.42a	5.98a	6.67	5.44	4.59	3.96	3.47	3.09	2.77	-	-
-1.00	3.04a	2.67a	5.16a	5.19a	6.27a	8.59	6.66	5.43	4.57	3.94	3.46	3.08	-	-	-
-2.00	4.65a	4.55a	9.27a	9.90a	10.00	8.58b	6.69	5.45	4.59	3.96	3.48	-	-	-	-
-3.00	7.39a	7.72a	10.00	10.00	10.00	8.54b	6.78	5.53	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Maximum Loads)	Tool Pin	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.60a	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.35a	5.27a	4.88a	-	-	-	-	-	-	-
6.00	-	-	-	-	-	5.23a	5.35a	5.36a	5.06	4.29	-	-	-	-	-
5.00	-	-	-	5.37a	5.69a	5.89a	5.98a	5.94b	5.04b	4.33	3.72	-	-	-	-
4.00	-	-	-	10.00	9.87b	8.37b	7.25	5.94	5.00	4.32	3.73	3.25	-	-	-
3.00	-	-	8.84a	10.00	10.00	9.12	7.17	5.88b	4.97	4.30	3.71	3.23	2.85	-	-
2.00	-	-	10.00	10.00	10.00	9.07	7.13	5.86	4.96	4.28	3.68	3.21	2.83	-	-
1.00	-	2.03a	8.49a	10.00	10.00	9.09	7.14	5.87	4.96	4.22	3.63	3.17	2.80	-	-
0.00	3.12a	3.80a	10.00	10.00	10.00	9.15b	7.15	5.83	4.89	4.15	3.58	3.13	2.78	-	-
-1.00	4.92a	5.87a	10.00	10.00	10.00	9.09	7.07	5.75	4.78	4.07	3.53	3.10	-	-	-
-2.00	7.12a	8.58a	10.00	10.00	10.00	9.05	6.98	5.64	4.69	4.01	3.49	-	-	-	-
-3.00	9.81a	10.00	10.00	10.00	10.00	8.93	6.89	5.57	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Minimum Loads)	AUX LIFTING POINT	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.52a	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.69b	3.80a	3.99a	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.62b	3.98b	3.79a	3.69a	3.66	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54b	3.93b	3.84b	3.73a	3.62	3.19	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.48b	3.89b	3.92b	4.09	3.57	3.15	-	-	-
2.00	-	-	4.03a	4.03a	4.46a	4.61a	4.46b	4.43b	4.66b	4.02	3.52	3.12	-	-	-
1.00	-	-	4.01a	3.90a	3.95a	4.15a	5.00	5.00	4.61	3.97	3.48	3.08	-	-	-
0.00	3.48a	2.53a	4.56a	4.14a	3.82a	5.00	5.00	5.00	4.57	3.94	3.45	3.07	-	-	-
-1.00	4.15a	3.67a	5.00	5.00	5.00	5.00	5.00	5.00	4.56	3.93	3.45	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.58	3.95	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Maximum Loads)	AUX LIFTING POINT	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.26	3.66	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.97	4.27	3.67	3.19	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.95	4.25	3.65	3.18	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.95	4.21	3.61	3.15	-	-	-
1.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	4.91	4.15	3.57	3.12	-	-	-
0.00	3.84a	4.45a	5.00	5.00	5.00	5.00	5.00	5.00	4.80	4.07	3.52	3.08	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.71	4.01	3.47	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.64	3.97	-	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Minimum Loads)	Hitch	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.07a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.08a	3.36a	2.77a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28a	4.13a	3.37a	2.71a	2.69a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.74a	4.15b	3.62b	2.58a	2.57a	2.45a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.69b	4.06b	3.56b	3.16b	2.48a	2.65a	2.65a	-	-
3.00	-	2.55a	4.82a	5.00	5.00	5.00	4.57b	3.97b	3.50b	3.13b	2.80a	2.70a	2.84a	2.60	-
2.00	1.20a	1.23a	2.84a	3.01a	4.92a	5.00	4.49b	3.92b	3.47b	3.26a	2.95a	2.94a	2.85	2.57	-
1.00	1.86a	1.38a	2.70a	2.65a	4.27a	5.00	4.60b	4.34b	4.32b	3.59a	3.21a	3.13	2.81	2.54	-
0.00	2.18a	1.71a	3.06a	3.80a	5.00	5.00	5.00	5.00	4.58	3.95	3.47	3.09	2.78	-	-
-1.00	2.83a	2.64a	5.00	5.00	5.00	5.00	5.00	5.00	4.54	3.93	3.45	3.08	2.77	-	-
-2.00	3.87a	3.87a	5.00	5.00	5.00	5.00	5.00	5.00	4.54	3.92	3.45	3.08	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.57	3.95	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
1EL (Maximum Loads)	Hitch	ROAD	+/- 160° - +/- 180° Over Fixed End		71%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.25a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.10a	3.88a	3.46a	-	-	-	-	-	-
6.00	-	-	-	-	-	-	4.29a	4.26a	4.13a	3.80a	3.15a	-	-	-	-
5.00	-	-	-	-	-	4.69a	4.79a	4.80a	4.71a	4.37	3.80	3.33	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.36	3.80	3.33	2.93	-	-
3.00	-	4.09a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.32	3.79	3.31	2.92	2.60	-
2.00	2.31a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	4.96	4.31	3.75	3.27	2.90	2.58	-
1.00	2.38a	3.92a	5.00	5.00	5.00	5.00	5.00	5.00	4.96	4.29	3.70	3.23	2.85	2.55	-
0.00	3.47a	4.48a	5.00	5.00	5.00	5.00	5.00	5.00	4.94	4.20	3.63	3.17	2.81	-	-
-1.00	4.65a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.83	4.10	3.55	3.12	2.77	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.71	4.02	3.50	3.08	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.65	3.98	-	-	-	-	-
-4.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Minimum Loads)	Tool Pin	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.22	4.44	3.85	3.37	-	-	-	-	-	-
6.00	-	-	-	-	-	5.18	4.42	3.83	3.37	2.99	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.07	5.08	4.35	3.78	3.34	2.97	2.66	2.40	-	-	-
4.00	-	-	-	7.27	5.83	4.92	4.23	3.70	3.28	2.92	2.63	2.39	-	-	-
3.00	-	-	6.48a	6.32a	5.71	4.74	4.11	3.61	3.20	2.87	2.59	2.36	2.15	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.64	4.01	3.53	3.14	2.82	2.55	2.33	2.13	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.95	3.48	3.10	2.78	2.52	2.30	2.12	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.56	3.93	3.45	3.07	2.76	2.51	2.29	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.45	4.57	3.93	3.45	3.06	2.76	2.50	2.29	-	-	-
-2.00	10.00	10.00	8.75	6.76	5.48	4.59	3.95	3.46	3.08	2.77	-	-	-	-	-
-3.00	10.00	10.00	8.86	6.85	5.56	4.67	4.02	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Maximum Loads)	Tool Pin	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.18	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.22	4.47	3.86	3.37	-	-	-	-	-	-
6.00	-	-	-	-	-	5.20	4.46	3.89	3.41	3.01	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.13	5.15	4.43	3.87	3.43	3.03	2.69	2.40	-	-	-
4.00	-	-	-	7.42	6.05	5.10	4.39	3.85	3.41	3.03	2.69	2.41	-	-	-
3.00	-	-	8.59a	7.34	5.99	5.05	4.36	3.83	3.41	3.02	2.68	2.40	2.16	-	-
2.00	-	-	9.39	7.31	5.97	5.04	4.35	3.81	3.36	2.98	2.65	2.38	2.14	-	-
1.00	-	5.10a	8.87a	7.16	5.87	4.95	4.27	3.73	3.31	2.93	2.62	2.35	2.12	-	-
0.00	7.17a	8.50a	9.02	7.05	5.77	4.86	4.20	3.68	3.26	2.88	2.58	2.32	-	-	-
-1.00	10.00	10.00	8.97	6.99	5.71	4.82	4.16	3.63	3.19	2.83	2.54	2.29	-	-	-
-2.00	10.00	10.00	8.98	6.98	5.70	4.79	4.10	3.56	3.14	2.80	-	-	-	-	-
-3.00	10.00	10.00	9.01	6.95	5.65	4.72	4.06	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.40	3.81	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.37	3.79	3.33	2.96	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.30	3.74	3.30	2.94	2.64	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.86	4.18	3.66	3.24	2.89	2.61	2.36	-	-	-
3.00	-	-	5.00	5.00	5.00	4.70	4.06	3.57	3.17	2.85	2.57	2.33	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	3.98	3.50	3.12	2.80	2.53	2.31	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.94	3.46	3.08	2.77	2.51	2.29	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.58	3.93	3.44	3.06	2.75	2.49	2.28	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.58	3.94	3.44	3.06	2.75	2.49	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.61	3.96	3.46	3.07	2.77	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.70	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.42	3.81	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.43	3.85	3.36	2.96	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.39	3.84	3.38	2.98	2.65	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.36	3.82	3.38	2.98	2.64	2.37	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.34	3.81	3.37	2.96	2.63	2.36	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.31	3.77	3.33	2.93	2.60	2.34	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.91	4.23	3.70	3.27	2.88	2.57	2.31	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	4.83	4.17	3.65	3.20	2.83	2.54	2.29	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.79	4.12	3.57	3.14	2.79	2.51	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.74	4.05	3.52	3.11	2.77	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.70	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Minimum Loads)	Hitch	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	3.92	3.45	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.43	3.86	3.40	2.85a	2.61a	2.46	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.30	3.76	3.32	2.97	2.54a	2.43	2.22	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.81	4.16	3.65	3.24	2.91	2.63	2.39	2.19	2.01	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.64	4.03	3.55	3.16	2.84	2.58	2.35	2.16	1.99	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.55	3.94	3.47	3.10	2.79	2.53	2.32	2.13	1.97	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.51	3.90	3.43	3.06	2.76	2.51	2.29	2.11	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.50	3.89	3.42	3.04	2.74	2.49	2.28	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.52	3.90	3.42	3.05	2.74	2.50	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.57	3.93	3.45	3.07	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AU (Maximum Loads)	Hitch	RAIL	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	3.95	3.47	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	3.95	3.50	3.09	2.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.48	3.92	3.47	3.11	2.77	2.48	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.42	3.88	3.44	3.10	2.77	2.48	2.23	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.37	3.84	3.42	3.08	2.75	2.46	2.22	2.01	-
2.00	3.93a	5.00	5.00	5.00	5.00	5.00	4.34	3.82	3.41	3.05	2.72	2.43	2.19	1.99	-
1.00	5.00	5.00	5.00	5.00	5.00	4.99	4.30	3.77	3.35	3.00	2.66	2.39	2.16	1.97	-
0.00	5.00	5.00	5.00	5.00	5.00	4.88	4.22	3.70	3.29	2.93	2.61	2.35	2.13	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.81	4.15	3.65	3.21	2.85	2.56	2.31	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.78	4.10	3.56	3.14	2.80	2.52	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.70	4.02	3.51	3.11	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Minimum Loads)	Tool Pin	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.15	4.18	3.48	2.95	-	-	-	-	-	-
6.00	-	-	-	-	-	5.10	4.15	3.47	2.96	2.56	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	4.96	4.05	3.40	2.91	2.53	2.22	1.96	-	-	-
4.00	-	-	-	8.13b	5.99	4.76	3.91	3.30	2.84	2.48	2.19	1.94	-	-	-
3.00	-	-	6.48a	6.32a	5.81	4.51	3.75	3.19	2.76	2.42	2.14	1.91	1.71	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.38	3.62	3.09	2.68	2.36	2.09	1.87	1.69	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.56	3.03	2.63	2.31	2.06	1.85	1.67	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.28	3.53	3.00	2.60	2.29	2.04	1.83	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.45	4.29	3.53	2.99	2.59	2.28	2.03	1.83	-	-	-
-2.00	10.00	10.00	10.00	7.46	5.50	4.32	3.55	3.01	2.61	2.30	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.60	5.61	4.42	3.64	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Maximum Loads)	Tool Pin	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.10	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.16	4.21	3.50	2.95	-	-	-	-	-	-
6.00	-	-	-	-	-	5.12	4.20	3.53	3.01	2.58	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.33a	5.06	4.16	3.51	3.02	2.60	2.25	1.96	-	-	-
4.00	-	-	-	8.43	6.30	4.99	4.11	3.48	3.01	2.60	2.25	1.97	-	-	-
3.00	-	-	8.59a	8.31	6.21	4.93	4.07	3.46	3.00	2.58	2.24	1.96	1.72	-	-
2.00	-	-	10.00	8.27	6.18	4.91	4.06	3.43	2.95	2.55	2.20	1.93	1.70	-	-
1.00	-	5.10a	8.87a	8.07	6.04	4.80	3.96	3.34	2.88	2.49	2.16	1.90	1.68	-	-
0.00	7.17a	8.50a	10.00	7.90	5.90	4.68	3.87	3.28	2.82	2.43	2.12	1.86	-	-	-
-1.00	10.00	10.00	10.00	7.81	5.82	4.62	3.81	3.22	2.73	2.37	2.07	1.84	-	-	-
-2.00	10.00	10.00	10.00	7.81	5.80	4.58	3.74	3.13	2.68	2.33	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.75	5.73	4.49	3.69	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.12	3.43	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.09	3.42	2.91	2.52	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.88	3.99	3.35	2.87	2.49	2.19	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.67	3.85	3.25	2.80	2.44	2.15	1.91	-	-	-
3.00	-	-	5.00	5.00	5.00	4.46	3.70	3.15	2.72	2.38	2.11	1.88	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.38	3.59	3.06	2.65	2.33	2.07	1.85	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.54	3.01	2.61	2.29	2.04	1.83	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.30	3.53	2.99	2.58	2.27	2.02	1.82	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.31	3.53	2.99	2.58	2.27	2.02	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.34	3.56	3.01	2.60	2.29	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.47	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.15	3.44	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.16	3.49	2.95	2.52	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.12	3.48	2.97	2.54	2.20	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.94	4.07	3.45	2.97	2.54	2.20	1.92	-	-	-
3.00	-	-	5.00	5.00	5.00	4.90	4.04	3.44	2.95	2.52	2.18	1.91	-	-	-
2.00	-	-	5.00	5.00	5.00	4.88	4.01	3.38	2.90	2.48	2.15	1.89	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.74	3.91	3.30	2.83	2.43	2.11	1.85	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	4.64	3.83	3.24	2.75	2.37	2.07	1.83	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.59	3.77	3.14	2.68	2.32	2.04	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.51	3.68	3.08	2.64	2.30	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.47	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Minimum Loads)	Hitch	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.60	2.83a	2.65	-	-	-	-	-
6.00	-	-	-	-	-	-	4.27	3.57	3.05	2.54a	2.31	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.16	3.49	2.99	2.60	2.29	2.03	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.88	4.00	3.38	2.90	2.53	2.24	1.99	1.79	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.61	3.82	3.24	2.80	2.46	2.18	1.95	1.75	1.59	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.38	3.65	3.12	2.70	2.38	2.12	1.90	1.72	1.56	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.26	3.54	3.02	2.63	2.32	2.07	1.86	1.69	1.54	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.21	3.49	2.97	2.58	2.28	2.04	1.84	1.67	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.20	3.47	2.95	2.56	2.26	2.02	1.82	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.23	3.49	2.96	2.57	2.26	2.03	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.29	3.53	3.00	2.60	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BU (Maximum Loads)	Hitch	RAIL	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	3.63	3.09	2.65	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28	3.61	3.11	2.69	2.33	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.22	3.57	3.08	2.70	2.35	2.05	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.15	3.52	3.05	2.68	2.34	2.05	1.81	-	-
3.00	-	5.00	5.00	5.00	5.00	4.94	4.09	3.47	3.02	2.66	2.32	2.03	1.79	1.59	-
2.00	3.93a	5.00	5.00	5.00	5.00	4.89	4.05	3.45	3.00	2.63	2.28	1.99	1.76	1.57	-
1.00	5.00	5.00	5.00	5.00	5.00	4.85	4.00	3.39	2.93	2.56	2.22	1.95	1.73	1.54	-
0.00	5.00	5.00	5.00	5.00	5.00	4.70	3.89	3.30	2.86	2.48	2.15	1.90	1.69	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.61	3.81	3.24	2.77	2.39	2.10	1.85	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.57	3.74	3.13	2.68	2.33	2.05	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.46	3.65	3.07	2.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Minimum Loads)	Tool Pin	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.98	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.02	3.29	2.75	2.33	-	-	-	-	-	-
6.00	-	-	-	-	-	3.98	3.26	2.74	2.34	2.02	-	-	-	-	-
5.00	-	-	6.02a	6.07a	4.84	3.85	3.17	2.68	2.30	2.00	1.75	1.54	-	-	-
4.00	-	-	-	6.10	4.53	3.66	3.04	2.58	2.23	1.94	1.71	1.52	-	-	-
3.00	-	-	6.48a	5.91	4.37	3.43	2.89	2.47	2.15	1.89	1.67	1.49	1.33	-	-
2.00	-	-	3.75a	3.90a	4.22	3.31	2.77	2.38	2.07	1.83	1.63	1.46	1.31	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.23	2.71	2.32	2.02	1.79	1.59	1.43	1.29	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	3.22	2.68	2.29	2.00	1.76	1.57	1.41	-	-	-
-1.00	6.84a	6.24a	5.95a	5.36	4.04	3.23	2.68	2.29	1.99	1.76	1.57	1.42	-	-	-
-2.00	10.00	10.00	7.83	5.41	4.08	3.26	2.70	2.30	2.00	1.77	-	-	-	-	-
-3.00	10.00	10.00	7.99	5.52	4.19	3.35	2.79	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Maximum Loads)	Tool Pin	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.98	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.03	3.32	2.77	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	4.00	3.31	2.80	2.39	2.04	-	-	-	-	-
5.00	-	-	6.02a	6.25a	4.91	3.94	3.27	2.78	2.40	2.06	1.78	1.54	-	-	-
4.00	-	-	-	6.29	4.81	3.87	3.22	2.75	2.39	2.07	1.78	1.55	-	-	-
3.00	-	-	8.59a	6.19	4.74	3.82	3.19	2.73	2.38	2.05	1.77	1.54	1.34	-	-
2.00	-	-	8.79	6.15	4.71	3.80	3.18	2.70	2.33	2.01	1.73	1.51	1.33	-	-
1.00	-	5.10a	8.40	5.94	4.58	3.70	3.08	2.62	2.27	1.95	1.69	1.48	1.30	-	-
0.00	7.17a	8.50a	8.23	5.79	4.45	3.59	3.00	2.56	2.21	1.90	1.65	1.45	-	-	-
-1.00	10.00	10.00	8.16	5.72	4.38	3.53	2.95	2.50	2.13	1.84	1.61	1.42	-	-	-
-2.00	10.00	10.00	8.17	5.71	4.36	3.50	2.88	2.42	2.07	1.80	-	-	-	-	-
-3.00	10.00	10.00	8.22	5.67	4.29	3.42	2.83	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.97	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.96	3.24	2.70	-	-	-	-	-	-	-
6.00	-	-	-	-	4.93	3.91	3.20	2.69	2.30	1.98	-	-	-	-	-
5.00	-	-	5.00	5.00	4.74	3.78	3.11	2.63	2.25	1.96	1.72	-	-	-	-
4.00	-	-	5.00	5.00	4.43	3.58	2.98	2.53	2.19	1.91	1.68	1.49	-	-	-
3.00	-	-	5.00	5.00	4.34	3.39	2.84	2.43	2.11	1.85	1.64	1.46	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.31	2.74	2.35	2.05	1.80	1.60	1.44	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.25	2.69	2.30	2.00	1.77	1.57	1.41	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	3.24	2.68	2.28	1.98	1.75	1.56	1.40	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.08	3.25	2.69	2.28	1.98	1.74	1.56	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.12	3.28	2.71	2.30	2.00	1.77	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.23	3.39	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.97	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.98	3.26	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	4.94	3.95	3.27	2.76	2.33	1.99	-	-	-	-	-
5.00	-	-	5.00	5.00	4.85	3.89	3.23	2.75	2.35	2.01	1.73	-	-	-	-
4.00	-	-	5.00	5.00	4.76	3.83	3.19	2.72	2.35	2.01	1.73	1.50	-	-	-
3.00	-	-	5.00	5.00	4.70	3.79	3.16	2.71	2.33	1.99	1.71	1.49	-	-	-
2.00	-	-	5.00	5.00	4.69	3.78	3.14	2.66	2.29	1.95	1.68	1.47	-	-	-
1.00	-	5.00	5.00	5.00	4.51	3.65	3.04	2.58	2.22	1.89	1.64	1.44	-	-	-
0.00	5.00	5.00	5.00	5.00	4.41	3.55	2.96	2.52	2.14	1.84	1.60	1.41	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.35	3.50	2.91	2.43	2.07	1.79	1.57	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.31	3.44	2.82	2.37	2.04	1.77	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.25	3.39	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Minimum Loads)	Hitch	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.42	2.87	2.45	2.11	-	-	-	-	-
6.00	-	-	-	-	-	-	3.37	2.84	2.42	2.10	1.84	-	-	-	-
5.00	-	-	-	-	4.80a	3.98	3.27	2.76	2.37	2.06	1.81	1.60	-	-	-
4.00	-	5.00	5.00	5.00	4.70	3.77	3.12	2.65	2.28	2.00	1.76	1.57	1.40	-	-
3.00	-	4.06a	3.93a	4.47a	4.31	3.52	2.95	2.52	2.19	1.93	1.71	1.52	1.37	1.24	-
2.00	2.78a	2.62a	2.65a	2.91a	4.03	3.31	2.80	2.41	2.10	1.85	1.65	1.48	1.34	1.21	-
1.00	4.19a	3.17a	2.68a	2.66a	3.94	3.20	2.69	2.32	2.03	1.79	1.60	1.44	1.31	1.19	-
0.00	4.74a	3.98a	3.51a	4.25a	3.92	3.16	2.64	2.27	1.98	1.75	1.57	1.42	1.29	-	-
-1.00	5.00	5.00	5.00	5.00	3.92	3.15	2.63	2.25	1.96	1.74	1.56	1.41	-	-	-
-2.00	5.00	5.00	5.00	5.00	3.95	3.17	2.64	2.26	1.97	1.74	1.56	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.03	3.23	2.68	2.29	2.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CU (Maximum Loads)	Hitch	RAIL	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.40	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.42	2.89	2.47	2.11	-	-	-	-	-
6.00	-	-	-	-	-	-	3.39	2.87	2.48	2.15	1.86	-	-	-	-
5.00	-	-	-	-	4.80a	4.01	3.33	2.83	2.45	2.16	1.87	1.63	-	-	-
4.00	-	5.00	5.00	5.00	4.86	3.91	3.26	2.78	2.42	2.14	1.87	1.62	1.42	-	-
3.00	-	5.00	5.00	5.00	4.74	3.83	3.20	2.74	2.39	2.12	1.84	1.60	1.41	1.24	-
2.00	3.93a	5.00	5.00	5.00	4.67	3.78	3.17	2.72	2.38	2.09	1.80	1.57	1.38	1.22	-
1.00	5.00	5.00	5.00	5.00	4.64	3.74	3.12	2.67	2.31	2.03	1.75	1.53	1.35	1.19	-
0.00	5.00	5.00	5.00	5.00	4.46	3.61	3.02	2.58	2.24	1.95	1.69	1.48	1.31	-	-
-1.00	5.00	5.00	5.00	5.00	4.36	3.52	2.94	2.52	2.16	1.86	1.63	1.44	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.31	3.48	2.88	2.42	2.07	1.81	1.59	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.24	3.38	2.79	2.36	2.03	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Minimum Loads)	Tool Pin	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.15	4.18	3.48	2.95	-	-	-	-	-	-
6.00	-	-	-	-	-	5.10	4.15	3.47	2.96	2.56	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	4.96	4.05	3.40	2.91	2.53	2.22	1.96	-	-	-
4.00	-	-	-	8.13b	5.99	4.76	3.91	3.30	2.84	2.48	2.19	1.94	-	-	-
3.00	-	-	6.48a	6.32a	5.81	4.51	3.75	3.19	2.76	2.42	2.14	1.91	1.71	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.38	3.62	3.09	2.68	2.36	2.09	1.87	1.69	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.56	3.03	2.63	2.31	2.06	1.85	1.67	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.28	3.53	3.00	2.60	2.29	2.04	1.83	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.45	4.29	3.53	2.99	2.59	2.28	2.03	1.83	-	-	-
-2.00	10.00	10.00	10.00	7.46	5.50	4.32	3.55	3.01	2.61	2.30	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.60	5.61	4.42	3.64	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Maximum Loads)	Tool Pin	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.10	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.16	4.21	3.50	2.95	-	-	-	-	-	-
6.00	-	-	-	-	-	5.12	4.20	3.53	3.01	2.58	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.33a	5.06	4.16	3.51	3.02	2.60	2.25	1.96	-	-	-
4.00	-	-	-	8.43	6.30	4.99	4.11	3.48	3.01	2.60	2.25	1.97	-	-	-
3.00	-	-	8.59a	8.31	6.21	4.93	4.07	3.46	3.00	2.58	2.24	1.96	1.72	-	-
2.00	-	-	10.00	8.27	6.18	4.91	4.06	3.43	2.95	2.55	2.20	1.93	1.70	-	-
1.00	-	5.10a	8.87a	8.07	6.04	4.80	3.96	3.34	2.88	2.49	2.16	1.90	1.68	-	-
0.00	7.17a	8.50a	10.00	7.90	5.90	4.68	3.87	3.28	2.82	2.43	2.12	1.86	-	-	-
-1.00	10.00	10.00	10.00	7.81	5.82	4.62	3.81	3.22	2.73	2.37	2.07	1.84	-	-	-
-2.00	10.00	10.00	10.00	7.81	5.80	4.58	3.74	3.13	2.68	2.33	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.75	5.73	4.49	3.69	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.12	3.43	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.09	3.42	2.91	2.52	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.88	3.99	3.35	2.87	2.49	2.19	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.67	3.85	3.25	2.80	2.44	2.15	1.91	-	-	-
3.00	-	-	5.00	5.00	5.00	4.46	3.70	3.15	2.72	2.38	2.11	1.88	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.38	3.59	3.06	2.65	2.33	2.07	1.85	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.54	3.01	2.61	2.29	2.04	1.83	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.30	3.53	2.99	2.58	2.27	2.02	1.82	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.31	3.53	2.99	2.58	2.27	2.02	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.34	3.56	3.01	2.60	2.29	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.47	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.15	3.44	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.16	3.49	2.95	2.52	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.12	3.48	2.97	2.54	2.20	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.94	4.07	3.45	2.97	2.54	2.20	1.92	-	-	-
3.00	-	-	5.00	5.00	5.00	4.90	4.04	3.44	2.95	2.52	2.18	1.91	-	-	-
2.00	-	-	5.00	5.00	5.00	4.88	4.01	3.38	2.90	2.48	2.15	1.89	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.74	3.91	3.30	2.83	2.43	2.11	1.85	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	4.64	3.83	3.24	2.75	2.37	2.07	1.83	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.59	3.77	3.14	2.68	2.32	2.04	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.51	3.68	3.08	2.64	2.30	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.47	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Minimum Loads)	Hitch	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.60	2.83a	2.65	-	-	-	-	-
6.00	-	-	-	-	-	-	4.27	3.57	3.05	2.54a	2.31	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.16	3.49	2.99	2.60	2.29	2.03	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.88	4.00	3.38	2.90	2.53	2.24	1.99	1.79	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.61	3.82	3.24	2.80	2.46	2.18	1.95	1.75	1.59	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.38	3.65	3.12	2.70	2.38	2.12	1.90	1.72	1.56	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.26	3.54	3.02	2.63	2.32	2.07	1.86	1.69	1.54	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.21	3.49	2.97	2.58	2.28	2.04	1.84	1.67	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.20	3.47	2.95	2.56	2.26	2.02	1.82	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.23	3.49	2.96	2.57	2.26	2.03	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.29	3.53	3.00	2.60	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DU (Maximum Loads)	Hitch	RAIL	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	3.63	3.09	2.65	-	-	-	-	-
6.00	-	-	-	-	-	-	4.28	3.61	3.11	2.69	2.33	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.22	3.57	3.08	2.70	2.35	2.05	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.15	3.52	3.05	2.68	2.34	2.05	1.81	-	-
3.00	-	5.00	5.00	5.00	5.00	4.94	4.09	3.47	3.02	2.66	2.32	2.03	1.79	1.59	-
2.00	3.93a	5.00	5.00	5.00	5.00	4.89	4.05	3.45	3.00	2.63	2.28	1.99	1.76	1.57	-
1.00	5.00	5.00	5.00	5.00	5.00	4.85	4.00	3.39	2.93	2.56	2.22	1.95	1.73	1.54	-
0.00	5.00	5.00	5.00	5.00	5.00	4.70	3.89	3.30	2.86	2.48	2.15	1.90	1.69	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.61	3.81	3.24	2.77	2.39	2.10	1.85	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.57	3.74	3.13	2.68	2.33	2.05	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.46	3.65	3.07	2.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Minimum Loads)	Tool Pin	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.50a	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.68b	4.03b	3.51b	3.43a	3.18a	3.34a	-	-	-
4.00	-	-	-	8.13b	6.53b	5.41b	4.59b	3.97b	3.48b	3.26a	3.66a	3.19a	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.31b	4.53b	3.93b	3.46b	3.73a	3.48a	3.28a	3.68a	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.50b	4.24b	4.32b	3.96a	4.12a	3.58a	3.85a	-	-
1.00	-	1.55a	3.30a	3.36a	3.58a	3.97a	6.19b	5.79b	5.55b	5.00a	4.40a	4.54a	4.28a	-	-
0.00	2.22a	1.75a	3.52a	3.39a	3.55a	6.61a	7.96b	7.20b	5.23a	5.07a	4.79a	4.67a	-	-	-
-1.00	3.33a	3.03a	5.95a	6.08a	7.13a	9.61b	8.64b	7.50a	6.96b	6.15	5.39	4.80	-	-	-
-2.00	5.11a	5.07a	10.00	10.00	10.00	8.42b	7.49b	6.78b	6.11b	5.38b	-	-	-	-	-
-3.00	8.35a	8.90a	10.00	10.00	10.00	8.59b	7.35b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Maximum Loads)	Tool Pin	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	5.29a	5.07a	4.33a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	5.41a	5.44a	5.32a	4.91a	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	6.38a	6.36a	6.11b	5.70b	5.42b	5.19a	3.76a	-	-	-
4.00	-	-	-	10.00	10.00	8.68b	7.62b	6.81b	6.23b	5.81b	5.45b	4.94	-	-	-
3.00	-	-	8.59a	10.00	10.00	10.00	8.76b	7.66b	6.85b	6.23b	5.54	4.93	4.38	-	-
2.00	-	-	10.00	10.00	10.00	10.00	9.53b	8.24b	7.25	6.29	5.54	4.90	4.37	-	-
1.00	-	2.44a	8.87a	10.00	10.00	10.00	9.71b	8.49b	7.25	6.29	5.53	4.87	4.34	-	-
0.00	3.52a	4.22a	10.00	10.00	10.00	10.00	9.76b	8.52b	7.30	6.31	5.48	4.83	-	-	-
-1.00	5.40a	6.44a	10.00	10.00	10.00	10.00	9.85b	8.62b	7.31	6.25	5.44	4.81	-	-	-
-2.00	7.75a	9.33a	10.00	10.00	10.00	10.00	10.00	8.58b	7.24	6.04b	-	-	-	-	-
-3.00	10.00	10.00	10.00	10.00	10.00	9.96b	8.15b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.39a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.80a	3.90a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.98a	3.89a	3.83a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.53b	3.92b	3.84b	3.84a	4.14a	3.75a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.47b	3.88b	4.01b	4.27a	4.16a	4.29a	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.84b	4.75b	4.60a	4.53a	4.93a	4.08a	-	-	-
1.00	-	2.12a	4.10a	3.85a	3.84a	4.09a	5.00	5.00	5.00	5.00	5.00	4.80	-	-	-
0.00	3.55a	2.55a	4.55a	4.04a	3.83a	5.00	5.00	5.00	5.00	5.00	5.00	4.79	-	-	-
-1.00	4.45a	4.07a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.97b	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	4.71a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	4.28a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.86a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.61a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.88	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.86	-	-	-
1.00	-	2.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.83	-	-	-
0.00	4.29a	4.90a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.80	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Minimum Loads)	Hitch	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.55b	3.15b	2.54a	2.70a	2.49a	-	-
3.00	-	2.02a	3.93a	4.47a	5.00	5.00	4.55b	3.96b	3.49b	3.12b	2.86a	2.77a	2.66a	2.73a	-
2.00	1.26a	1.20a	2.65a	2.91a	4.44a	5.00	4.48b	3.91b	3.47b	3.28a	3.00a	3.04a	3.07a	2.74a	-
1.00	1.98a	1.44a	2.68a	2.66a	4.46a	5.00	5.00	4.76b	4.60b	3.56a	3.72a	3.31a	3.20a	3.23a	-
0.00	2.27a	1.89a	3.51a	4.25a	5.00	5.00	5.00	5.00	5.00	4.20a	4.29a	3.78a	3.84a	-	-
-1.00	3.02a	2.88a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.75a	-	-	-
-2.00	4.14a	4.19a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EU (Maximum Loads)	Hitch	RAIL	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.35a	4.25a	3.95a	3.42a	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	5.00	4.99a	4.88a	4.66a	4.26a	3.58a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.53a	3.56a	-	-
3.00	-	3.78a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.96	4.31a	2.73a	-
2.00	1.91a	4.14a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.94	4.40	3.25a	-
1.00	2.60a	3.96a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.91	4.38	3.23a	-
0.00	3.72a	4.66a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.86	4.34	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.82	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Minimum Loads)	Tool Pin	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.50a	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.68b	4.03b	3.51b	3.43a	3.18a	3.29	-	-	-
4.00	-	-	-	8.13b	6.53b	5.41b	4.59b	3.97b	3.48b	3.26a	3.66a	3.19a	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.31b	4.53b	3.93b	3.46b	3.73a	3.48a	3.21	2.85	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.50b	4.24b	4.32b	3.96a	3.57	3.16	2.82	-	-
1.00	-	1.55a	3.30a	3.36a	3.58a	3.97a	6.19b	5.55	4.67	4.02	3.52	3.11	2.79	-	-
0.00	2.22a	1.75a	3.52a	3.39a	3.55a	6.61a	6.75	5.50	4.63	3.98	3.48	3.09	-	-	-
-1.00	3.33a	3.03a	5.95a	6.08a	7.13a	8.73	6.75	5.49	4.61	3.97	3.48	3.09	-	-	-
-2.00	5.11a	5.07a	10.00	10.00	10.00	8.42b	6.79	5.52	4.64	3.99	-	-	-	-	-
-3.00	8.35a	8.90a	10.00	10.00	10.00	8.59b	6.95	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Maximum Loads)	Tool Pin	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	5.29a	5.07a	4.33a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	5.41a	5.44a	5.22	4.42	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	6.38a	6.36a	6.11b	5.19	4.45	3.81	3.29	-	-	-
4.00	-	-	-	10.00	10.00	8.68b	7.43	6.09	5.14	4.43	3.81	3.30	-	-	-
3.00	-	-	8.59a	10.00	10.00	9.34	7.34	6.04	5.11	4.41	3.79	3.28a	2.87	-	-
2.00	-	-	10.00	10.00	10.00	9.30	7.31	6.02	5.10	4.38	3.75	3.25	2.84	-	-
1.00	-	2.44a	8.87a	10.00	10.00	9.32	7.33	6.04	5.09	4.30	3.68	3.19	2.80	-	-
0.00	3.52a	4.22a	10.00	10.00	10.00	9.42	7.34	5.97	4.99	4.21	3.61	3.14	-	-	-
-1.00	5.40a	6.44a	10.00	10.00	10.00	9.33	7.25	5.87	4.85	4.11	3.54	3.10	-	-	-
-2.00	7.75a	9.33a	10.00	10.00	10.00	9.27	7.11	5.72	4.76	4.05	-	-	-	-	-
-3.00	10.00	10.00	10.00	10.00	10.00	9.10	7.03	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.39a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.80a	3.90a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.98a	3.89a	3.72	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.53b	3.92b	3.84b	3.84a	3.66	3.22	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.47b	3.88b	4.01b	4.14	3.60	3.17	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.84b	4.75b	4.60a	4.05	3.53	3.13	-	-	-
1.00	-	2.12a	4.10a	3.85a	3.84a	4.09a	5.00	5.00	4.64	3.99	3.49	3.09	-	-	-
0.00	3.55a	2.55a	4.55a	4.04a	3.83a	5.00	5.00	5.00	4.60	3.96	3.46	3.07	-	-	-
-1.00	4.45a	4.07a	5.00	5.00	5.00	5.00	5.00	5.00	4.60	3.95	3.46	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	3.99	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	4.71a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	4.28a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.37	3.74	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.38	3.74	3.23	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.34	3.71	3.21	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.29	3.66	3.18	-	-	-
1.00	-	2.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.20	3.60	3.13	-	-	-
0.00	4.29a	4.90a	5.00	5.00	5.00	5.00	5.00	5.00	4.87	4.12	3.54	3.08	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.76	4.03	3.49	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.69	4.00	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Minimum Loads)	Hitch	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.55b	3.15b	2.54a	2.70a	2.49a	-	-
3.00	-	2.02a	3.93a	4.47a	5.00	5.00	4.55b	3.96b	3.49b	3.12b	2.86a	2.77a	2.66a	2.61	-
2.00	1.26a	1.20a	2.65a	2.91a	4.44a	5.00	4.48b	3.91b	3.47b	3.28a	3.00a	3.04a	2.86	2.58	-
1.00	1.98a	1.44a	2.68a	2.66a	4.46a	5.00	5.00	4.76b	4.60b	3.56a	3.53	3.14	2.82	2.54	-
0.00	2.27a	1.89a	3.51a	4.25a	5.00	5.00	5.00	5.00	4.60	3.97	3.49	3.10	2.78	-	-
-1.00	3.02a	2.88a	5.00	5.00	5.00	5.00	5.00	5.00	4.57	3.94	3.46	3.08	-	-	-
-2.00	4.14a	4.19a	5.00	5.00	5.00	5.00	5.00	5.00	4.58	3.94	3.47	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2AL (Maximum Loads)	Hitch	RAIL	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.35a	4.25a	3.95a	3.42a	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	5.00	4.99a	4.88a	4.50	3.91	3.40	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.48	3.90	3.39	2.98	-	-
3.00	-	3.78a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.44	3.88	3.37	2.95	2.61	-
2.00	1.91a	4.14a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.42	3.83	3.33	2.92	2.59	-
1.00	2.60a	3.96a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.38	3.76	3.27	2.87	2.54	-
0.00	3.72a	4.66a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.27	3.67	3.20	2.81	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.91	4.14	3.58	3.13	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.76	4.06	3.51	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.69	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Minimum Loads)	Tool Pin	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.71	3.83	3.18	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.67	3.81	3.18	2.70	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.53	3.71	3.12	2.66	2.30	1.99	-	-	-
4.00	-	-	-	8.13b	6.53b	5.40	4.32	3.57	3.01	2.59	2.25	1.97	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.02	4.08	3.40	2.89	2.50	2.18	1.92	1.70	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	3.89	3.26	2.78	2.41	2.11	1.87	1.67	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.78	3.16	2.70	2.35	2.07	1.83	1.64	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	4.67	3.74	3.12	2.66	2.31	2.03	1.81	-	-	-
-1.00	3.33a	6.24a	5.95a	6.08a	6.19	4.68	3.74	3.11	2.65	2.30	2.03	1.81	-	-	-
-2.00	5.11a	10.00	10.00	9.10	6.27	4.73	3.78	3.13	2.67	2.32	-	-	-	-	-
-3.00	8.35a	10.00	10.00	9.33	6.44	4.88	3.91	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Maximum Loads)	Tool Pin	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	4.76	3.86	3.18	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	4.74	3.90	3.26	2.73	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	5.83	4.68	3.87	3.28	2.76	2.34	2.00	-	-	-
4.00	-	-	-	10.00	7.42	5.70b	4.60	3.83	3.26	2.77	2.34	2.01	-	-	-
3.00	-	-	8.59a	10.00	7.29	5.61	4.54	3.79	3.24	2.74	2.32	1.99	1.71	-	-
2.00	-	-	10.00	10.00	7.24	5.58	4.52	3.76	3.17	2.69	2.27	1.96	1.69	-	-
1.00	-	5.10a	8.87a	10.00	7.12	5.45	4.39	3.63	3.07	2.60	2.22	1.90	1.65	-	-
0.00	3.52a	8.50a	10.00	9.84	6.90	5.27	4.25	3.53	2.99	2.52	2.15	1.86	-	-	-
-1.00	5.40a	10.00	10.00	9.69	6.78	5.18	4.17	3.44	2.86	2.42	2.09	1.82	-	-	-
-2.00	7.75a	10.00	10.00	9.68	6.75	5.12	4.05	3.31	2.78	2.37	-	-	-	-	-
-3.00	10.00	10.00	10.00	9.59	6.63	4.99	3.98	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	3.76	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.58	3.73	3.12	2.64	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.43	3.64	3.05	2.61	2.25	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.22	3.49	2.95	2.53	2.20	1.93	-	-	-
3.00	-	-	5.00	5.00	5.00	4.94	4.00	3.34	2.84	2.45	2.14	1.88	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	3.84	3.21	2.74	2.37	2.08	1.84	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.77	3.14	2.67	2.32	2.04	1.81	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	4.70	3.74	3.10	2.64	2.29	2.01	1.79	-	-	-
-1.00	4.45a	5.00	5.00	5.00	5.00	4.71	3.75	3.10	2.64	2.29	2.01	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.76	3.79	3.13	2.66	2.32	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.95	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.67	3.76	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68	3.84	3.17	2.65	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61	3.83	3.20	2.68	2.27	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.54	3.79	3.20	2.68	2.26	1.94	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.50	3.76	3.17	2.65	2.24	1.92	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.47	3.68	3.10	2.60	2.20	1.89	-	-	-
1.00	-	5.00	5.00	5.00	5.00	5.00	4.31	3.56	3.00	2.51	2.14	1.84	-	-	-
0.00	4.29a	5.00	5.00	5.00	5.00	5.00	4.19	3.47	2.88	2.43	2.08	1.80	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.10	3.33	2.78	2.36	2.04	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	3.97	3.24	2.72	2.33	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.95	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Minimum Loads)	Hitch	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	3.96	3.31	2.54a	2.43	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.68	3.85	3.23	2.76	2.39	2.09	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.45	3.67	3.10	2.66	2.32	2.04	1.80	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	5.00	4.17	3.47	2.95	2.56	2.23	1.97	1.76	1.57	-
2.00	1.26a	2.62a	2.65a	2.91a	4.44a	4.82	3.93	3.29	2.81	2.45	2.15	1.91	1.71	1.54	-
1.00	1.98a	3.17a	2.68a	2.66a	4.46a	4.63	3.76	3.16	2.71	2.36	2.08	1.85	1.67	1.50	-
0.00	2.27a	3.98a	3.51a	4.25a	5.00	4.56	3.68	3.08	2.64	2.30	2.04	1.82	1.64	-	-
-1.00	3.02a	5.00	5.00	5.00	5.00	4.55	3.66	3.05	2.61	2.27	2.01	1.80	-	-	-
-2.00	4.14a	5.00	5.00	5.00	5.00	4.58	3.68	3.06	2.62	2.28	2.02	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.68	3.75	3.11	2.67	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2BL (Maximum Loads)	Hitch	RAIL	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.36	2.84	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.02	3.40	2.88	2.46	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.77	3.96	3.36	2.90	2.48	2.12	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	3.88	3.31	2.88	2.47	2.12	1.83	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.56	3.82	3.27	2.85	2.44	2.09	1.81	1.57	-
2.00	1.91a	5.00	5.00	5.00	5.00	5.00	4.51	3.78	3.25	2.80	2.38	2.04	1.76	1.54	-
1.00	2.60a	5.00	5.00	5.00	5.00	5.00	4.45	3.70	3.15	2.71	2.29	1.98	1.72	1.50	-
0.00	3.72a	5.00	5.00	5.00	5.00	5.00	4.29	3.57	3.04	2.59	2.20	1.91	1.66	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	5.00	4.16	3.48	2.91	2.46	2.12	1.84	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.06	3.31	2.78	2.38	2.06	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.93	3.92	3.22	2.72	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Minimum Loads)	Tool Pin	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.15	4.09	3.36	2.80	-	-	-	-	-	-
6.00	-	-	-	-	-	5.09	4.06	3.34	2.81	2.40	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	4.92	3.95	3.26	2.76	2.37	2.06	1.79	-	-	-
4.00	-	-	-	8.13b	6.02	4.68	3.78	3.15	2.67	2.31	2.01	1.77	-	-	-
3.00	-	-	6.48a	6.32a	5.81	4.38	3.59	3.01	2.57	2.23	1.96	1.74	1.54	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.22	3.43	2.90	2.48	2.16	1.91	1.69	1.52	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.35	2.82	2.42	2.11	1.87	1.66	1.50	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	4.10	3.32	2.78	2.39	2.08	1.84	1.64	-	-	-
-1.00	3.33a	6.24a	5.95a	6.08a	5.35	4.11	3.32	2.78	2.38	2.08	1.84	1.65	-	-	-
-2.00	5.11a	10.00	10.00	7.67	5.41	4.15	3.35	2.80	2.40	2.09	-	-	-	-	-
-3.00	8.35a	10.00	10.00	7.84	5.55	4.27	3.45	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Maximum Loads)	Tool Pin	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.09	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.16	4.13	3.38	2.81	-	-	-	-	-	-
6.00	-	-	-	-	-	5.12	4.12	3.42	2.87	2.42	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	5.04	4.07	3.39	2.89	2.45	2.09	1.80	-	-	-
4.00	-	-	-	8.88	6.41	4.95	4.01	3.36	2.87	2.45	2.09	1.80	-	-	-
3.00	-	-	8.59a	8.72	6.31	4.89	3.97	3.33	2.86	2.43	2.08	1.79	1.55	-	-
2.00	-	-	10.00	8.68	6.26	4.86	3.95	3.30	2.80	2.39	2.04	1.76	1.53	-	-
1.00	-	5.10a	8.87a	8.45	6.09	4.72	3.83	3.19	2.72	2.32	1.99	1.72	1.50	-	-
0.00	3.52a	8.50a	10.00	8.23	5.91	4.58	3.73	3.11	2.65	2.25	1.93	1.68	-	-	-
-1.00	5.40a	10.00	10.00	8.12	5.81	4.50	3.66	3.05	2.55	2.17	1.88	1.65	-	-	-
-2.00	7.75a	10.00	10.00	8.11	5.79	4.46	3.57	2.94	2.48	2.13	-	-	-	-	-
-3.00	10.00	10.00	10.00	8.05	5.70	4.35	3.51	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.03	3.30	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	3.99	3.28	2.76	2.35	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.83	3.87	3.20	2.70	2.32	2.02	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.57	3.70	3.08	2.63	2.26	1.98	1.74	-	-	-
3.00	-	-	5.00	5.00	5.00	4.31	3.52	2.96	2.53	2.20	1.93	1.70	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.22	3.40	2.86	2.45	2.13	1.88	1.67	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.34	2.80	2.40	2.09	1.84	1.64	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	4.12	3.32	2.77	2.37	2.06	1.82	1.63	-	-	-
-1.00	4.45a	5.00	5.00	5.00	5.00	4.13	3.32	2.77	2.37	2.06	1.82	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.17	3.35	2.80	2.39	2.09	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.32	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.06	3.30	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.07	3.37	2.80	2.36	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.98	4.02	3.35	2.82	2.38	2.03	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.90	3.97	3.32	2.82	2.38	2.03	1.75	-	-	-
3.00	-	-	5.00	5.00	5.00	4.84	3.93	3.30	2.80	2.36	2.01	1.73	-	-	-
2.00	-	-	5.00	5.00	5.00	4.83	3.90	3.24	2.75	2.31	1.97	1.71	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.66	3.77	3.14	2.66	2.24	1.93	1.67	-	-	-
0.00	4.29a	5.00	5.00	5.00	5.00	4.53	3.68	3.07	2.56	2.18	1.88	1.64	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.47	3.61	2.95	2.48	2.12	1.84	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.38	3.50	2.88	2.44	2.10	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.32	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Minimum Loads)	Hitch	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.50	2.83a	2.51	-	-	-	-	-
6.00	-	-	-	-	-	-	4.20	3.46	2.92	2.50	2.17	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.07	3.37	2.85	2.45	2.13	1.87	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.82	3.88	3.23	2.74	2.37	2.07	1.83	1.63	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.49	3.66	3.07	2.63	2.28	2.00	1.78	1.59	1.43	-
2.00	1.26a	2.62a	2.65a	2.91a	4.44a	4.22	3.47	2.92	2.51	2.19	1.94	1.73	1.55	1.40	-
1.00	1.98a	3.17a	2.68a	2.66a	4.46a	4.07	3.33	2.81	2.42	2.12	1.88	1.68	1.51	1.37	-
0.00	2.27a	3.98a	3.51a	4.25a	5.00	4.01	3.27	2.75	2.37	2.07	1.84	1.65	1.49	-	-
-1.00	3.02a	5.00	5.00	5.00	5.00	4.00	3.25	2.73	2.35	2.05	1.82	1.64	-	-	-
-2.00	4.14a	5.00	5.00	5.00	5.00	4.03	3.26	2.74	2.35	2.06	1.83	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.11	3.32	2.78	2.39	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2CL (Maximum Loads)	Hitch	RAIL	+/- 45° - +/- 135°		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	3.53	2.97	2.51	-	-	-	-	-
6.00	-	-	-	-	-	-	4.22	3.51	2.99	2.55	2.19	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.15	3.46	2.95	2.57	2.20	1.90	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.06	3.40	2.91	2.54	2.20	1.89	1.65	-	-
3.00	-	5.00	5.00	5.00	5.00	4.90	3.99	3.35	2.88	2.52	2.17	1.87	1.63	1.43	-
2.00	1.91a	5.00	5.00	5.00	5.00	4.83	3.94	3.32	2.86	2.48	2.12	1.83	1.59	1.40	-
1.00	2.60a	5.00	5.00	5.00	5.00	4.78	3.88	3.25	2.78	2.41	2.05	1.78	1.56	1.37	-
0.00	3.72a	5.00	5.00	5.00	5.00	4.60	3.76	3.14	2.69	2.31	1.98	1.72	1.51	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	4.49	3.65	3.07	2.59	2.20	1.91	1.67	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.44	3.58	2.94	2.48	2.14	1.86	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.31	3.46	2.87	2.43	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Minimum Loads)	Tool Pin	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.57	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.10	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.68b	4.03b	3.51b	3.07	2.70	2.39	-	-	-
4.00	-	-	-	8.13b	6.53b	5.41b	4.59b	3.97b	3.45	3.01	2.66	2.36	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.31b	4.53b	3.87	3.35	2.94	2.61	2.33	2.09	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.41	3.76	3.27	2.87	2.55	2.29	2.07	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	4.33	3.69	3.20	2.82	2.52	2.26	2.05	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	5.22	4.30	3.66	3.17	2.79	2.49	2.24	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	6.63	5.23	4.30	3.65	3.16	2.79	2.49	2.24	-	-	-
-2.00	10.00	10.00	10.00	9.05	6.68	5.26	4.33	3.67	3.18	2.80	-	-	-	-	-
-3.00	10.00	10.00	10.00	9.21	6.80	5.37	4.43	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Maximum Loads)	Tool Pin	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	5.05	4.22	3.57	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	5.03	4.25	3.63	3.12	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	6.05	4.98	4.22	3.64	3.14	2.73	2.39	-	-	-
4.00	-	-	-	9.99	7.50	5.96	4.93	4.19	3.62	3.15	2.73	2.40	-	-	-
3.00	-	-	8.59a	9.86	7.40b	5.89	4.88	4.15	3.61	3.13	2.72	2.38	2.10	-	-
2.00	-	-	10.00	9.83	7.36	5.86	4.87	4.14	3.57	3.09	2.68	2.36	2.08	-	-
1.00	-	5.10a	8.87a	9.73	7.29	5.79	4.79	4.05	3.49	3.02	2.63	2.32	2.06	-	-
0.00	7.17a	8.50a	10.00	9.55	7.13	5.66	4.68	3.97	3.42	2.95	2.58	2.28	-	-	-
-1.00	10.00	10.00	10.00	9.45	7.04	5.59	4.62	3.91	3.33	2.88	2.53	2.25	-	-	-
-2.00	10.00	10.00	10.00	9.44	7.02	5.55	4.54	3.81	3.26	2.84	-	-	-	-	-
-3.00	10.00	10.00	10.00	9.38	6.94	5.45	4.48	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.14	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.53	3.05	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.47	3.02	2.66	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.53b	3.92b	3.40	2.97	2.62	2.33	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.47b	3.83	3.31	2.90	2.57	2.30	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.38	3.73	3.23	2.84	2.53	2.27	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	4.32	3.67	3.18	2.80	2.49	2.24	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	5.00	4.30	3.64	3.16	2.78	2.48	2.23	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.31	3.65	3.15	2.77	2.48	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.34	3.67	3.18	2.80	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.99	4.15	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.99	4.21	3.56	3.06	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.94	4.19	3.59	3.08	2.67	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.89	4.15	3.59	3.08	2.67	2.34	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.85b	4.13	3.57	3.06	2.65	2.33	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.84b	4.09	3.51	3.02	2.62	2.30	-	-	-
1.00	-	5.00	5.00	5.00	5.00	5.00	4.73	4.00	3.44	2.95	2.57	2.27	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.64	3.93	3.34	2.89	2.53	2.24	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.57	3.82	3.26	2.83	2.50	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.47	3.75	3.22	2.81	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Minimum Loads)	Hitch	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.46	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.51	3.07	2.54a	2.42	2.17	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	5.00	4.55b	3.93	3.40	2.99	2.65	2.37	2.14	1.94	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	5.00	4.44	3.79	3.29	2.90	2.58	2.32	2.10	1.91	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	5.00	4.32	3.69	3.21	2.83	2.53	2.28	2.07	1.89	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	5.00	4.26	3.63	3.16	2.79	2.49	2.25	2.04	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.24	3.61	3.13	2.77	2.47	2.23	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.25	3.62	3.14	2.77	2.48	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.30	3.66	3.18	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2DL (Maximum Loads)	Hitch	RAIL	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.32a	3.73	3.23a	2.82	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	5.00	4.28	3.71	3.24	2.83a	2.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.97	4.23	3.66	3.23	2.82	2.48	2.20	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.90	4.18	3.63	3.21b	2.81	2.46	2.18	1.94	-
2.00	3.93a	5.00	5.00	5.00	5.00	5.00	4.85b	4.14	3.61	3.18	2.76	2.42	2.14	1.92	-
1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.83	4.10	3.55	3.10	2.69	2.37	2.11	1.89	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.71	4.00	3.46	3.01	2.62	2.32	2.06	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.62	3.93	3.37	2.91	2.56	2.27	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.54	3.81	3.26	2.85	2.51	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.44	3.74	3.22	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Minimum Loads)	Tool Pin	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.50a	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.68b	4.03b	3.51b	3.43a	3.18a	3.34a	-	-	-
4.00	-	-	-	8.13b	6.53b	5.41b	4.59b	3.97b	3.48b	3.26a	3.66a	3.19a	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.31b	4.53b	3.93b	3.46b	3.73a	3.48a	3.28a	3.68a	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.50b	4.24b	4.32b	3.96a	4.12a	3.58a	3.85a	-	-
1.00	-	1.55a	3.30a	3.36a	3.58a	3.97a	6.19b	5.79b	5.55b	5.00a	4.40a	4.54a	4.28a	-	-
0.00	2.22a	1.75a	3.52a	3.39a	3.55a	6.61a	7.96b	7.20b	5.23a	5.07a	4.79a	4.67a	-	-	-
-1.00	3.33a	3.03a	5.95a	6.08a	7.13a	9.61b	8.64b	7.50a	6.96b	6.30b	5.61b	4.91b	-	-	-
-2.00	5.11a	5.07a	10.00	10.00	10.00	8.42b	7.49b	6.78b	6.11b	5.38b	-	-	-	-	-
-3.00	8.35a	8.90a	10.00	10.00	10.00	8.59b	7.35b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Maximum Loads)	Tool Pin	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	5.29a	5.07a	4.33a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	5.41a	5.44a	5.32a	4.91a	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	6.38a	6.36a	6.11b	5.70b	5.42b	5.19a	3.76a	-	-	-
4.00	-	-	-	10.00	10.00	8.68b	7.62b	6.81b	6.23b	5.81b	5.45b	5.20b	-	-	-
3.00	-	-	8.59a	10.00	10.00	10.00	8.76b	7.66b	6.85b	6.23b	5.75b	5.37b	4.73a	-	-
2.00	-	-	10.00	10.00	10.00	10.00	9.53b	8.24b	7.32b	6.60b	6.02b	5.46	4.88	-	-
1.00	-	2.44a	8.87a	10.00	10.00	10.00	9.71b	8.49b	7.53b	6.76b	6.10	5.45	4.86	-	-
0.00	3.52a	4.22a	10.00	10.00	10.00	10.00	9.76b	8.52b	7.56b	6.79b	6.13	5.41	-	-	-
-1.00	5.40a	6.44a	10.00	10.00	10.00	10.00	9.85b	8.62b	7.67b	6.89b	6.04b	4.98b	-	-	-
-2.00	7.75a	9.33a	10.00	10.00	10.00	10.00	10.00	8.58b	7.29b	6.04b	-	-	-	-	-
-3.00	10.00	10.00	10.00	10.00	10.00	9.96b	8.15b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Minimum Loads)	AUX LIFTING POINT	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.39a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.80a	3.90a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.98a	3.89a	3.83a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.53b	3.92b	3.84b	3.84a	4.14a	3.75a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.47b	3.88b	4.01b	4.27a	4.16a	4.29a	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.84b	4.75b	4.60a	4.53a	4.93a	4.08a	-	-	-
1.00	-	2.12a	4.10a	3.85a	3.84a	4.09a	5.00	5.00	5.00	5.00	5.00	5.00a	-	-	-
0.00	3.55a	2.55a	4.55a	4.04a	3.83a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	4.45a	4.07a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.97b	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Maximum Loads)	AUX LIFTING POINT	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	4.71a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	4.28a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.86a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.61a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
1.00	-	2.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
0.00	4.29a	4.90a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Minimum Loads)	Hitch	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.55b	3.15b	2.54a	2.70a	2.49a	-	-
3.00	-	2.02a	3.93a	4.47a	5.00	5.00	4.55b	3.96b	3.49b	3.12b	2.86a	2.77a	2.66a	2.73a	-
2.00	1.26a	1.20a	2.65a	2.91a	4.44a	5.00	4.48b	3.91b	3.47b	3.28a	3.00a	3.04a	3.07a	2.74a	-
1.00	1.98a	1.44a	2.68a	2.66a	4.46a	5.00	5.00	4.76b	4.60b	3.56a	3.72a	3.31a	3.20a	3.23a	-
0.00	2.27a	1.89a	3.51a	4.25a	5.00	5.00	5.00	5.00	5.00	4.20a	4.29a	3.78a	3.84a	-	-
-1.00	3.02a	2.88a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.75a	-	-	-
-2.00	4.14a	4.19a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
2EL (Maximum Loads)	Hitch	RAIL	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.35a	4.25a	3.95a	3.42a	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	5.00	4.99a	4.88a	4.66a	4.26a	3.58a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.53a	3.56a	-	-
3.00	-	3.78a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.31a	2.73a	-
2.00	1.91a	4.14a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.92	3.25a	-
1.00	2.60a	3.96a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.89	3.23a	-
0.00	3.72a	4.66a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Minimum Loads)	Tool Pin	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.22	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.56	3.03	2.61	-	-	-	-	-	-
6.00	-	-	-	-	-	4.22	3.53	3.01	2.61	2.28	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.03	4.11	3.45	2.96	2.57	2.26	2.00	1.78	-	-	-
4.00	-	-	-	6.15	4.76	3.94	3.33	2.87	2.51	2.21	1.97	1.77	-	-	-
3.00	-	-	6.48a	5.99	4.62	3.74	3.19	2.77	2.43	2.16	1.93	1.74	1.57	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.63	3.08	2.69	2.37	2.10	1.89	1.71	1.55	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.55	3.03	2.63	2.32	2.07	1.86	1.68	1.53	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	3.54	3.00	2.60	2.29	2.04	1.84	1.67	-	-	-
-1.00	6.84a	6.24a	5.95a	5.52	4.33	3.55	3.00	2.60	2.28	2.04	1.83	1.67	-	-	-
-2.00	10.00	10.00	7.55	5.56	4.37	3.58	3.02	2.61	2.30	2.05	-	-	-	-	-
-3.00	10.00	10.00	7.68	5.66	4.46	3.66	3.10	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Maximum Loads)	Tool Pin	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.22	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.27	3.59	3.04	2.61	-	-	-	-	-	-
6.00	-	-	-	-	-	4.24	3.58	3.07	2.66	2.30	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.10	4.19	3.54	3.05	2.67	2.32	2.03	1.79	-	-	-
4.00	-	-	-	6.32	5.01	4.13	3.50	3.03	2.66	2.33	2.03	1.79	-	-	-
3.00	-	-	8.35	6.22	4.94	4.08	3.47	3.01	2.65	2.31	2.02	1.78	1.58	-	-
2.00	-	-	8.32	6.19	4.92	4.06	3.45	2.98	2.60	2.28	1.99	1.76	1.56	-	-
1.00	-	5.10a	8.01	6.02	4.80	3.97	3.37	2.91	2.54	2.22	1.95	1.73	1.54	-	-
0.00	7.17a	8.50a	7.87	5.89	4.69	3.88	3.29	2.85	2.49	2.17	1.91	1.70	-	-	-
-1.00	10.00	10.00	7.82	5.82	4.63	3.82	3.25	2.80	2.41	2.11	1.87	1.67	-	-	-
-2.00	10.00	10.00	7.83	5.82	4.61	3.79	3.18	2.72	2.36	2.08	-	-	-	-	-
-3.00	10.00	10.00	7.86	5.78	4.55	3.72	3.14	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.21	3.51	2.98	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.16	3.48	2.97	2.57	2.25	-	-	-	-	-
5.00	-	-	5.00	5.00	4.94	4.04	3.40	2.91	2.53	2.23	1.97	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.87	3.28	2.82	2.47	2.18	1.94	1.74	-	-	-
3.00	-	-	5.00	5.00	4.59	3.69	3.15	2.74	2.40	2.13	1.90	1.71	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.62	3.06	2.66	2.34	2.08	1.87	1.69	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.57	3.02	2.61	2.30	2.05	1.84	1.66	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	3.56	3.00	2.59	2.28	2.03	1.82	1.65	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.37	3.57	3.01	2.59	2.28	2.03	1.82	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.40	3.60	3.03	2.61	2.29	2.05	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.49	3.70	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.23	3.53	2.99	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.20	3.54	3.04	2.60	2.25	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.15	3.51	3.03	2.62	2.27	1.98	-	-	-	-
4.00	-	-	5.00	5.00	4.96	4.09	3.47	3.00	2.62	2.27	1.98	1.75	-	-	-
3.00	-	-	5.00	5.00	4.91	4.06	3.44	2.99	2.61	2.25	1.97	1.73	-	-	-
2.00	-	-	5.00	5.00	4.90	4.04	3.42	2.94	2.56	2.22	1.94	1.72	-	-	-
1.00	-	5.00	5.00	5.00	4.75	3.93	3.33	2.87	2.50	2.17	1.90	1.69	-	-	-
0.00	5.00	5.00	5.00	5.00	4.65	3.84	3.26	2.81	2.42	2.12	1.87	1.66	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.60	3.80	3.21	2.73	2.36	2.07	1.84	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.57	3.74	3.13	2.68	2.33	2.05	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.51	3.70	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Minimum Loads)	Hitch	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.68	3.13	2.71	2.37	-	-	-	-	-
6.00	-	-	-	-	-	-	3.63	3.11	2.69	2.36	2.09	-	-	-	-
5.00	-	-	-	-	4.80a	4.23	3.54	3.04	2.64	2.32	2.06	1.85	-	-	-
4.00	-	5.00	5.00	5.00	4.91	4.04	3.41	2.93	2.56	2.26	2.02	1.81	1.64	-	-
3.00	-	4.06a	3.93a	4.47a	4.57	3.81	3.25	2.82	2.47	2.20	1.96	1.77	1.61	1.46	-
2.00	2.78a	2.62a	2.65a	2.91a	4.32	3.62	3.11	2.71	2.39	2.13	1.91	1.73	1.57	1.44	-
1.00	4.19a	3.17a	2.68a	2.66a	4.24	3.52	3.02	2.63	2.32	2.07	1.87	1.69	1.55	1.42	-
0.00	4.74a	3.98a	3.51a	4.25a	4.22	3.49	2.97	2.58	2.28	2.03	1.84	1.67	1.53	-	-
-1.00	5.00	5.00	5.00	5.00	4.22	3.48	2.95	2.56	2.26	2.02	1.82	1.66	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.25	3.50	2.97	2.57	2.27	2.02	1.83	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.32	3.55	3.00	2.60	2.30	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AU (Maximum Loads)	Hitch	CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.66	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.68	3.16	2.73	2.37	-	-	-	-	-
6.00	-	-	-	-	-	-	3.65	3.14	2.74	2.41	2.11	-	-	-	-
5.00	-	-	-	-	4.80a	4.25	3.60	3.10	2.72	2.41	2.12	1.87	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.17	3.53	3.06	2.69	2.40	2.12	1.86	1.65	-	-
3.00	-	5.00	5.00	5.00	4.94	4.09	3.48	3.02	2.66	2.38	2.09	1.85	1.64	1.46	-
2.00	3.93a	5.00	5.00	5.00	4.89	4.05	3.45	3.00	2.65	2.35	2.06	1.81	1.61	1.45	-
1.00	5.00	5.00	5.00	5.00	4.86	4.01	3.41	2.95	2.59	2.29	2.00	1.77	1.58	1.42	-
0.00	5.00	5.00	5.00	5.00	4.69	3.89	3.32	2.87	2.52	2.22	1.94	1.73	1.55	-	-
-1.00	5.00	5.00	5.00	5.00	4.61	3.82	3.24	2.82	2.44	2.13	1.89	1.69	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.57	3.78	3.19	2.72	2.36	2.08	1.85	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.51	3.69	3.10	2.67	2.33	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Minimum Loads)	Tool Pin	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.92	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.97	3.26	2.74	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	3.92	3.24	2.73	2.34	2.03	-	-	-	-	-
5.00	-	-	6.02a	6.07a	4.74	3.80	3.15	2.67	2.30	2.01	1.76	1.56	-	-	-
4.00	-	-	-	5.90	4.44	3.62	3.02	2.58	2.23	1.96	1.73	1.54	-	-	-
3.00	-	-	6.48a	5.72	4.29	3.40	2.88	2.47	2.15	1.90	1.69	1.51	1.35	-	-
2.00	-	-	3.75a	3.90a	4.14	3.28	2.76	2.39	2.08	1.84	1.64	1.47	1.33	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.20	2.70	2.33	2.03	1.80	1.61	1.45	1.31	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	3.19	2.67	2.30	2.01	1.78	1.59	1.43	-	-	-
-1.00	6.84a	6.24a	5.95a	5.20	3.97	3.20	2.67	2.29	2.00	1.77	1.58	1.43	-	-	-
-2.00	10.00	10.00	7.42	5.24	4.02	3.23	2.70	2.31	2.01	1.78	-	-	-	-	-
-3.00	10.00	10.00	7.56	5.36	4.11	3.32	2.78	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Maximum Loads)	Tool Pin	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.93	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.97	3.29	2.76	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	3.95	3.28	2.79	2.39	2.05	-	-	-	-	-
5.00	-	-	6.02a	6.20	4.81	3.89	3.25	2.77	2.40	2.07	1.79	1.56	-	-	-
4.00	-	-	-	6.08	4.71	3.82	3.20	2.74	2.39	2.07	1.79	1.56	-	-	-
3.00	-	-	8.33	5.98	4.64	3.77	3.17	2.72	2.38	2.06	1.78	1.55	1.36	-	-
2.00	-	-	8.30	5.95	4.61	3.75	3.15	2.70	2.33	2.02	1.75	1.53	1.34	-	-
1.00	-	5.10a	7.94	5.75	4.49	3.66	3.07	2.62	2.27	1.96	1.71	1.49	1.32	-	-
0.00	7.17a	8.50a	7.79	5.61	4.36	3.55	2.98	2.55	2.22	1.91	1.66	1.46	-	-	-
-1.00	10.00	10.00	7.72	5.54	4.30	3.49	2.93	2.50	2.13	1.85	1.62	1.44	-	-	-
-2.00	10.00	10.00	7.74	5.53	4.28	3.46	2.86	2.42	2.08	1.82	-	-	-	-	-
-3.00	10.00	10.00	7.78	5.49	4.22	3.38	2.82	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.86	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.91	3.21	2.70	-	-	-	-	-	-	-
6.00	-	-	-	-	4.82	3.86	3.18	2.68	2.30	1.99	-	-	-	-	-
5.00	-	-	5.00	5.00	4.64	3.73	3.09	2.62	2.26	1.97	1.73	-	-	-	-
4.00	-	-	5.00	5.00	4.35	3.54	2.96	2.53	2.20	1.92	1.70	1.51	-	-	-
3.00	-	-	5.00	5.00	4.26	3.35	2.83	2.44	2.12	1.87	1.66	1.48	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.28	2.73	2.36	2.06	1.82	1.62	1.45	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.22	2.69	2.31	2.02	1.78	1.59	1.43	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	3.21	2.67	2.29	1.99	1.76	1.58	1.42	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.01	3.22	2.68	2.29	1.99	1.76	1.58	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.05	3.25	2.70	2.31	2.01	1.78	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.15	3.36	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.86	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.93	3.24	2.70	-	-	-	-	-	-	-
6.00	-	-	-	-	4.84	3.90	3.24	2.75	2.33	2.00	-	-	-	-	-
5.00	-	-	5.00	5.00	4.75	3.84	3.21	2.74	2.35	2.02	1.74	-	-	-	-
4.00	-	-	5.00	5.00	4.66	3.78	3.17	2.72	2.35	2.02	1.74	1.52	-	-	-
3.00	-	-	5.00	5.00	4.61	3.74	3.14	2.70	2.34	2.00	1.73	1.50	-	-	-
2.00	-	-	5.00	5.00	4.59	3.73	3.12	2.65	2.29	1.96	1.69	1.49	-	-	-
1.00	-	5.00	5.00	5.00	4.43	3.61	3.02	2.58	2.23	1.91	1.66	1.45	-	-	-
0.00	5.00	5.00	5.00	5.00	4.33	3.51	2.95	2.52	2.15	1.86	1.62	1.43	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.27	3.47	2.89	2.43	2.08	1.81	1.59	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.23	3.40	2.81	2.38	2.05	1.79	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.17	3.36	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Minimum Loads)	Hitch	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.39	2.86	2.45	2.12	-	-	-	-	-
6.00	-	-	-	-	-	-	3.34	2.83	2.43	2.11	1.85	-	-	-	-
5.00	-	-	-	-	4.80a	3.93	3.25	2.75	2.37	2.07	1.82	1.62	-	-	-
4.00	-	5.00	5.00	5.00	4.61	3.73	3.10	2.65	2.29	2.01	1.78	1.58	1.42	-	-
3.00	-	4.06a	3.93a	4.47a	4.23	3.48	2.93	2.52	2.20	1.94	1.72	1.54	1.39	1.26	-
2.00	2.78a	2.62a	2.65a	2.91a	3.97	3.28	2.79	2.41	2.11	1.87	1.67	1.50	1.36	1.23	-
1.00	4.19a	3.17a	2.68a	2.66a	3.87	3.17	2.69	2.32	2.04	1.81	1.62	1.46	1.33	1.21	-
0.00	4.74a	3.98a	3.51a	4.25a	3.85	3.13	2.64	2.27	1.99	1.77	1.59	1.44	1.31	-	-
-1.00	5.00	5.00	5.00	5.00	3.86	3.13	2.62	2.26	1.97	1.75	1.57	1.43	-	-	-
-2.00	5.00	5.00	5.00	5.00	3.89	3.15	2.63	2.26	1.98	1.76	1.58	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	3.97	3.20	2.68	2.30	2.01	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BU (Maximum Loads)	Hitch	CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.38	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.39	2.88	2.47	2.12	-	-	-	-	-
6.00	-	-	-	-	-	-	3.36	2.86	2.48	2.16	1.87	-	-	-	-
5.00	-	-	-	-	4.80a	3.96	3.30	2.82	2.45	2.16	1.88	1.64	-	-	-
4.00	-	5.00	5.00	5.00	4.76	3.86	3.24	2.78	2.42	2.14	1.88	1.64	1.44	-	-
3.00	-	5.00	5.00	5.00	4.64	3.78	3.18	2.74	2.40	2.13	1.85	1.62	1.42	1.26	-
2.00	3.93a	5.00	5.00	5.00	4.58	3.74	3.15	2.71	2.38	2.10	1.82	1.59	1.39	1.24	-
1.00	5.00	5.00	5.00	5.00	4.55	3.70	3.10	2.66	2.32	2.03	1.76	1.54	1.36	1.21	-
0.00	5.00	5.00	5.00	5.00	4.37	3.57	3.01	2.58	2.25	1.96	1.70	1.50	1.33	-	-
-1.00	5.00	5.00	5.00	5.00	4.27	3.49	2.93	2.52	2.17	1.87	1.65	1.45	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.23	3.45	2.87	2.42	2.08	1.82	1.61	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.17	3.35	2.78	2.36	2.04	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Minimum Loads)	Tool Pin	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.48	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.52	2.88	2.40	2.03	-	-	-	-	-	-
6.00	-	-	-	-	-	3.48	2.85	2.39	2.03	1.75	-	-	-	-	-
5.00	-	-	6.02a	5.55	4.21	3.35	2.76	2.33	1.99	1.73	1.51	1.32	-	-	-
4.00	-	-	-	5.25	3.91	3.17	2.63	2.24	1.93	1.68	1.47	1.30	-	-	-
3.00	-	-	6.48a	5.07	3.75	2.94	2.48	2.13	1.84	1.62	1.43	1.27	1.13	-	-
2.00	-	-	3.75a	3.90a	3.60	2.83	2.37	2.04	1.77	1.56	1.39	1.24	1.11	-	-
1.00	-	3.43a	3.30a	3.36a	3.47	2.74	2.30	1.98	1.72	1.52	1.35	1.21	1.10	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.42	2.73	2.28	1.95	1.70	1.50	1.33	1.20	-	-	-
-1.00	6.84a	6.24a	5.95a	4.54	3.43	2.74	2.28	1.94	1.69	1.49	1.33	1.20	-	-	-
-2.00	10.00	10.00	6.58	4.58	3.47	2.77	2.30	1.96	1.70	1.50	-	-	-	-	-
-3.00	10.00	10.00	6.73	4.70	3.57	2.86	2.38	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Maximum Loads)	Tool Pin	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.48	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.53	2.90	2.42	2.03	-	-	-	-	-	-
6.00	-	-	-	-	-	3.50	2.89	2.45	2.08	1.77	-	-	-	-	-
5.00	-	-	6.02a	5.60	4.28	3.44	2.86	2.43	2.10	1.79	1.54	1.32	-	-	-
4.00	-	-	-	5.44	4.18	3.38	2.81	2.40	2.08	1.80	1.54	1.33	-	-	-
3.00	-	-	7.53	5.34	4.11	3.32	2.78	2.38	2.07	1.78	1.53	1.32	1.14	-	-
2.00	-	-	7.50	5.30	4.08	3.30	2.76	2.35	2.03	1.74	1.49	1.30	1.13	-	-
1.00	-	5.10a	7.12	5.10	3.95	3.20	2.68	2.27	1.96	1.68	1.45	1.26	1.10	-	-
0.00	7.17a	8.50a	6.96	4.96	3.83	3.10	2.59	2.21	1.91	1.63	1.41	1.23	-	-	-
-1.00	10.00	10.00	6.90	4.88	3.76	3.04	2.54	2.16	1.82	1.57	1.37	1.20	-	-	-
-2.00	10.00	10.00	6.91	4.88	3.74	3.01	2.47	2.07	1.77	1.54	-	-	-	-	-
-3.00	10.00	10.00	6.95	4.83	3.68	2.93	2.43	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.33	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.46	2.83	2.35	-	-	-	-	-	-	-
6.00	-	-	-	-	4.30	3.41	2.79	2.34	1.99	1.71	-	-	-	-	-
5.00	-	-	5.00	5.00	4.11	3.28	2.70	2.28	1.95	1.69	1.48	-	-	-	-
4.00	-	-	5.00	5.00	3.81	3.09	2.57	2.18	1.89	1.64	1.44	1.28	-	-	-
3.00	-	-	5.00	5.00	3.72	2.90	2.43	2.09	1.81	1.59	1.40	1.25	-	-	-
2.00	-	-	3.90a	4.00a	3.60	2.82	2.34	2.01	1.75	1.54	1.36	1.22	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.52	2.76	2.29	1.96	1.70	1.50	1.33	1.20	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.48	2.75	2.28	1.94	1.68	1.48	1.32	1.18	-	-	-
-1.00	5.00	5.00	5.00	4.61	3.47	2.76	2.28	1.94	1.68	1.48	1.32	-	-	-	-
-2.00	5.00	5.00	5.00	4.63	3.50	2.79	2.31	1.96	1.70	1.50	-	-	-	-	-
-3.00	-	5.00	5.00	4.75	3.61	2.90	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.33	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.48	2.85	2.36	-	-	-	-	-	-	-
6.00	-	-	-	-	4.31	3.45	2.86	2.41	2.03	1.72	-	-	-	-	-
5.00	-	-	5.00	5.00	4.22	3.39	2.82	2.40	2.05	1.74	1.49	-	-	-	-
4.00	-	-	5.00	5.00	4.13	3.33	2.78	2.37	2.05	1.74	1.49	1.28	-	-	-
3.00	-	-	5.00	5.00	4.08	3.29	2.75	2.36	2.03	1.72	1.47	1.27	-	-	-
2.00	-	-	5.00	5.00	4.06	3.28	2.73	2.31	1.98	1.68	1.44	1.25	-	-	-
1.00	-	5.00	5.00	5.00	3.89	3.15	2.63	2.23	1.92	1.63	1.40	1.22	-	-	-
0.00	5.00	5.00	5.00	4.92	3.79	3.06	2.56	2.17	1.84	1.58	1.36	1.19	-	-	-
-1.00	5.00	5.00	5.00	4.86	3.73	3.01	2.50	2.08	1.77	1.53	1.34	-	-	-	-
-2.00	5.00	5.00	5.00	4.86	3.70	2.95	2.42	2.03	1.74	1.51	-	-	-	-	-
-3.00	-	5.00	5.00	4.78	3.63	2.90	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Minimum Loads)	Hitch	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.99	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.00	2.51	2.14	1.84	-	-	-	-	-
6.00	-	-	-	-	-	-	2.96	2.48	2.12	1.83	1.60	-	-	-	-
5.00	-	-	-	-	4.37	3.48	2.86	2.41	2.06	1.79	1.57	1.39	-	-	-
4.00	-	5.00	5.00	5.00	4.08	3.28	2.71	2.30	1.98	1.73	1.52	1.35	1.20	-	-
3.00	-	4.06a	3.93a	4.47a	3.70	3.03	2.54	2.17	1.89	1.66	1.47	1.31	1.17	1.06	-
2.00	2.78a	2.62a	2.65a	2.91a	3.42	2.82	2.39	2.06	1.79	1.58	1.41	1.26	1.14	1.03	-
1.00	4.19a	3.17a	2.68a	2.66a	3.33	2.71	2.29	1.97	1.73	1.53	1.36	1.23	1.11	1.01	-
0.00	4.74a	3.98a	3.51a	4.25a	3.31	2.67	2.24	1.92	1.68	1.49	1.33	1.20	1.09	-	-
-1.00	5.00	5.00	5.00	4.36	3.31	2.67	2.23	1.91	1.66	1.47	1.32	1.19	-	-	-
-2.00	5.00	5.00	5.00	4.40	3.34	2.69	2.24	1.91	1.67	1.47	1.32	-	-	-	-
-3.00	5.00	5.00	5.00	4.50	3.42	2.74	2.28	1.95	1.70	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CU (Maximum Loads)	Hitch	CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.99	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.01	2.54	2.16	1.84	-	-	-	-	-
6.00	-	-	-	-	-	-	2.97	2.52	2.17	1.88	1.62	-	-	-	-
5.00	-	-	-	-	4.37	3.51	2.92	2.48	2.15	1.89	1.63	1.41	-	-	-
4.00	-	5.00	5.00	5.00	4.23	3.41	2.85	2.43	2.12	1.87	1.62	1.40	1.22	-	-
3.00	-	5.00	5.00	5.00	4.11	3.33	2.79	2.39	2.09	1.85	1.60	1.39	1.21	1.06	-
2.00	3.93a	5.00	5.00	5.00	4.05	3.29	2.76	2.37	2.08	1.82	1.56	1.35	1.18	1.04	-
1.00	5.00	5.00	5.00	5.00	4.01	3.25	2.71	2.32	2.01	1.76	1.50	1.31	1.15	1.01	-
0.00	5.00	5.00	5.00	4.95	3.83	3.12	2.62	2.23	1.94	1.68	1.45	1.26	1.11	-	-
-1.00	5.00	5.00	5.00	4.83	3.74	3.03	2.54	2.18	1.86	1.59	1.39	1.22	-	-	-
-2.00	5.00	5.00	5.00	4.79	3.70	2.99	2.48	2.07	1.77	1.54	1.35	-	-	-	-
-3.00	5.00	5.00	5.00	4.78	3.63	2.90	2.39	2.01	1.73	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Minimum Loads)	Tool Pin	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.92	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.97	3.26	2.74	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	3.92	3.24	2.73	2.34	2.03	-	-	-	-	-
5.00	-	-	6.02a	6.07a	4.74	3.80	3.15	2.67	2.30	2.01	1.76	1.56	-	-	-
4.00	-	-	-	5.90	4.44	3.62	3.02	2.58	2.23	1.96	1.73	1.54	-	-	-
3.00	-	-	6.48a	5.72	4.29	3.40	2.88	2.47	2.15	1.90	1.69	1.51	1.35	-	-
2.00	-	-	3.75a	3.90a	4.14	3.28	2.76	2.39	2.08	1.84	1.64	1.47	1.33	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.20	2.70	2.33	2.03	1.80	1.61	1.45	1.31	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	3.19	2.67	2.30	2.01	1.78	1.59	1.43	-	-	-
-1.00	6.84a	6.24a	5.95a	5.20	3.97	3.20	2.67	2.29	2.00	1.77	1.58	1.43	-	-	-
-2.00	10.00	10.00	7.42	5.24	4.02	3.23	2.70	2.31	2.01	1.78	-	-	-	-	-
-3.00	10.00	10.00	7.56	5.36	4.11	3.32	2.78	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Maximum Loads)	Tool Pin	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.93	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.97	3.29	2.76	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	3.95	3.28	2.79	2.39	2.05	-	-	-	-	-
5.00	-	-	6.02a	6.20	4.81	3.89	3.25	2.77	2.40	2.07	1.79	1.56	-	-	-
4.00	-	-	-	6.08	4.71	3.82	3.20	2.74	2.39	2.07	1.79	1.56	-	-	-
3.00	-	-	8.33	5.98	4.64	3.77	3.17	2.72	2.38	2.06	1.78	1.55	1.36	-	-
2.00	-	-	8.30	5.95	4.61	3.75	3.15	2.70	2.33	2.02	1.75	1.53	1.34	-	-
1.00	-	5.10a	7.94	5.75	4.49	3.66	3.07	2.62	2.27	1.96	1.71	1.49	1.32	-	-
0.00	7.17a	8.50a	7.79	5.61	4.36	3.55	2.98	2.55	2.22	1.91	1.66	1.46	-	-	-
-1.00	10.00	10.00	7.72	5.54	4.30	3.49	2.93	2.50	2.13	1.85	1.62	1.44	-	-	-
-2.00	10.00	10.00	7.74	5.53	4.28	3.46	2.86	2.42	2.08	1.82	-	-	-	-	-
-3.00	10.00	10.00	7.78	5.49	4.22	3.38	2.82	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.86	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.91	3.21	2.70	-	-	-	-	-	-	-
6.00	-	-	-	-	4.82	3.86	3.18	2.68	2.30	1.99	-	-	-	-	-
5.00	-	-	5.00	5.00	4.64	3.73	3.09	2.62	2.26	1.97	1.73	-	-	-	-
4.00	-	-	5.00	5.00	4.35	3.54	2.96	2.53	2.20	1.92	1.70	1.51	-	-	-
3.00	-	-	5.00	5.00	4.26	3.35	2.83	2.44	2.12	1.87	1.66	1.48	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.28	2.73	2.36	2.06	1.82	1.62	1.45	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.22	2.69	2.31	2.02	1.78	1.59	1.43	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	3.21	2.67	2.29	1.99	1.76	1.58	1.42	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.01	3.22	2.68	2.29	1.99	1.76	1.58	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.05	3.25	2.70	2.31	2.01	1.78	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.15	3.36	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.86	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.93	3.24	2.70	-	-	-	-	-	-	-
6.00	-	-	-	-	4.84	3.90	3.24	2.75	2.33	2.00	-	-	-	-	-
5.00	-	-	5.00	5.00	4.75	3.84	3.21	2.74	2.35	2.02	1.74	-	-	-	-
4.00	-	-	5.00	5.00	4.66	3.78	3.17	2.72	2.35	2.02	1.74	1.52	-	-	-
3.00	-	-	5.00	5.00	4.61	3.74	3.14	2.70	2.34	2.00	1.73	1.50	-	-	-
2.00	-	-	5.00	5.00	4.59	3.73	3.12	2.65	2.29	1.96	1.69	1.49	-	-	-
1.00	-	5.00	5.00	5.00	4.43	3.61	3.02	2.58	2.23	1.91	1.66	1.45	-	-	-
0.00	5.00	5.00	5.00	5.00	4.33	3.51	2.95	2.52	2.15	1.86	1.62	1.43	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.27	3.47	2.89	2.43	2.08	1.81	1.59	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.23	3.40	2.81	2.38	2.05	1.79	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.17	3.36	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Minimum Loads)	Hitch	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.39	2.86	2.45	2.12	-	-	-	-	-
6.00	-	-	-	-	-	-	3.34	2.83	2.43	2.11	1.85	-	-	-	-
5.00	-	-	-	-	4.80a	3.93	3.25	2.75	2.37	2.07	1.82	1.62	-	-	-
4.00	-	5.00	5.00	5.00	4.61	3.73	3.10	2.65	2.29	2.01	1.78	1.58	1.42	-	-
3.00	-	4.06a	3.93a	4.47a	4.23	3.48	2.93	2.52	2.20	1.94	1.72	1.54	1.39	1.26	-
2.00	2.78a	2.62a	2.65a	2.91a	3.97	3.28	2.79	2.41	2.11	1.87	1.67	1.50	1.36	1.23	-
1.00	4.19a	3.17a	2.68a	2.66a	3.87	3.17	2.69	2.32	2.04	1.81	1.62	1.46	1.33	1.21	-
0.00	4.74a	3.98a	3.51a	4.25a	3.85	3.13	2.64	2.27	1.99	1.77	1.59	1.44	1.31	-	-
-1.00	5.00	5.00	5.00	5.00	3.86	3.13	2.62	2.26	1.97	1.75	1.57	1.43	-	-	-
-2.00	5.00	5.00	5.00	5.00	3.89	3.15	2.63	2.26	1.98	1.76	1.58	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	3.97	3.20	2.68	2.30	2.01	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DU (Maximum Loads)	Hitch	CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.38	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.39	2.88	2.47	2.12	-	-	-	-	-
6.00	-	-	-	-	-	-	3.36	2.86	2.48	2.16	1.87	-	-	-	-
5.00	-	-	-	-	4.80a	3.96	3.30	2.82	2.45	2.16	1.88	1.64	-	-	-
4.00	-	5.00	5.00	5.00	4.76	3.86	3.24	2.78	2.42	2.14	1.88	1.64	1.44	-	-
3.00	-	5.00	5.00	5.00	4.64	3.78	3.18	2.74	2.40	2.13	1.85	1.62	1.42	1.26	-
2.00	3.93a	5.00	5.00	5.00	4.58	3.74	3.15	2.71	2.38	2.10	1.82	1.59	1.39	1.24	-
1.00	5.00	5.00	5.00	5.00	4.55	3.70	3.10	2.66	2.32	2.03	1.76	1.54	1.36	1.21	-
0.00	5.00	5.00	5.00	5.00	4.37	3.57	3.01	2.58	2.25	1.96	1.70	1.50	1.33	-	-
-1.00	5.00	5.00	5.00	5.00	4.27	3.49	2.93	2.52	2.17	1.87	1.65	1.45	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.23	3.45	2.87	2.42	2.08	1.82	1.61	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.17	3.35	2.78	2.36	2.04	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Minimum Loads)	Tool Pin	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.76	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.74	4.07b	3.44a	3.27	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.40	4.67	4.03b	3.51b	3.25	2.94	2.66	-	-	-
4.00	-	-	-	7.55	6.16	5.26	4.56	3.97b	3.48b	3.21	2.91	2.64	-	-	-
3.00	-	-	6.48a	6.32a	6.04	5.08	4.44	3.93	3.46b	3.16	2.87	2.62	2.40	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.35	3.85	3.45	3.11	2.83	2.59	2.38	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	4.29	3.80	3.40	3.07	2.80	2.56	2.36	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.92	4.27	3.78	3.38	3.05	2.78	2.55	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.80	4.92	4.27	3.77	3.37	3.05	2.78	2.55	-	-	-
-2.00	10.00	10.00	8.96	7.08	5.83	4.95	4.29	3.79	3.39	3.06	-	-	-	-	-
-3.00	10.00	10.00	9.05	7.16	5.91	5.02	4.36	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Maximum Loads)	Tool Pin	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	4.78	4.17	3.66	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	4.77	4.19	3.71	3.29	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	5.47	4.74	4.17	3.71	3.31	2.96	2.66	-	-	-
4.00	-	-	-	7.69	6.37	5.41	4.70	4.14	3.70	3.31	2.96	2.67	-	-	-
3.00	-	-	8.59a	7.61	6.31	5.37	4.67	4.13	3.69	3.30	2.95	2.66	2.41	-	-
2.00	-	-	9.53	7.59	6.29	5.36	4.66	4.12	3.66	3.27	2.92	2.64	2.39	-	-
1.00	-	5.10a	8.87a	7.45	6.19	5.29	4.60	4.05	3.61	3.22	2.89	2.61	2.37	-	-
0.00	7.17a	8.50a	9.20	7.34	6.10	5.20	4.53	3.99	3.56	3.17	2.85	2.58	-	-	-
-1.00	10.00	10.00	9.15	7.29	6.05	5.16	4.49	3.95	3.49	3.12	2.81	2.56	-	-	-
-2.00	10.00	10.00	9.16	7.29	6.04	5.13	4.43	3.88	3.44	3.09	-	-	-	-	-
-3.00	10.00	10.00	9.19	7.26	5.99	5.07	4.39	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.12	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.63	3.24	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.59	3.22	2.91	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.51	3.92b	3.54	3.18	2.88	2.62	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.40	3.88b	3.48	3.13	2.84	2.59	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.32	3.83	3.42	3.09	2.81	2.57	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	4.28	3.79	3.39	3.06	2.78	2.55	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.93	4.27	3.77	3.37	3.04	2.77	2.54	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.94	4.28	3.77	3.37	3.04	2.77	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.96	4.30	3.79	3.38	3.06	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.74	4.12	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.74	4.16	3.66	3.25	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.71	4.14	3.68	3.26	2.92	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.67	4.12	3.68	3.26	2.92	2.63	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.65	4.10b	3.66	3.25	2.90	2.61	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.64	4.08	3.62	3.22	2.88	2.60	-	-	-
1.00	-	5.00	5.00	5.00	5.00	5.00	4.56	4.01	3.57	3.17	2.84	2.57	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.50	3.96	3.50	3.12	2.81	2.55	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.45	3.89	3.44	3.08	2.78	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.39	3.84	3.41	3.06	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Minimum Loads)	Hitch	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.75	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.63	4.04b	3.55b	3.15b	2.54a	2.69	2.46	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	5.00	4.49	3.96b	3.49b	3.12b	2.86a	2.65	2.43	2.24	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.99	4.37	3.87	3.46	3.13	2.85	2.61	2.40	2.22	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.90	4.28	3.80	3.41	3.08	2.81	2.58	2.38	2.20	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.87	4.24	3.76	3.37	3.05	2.78	2.56	2.36	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.86	4.23	3.74	3.35	3.03	2.77	2.54	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.88	4.24	3.75	3.36	3.04	2.77	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.92	4.27	3.78	3.38	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EU (Maximum Loads)	Hitch	CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.25	3.78	3.37	3.02	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.79	4.22	3.76	3.38	3.03	2.73a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.73	4.17	3.73	3.36	3.02	2.73	2.48	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.68	4.14	3.70	3.35	3.01	2.72	2.46	2.24	-
2.00	3.93a	5.00	5.00	5.00	5.00	5.00	4.65	4.12	3.69	3.33	2.98	2.69	2.44	2.23	-
1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.63	4.08	3.65	3.28	2.93	2.65	2.41	2.20	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.55	4.01	3.59	3.21	2.88	2.61	2.38	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.48	3.97	3.52	3.14	2.83	2.57	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.44	3.88	3.44	3.09	2.80	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.36	3.83	3.41	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Minimum Loads)	Tool Pin	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.22	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54	4.68b	4.03b	3.51b	3.19	2.85	2.55	-	-	-
4.00	-	-	-	7.92	6.32	5.33	4.57	3.97b	3.48b	3.13	2.81	2.53	-	-	-
3.00	-	-	6.48a	6.32a	6.15	5.08	4.40	3.86	3.42	3.06	2.75	2.49	2.26	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.26	3.75	3.33	2.99	2.70	2.45	2.24	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	4.19	3.68	3.27	2.94	2.66	2.42	2.22	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.84	4.16	3.65	3.24	2.91	2.63	2.40	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.80	4.85	4.16	3.64	3.23	2.90	2.63	2.40	-	-	-
-2.00	10.00	10.00	9.40	7.24	5.85	4.88	4.19	3.66	3.25	2.92	-	-	-	-	-
-3.00	10.00	10.00	9.54	7.35	5.95	4.98	4.28	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Maximum Loads)	Tool Pin	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	4.88	4.20	3.64	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	4.87	4.23	3.70	3.24	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	5.62	4.82	4.20	3.71b	3.27	2.88	2.56	-	-	-
4.00	-	-	-	8.12	6.60	5.55	4.76	4.16	3.68	3.26	2.88	2.56	-	-	-
3.00	-	-	8.59a	8.00	6.52	5.48	4.72	4.14	3.67	3.25	2.87	2.55	2.28	-	-
2.00	-	-	10.00	7.96	6.49	5.46	4.71	4.12	3.63	3.21	2.83	2.52	2.26	-	-
1.00	-	5.10a	8.87a	7.77	6.37	5.37	4.62	4.03	3.56	3.14	2.78	2.48	2.23	-	-
0.00	7.17a	8.50a	9.76	7.62	6.23	5.25	4.52	3.95	3.49	3.07	2.73	2.44	-	-	-
-1.00	10.00	10.00	9.70	7.54	6.16	5.18	4.46	3.89	3.39	3.00	2.68	2.41	-	-	-
-2.00	10.00	10.00	9.71	7.54	6.14	5.15	4.38	3.80	3.33	2.96	-	-	-	-	-
-3.00	10.00	10.00	9.75	7.49	6.07	5.06	4.33	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.12	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.59	3.17	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.54	3.14	2.81	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.50	3.92b	3.47	3.09	2.77	2.50	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.34	3.81	3.38	3.02	2.72	2.46	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.23	3.72	3.30	2.96	2.67	2.43	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	4.18	3.66	3.25	2.91	2.64	2.40	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.86	4.16	3.64	3.22	2.89	2.62	2.39	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.87	4.17	3.64	3.22	2.89	2.62	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.91	4.20	3.66	3.24	2.92	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.81	4.13	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.82	4.18	3.63	3.18	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.77	4.16	3.66	3.20	2.82	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.73	4.13	3.66	3.20	2.82	2.51	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.69	4.11	3.64	3.18	2.80	2.49	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.68	4.07	3.58	3.13	2.76	2.47	-	-	-
1.00	-	5.00	5.00	5.00	5.00	5.00	4.57	3.98	3.50	3.07	2.72	2.43	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.48	3.91	3.41	3.01	2.67	2.40	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.42	3.81	3.33	2.95	2.64	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.32	3.74	3.29	2.92	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Minimum Loads)	Hitch	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.55b	3.15b	2.54a	2.59	2.35	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	5.00	4.47	3.91	3.47	3.10	2.79	2.53	2.31	2.12	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.94	4.30	3.78	3.36	3.02	2.73	2.48	2.27	2.09	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.82	4.18	3.68	3.28	2.95	2.67	2.44	2.24	2.06	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.77	4.12	3.62	3.22	2.90	2.63	2.41	2.21	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.76	4.10	3.60	3.20	2.88	2.61	2.39	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.79	4.12	3.61	3.21	2.88	2.62	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.85	4.16	3.65	3.25	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3AL (Maximum Loads)	Hitch	CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.30	3.80	3.35a	2.97	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.89	4.26	3.77	3.36	2.98	2.66	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.80	4.20	3.73	3.34	2.98	2.65	2.37	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.74	4.16	3.69	3.32	2.95	2.63	2.36	2.12	-
2.00	3.93a	5.00	5.00	5.00	5.00	5.00	4.70	4.13	3.67	3.29	2.91	2.59	2.32	2.09	-
1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.66	4.08	3.62	3.22	2.84	2.54	2.28	2.06	-
0.00	5.00	5.00	5.00	5.00	5.00	5.00	4.55	3.98	3.53	3.13	2.77	2.48	2.23	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.46	3.92	3.43	3.03	2.70	2.43	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	4.39	3.80	3.33	2.96	2.65	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	4.29	3.73	3.29	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Minimum Loads)	Tool Pin	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.94	3.93	3.22	2.68	-	-	-	-	-	-
6.00	-	-	-	-	-	4.87	3.89	3.20	2.68	2.28	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.09	4.68	3.76	3.11	2.62	2.24	1.94	1.68	-	-	-
4.00	-	-	-	8.00	5.61	4.40	3.57	2.97	2.52	2.17	1.89	1.65	-	-	-
3.00	-	-	6.48a	6.32a	5.37	4.05	3.34	2.81	2.41	2.08	1.82	1.61	1.42	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.87	3.17	2.68	2.30	2.00	1.76	1.56	1.39	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.74	3.07	2.59	2.23	1.94	1.71	1.52	1.36	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.73	3.03	2.55	2.19	1.91	1.68	1.50	-	-	-
-1.00	3.33a	6.24a	5.95a	6.08a	4.85	3.74	3.03	2.54	2.17	1.90	1.68	1.50	-	-	-
-2.00	5.11a	10.00	10.00	6.87	4.92	3.79	3.06	2.56	2.20	1.92	-	-	-	-	-
-3.00	8.35a	10.00	10.00	7.06	5.07	3.93	3.19	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Maximum Loads)	Tool Pin	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.88	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.95	3.98	3.24	2.68	-	-	-	-	-	-
6.00	-	-	-	-	-	4.91	3.96	3.29	2.75	2.30	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.18	4.82	3.90	3.26	2.78	2.34	1.98	1.68	-	-	-
4.00	-	-	-	8.29	6.05	4.72	3.84	3.22	2.75	2.34	1.98	1.69	-	-	-
3.00	-	-	8.59a	8.12	5.93	4.64	3.79	3.18	2.74	2.32	1.96	1.67	1.43	-	-
2.00	-	-	10.00	8.06	5.89	4.60	3.77	3.15	2.67	2.27	1.91	1.64	1.41	-	-
1.00	-	5.10a	8.87a	7.74	5.68	4.45	3.63	3.03	2.58	2.18	1.86	1.59	1.38	-	-
0.00	3.52a	8.50a	10.00	7.50	5.49	4.29	3.51	2.93	2.50	2.10	1.79	1.55	-	-	-
-1.00	5.40a	10.00	10.00	7.37	5.37	4.20	3.43	2.86	2.38	2.02	1.73	1.51	-	-	-
-2.00	7.75a	10.00	10.00	7.36	5.35	4.15	3.32	2.73	2.30	1.97	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.29	5.24	4.03	3.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.84	3.86	3.15	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.77	3.81	3.13	2.62	2.22	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.57	3.67	3.04	2.56	2.19	1.89	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.28	3.48	2.90	2.47	2.12	1.84	1.61	-	-	-
3.00	-	-	5.00	5.00	5.00	3.98	3.27	2.76	2.36	2.04	1.79	1.57	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.87	3.12	2.64	2.26	1.97	1.73	1.53	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.78	3.05	2.57	2.20	1.91	1.69	1.50	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.76	3.03	2.53	2.17	1.89	1.66	1.48	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.91	3.77	3.04	2.53	2.16	1.88	1.66	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.97	3.82	3.08	2.56	2.19	1.92	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	3.99	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.88	3.89	3.15	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.83	3.90	3.23	2.67	2.23	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.74	3.85	3.22	2.70	2.26	1.90	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.65	3.79	3.18	2.70	2.26	1.90	1.62	-	-	-
3.00	-	-	5.00	5.00	5.00	4.59	3.75	3.15	2.67	2.23	1.88	1.60	-	-	-
2.00	-	-	5.00	5.00	5.00	4.57	3.71	3.08	2.61	2.18	1.84	1.58	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.38	3.56	2.97	2.51	2.10	1.78	1.53	-	-	-
0.00	4.29a	5.00	5.00	5.00	5.00	4.23	3.45	2.88	2.39	2.02	1.73	1.49	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.16	3.37	2.75	2.30	1.95	1.69	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.06	3.24	2.67	2.25	1.93	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	3.99	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Minimum Loads)	Hitch	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.12	3.39	2.83a	2.41	-	-	-	-	-
6.00	-	-	-	-	-	-	4.06	3.34	2.81	2.40	2.06	-	-	-	-
5.00	-	-	-	-	4.80a	4.88	3.91	3.23	2.73	2.34	2.03	1.77	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.56	3.69	3.07	2.60	2.24	1.96	1.72	1.52	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.19	3.43	2.88	2.47	2.14	1.87	1.66	1.48	1.32	-
2.00	1.26a	2.62a	2.65a	2.91a	4.44a	3.87	3.21	2.71	2.33	2.04	1.80	1.60	1.43	1.28	-
1.00	1.98a	3.17a	2.68a	2.66a	4.46a	3.70	3.05	2.58	2.23	1.95	1.73	1.54	1.39	1.25	-
0.00	2.27a	3.98a	3.51a	4.25a	4.66	3.64	2.97	2.51	2.17	1.90	1.68	1.51	1.36	-	-
-1.00	3.02a	5.00	5.00	5.00	4.67	3.62	2.95	2.49	2.14	1.87	1.66	1.49	-	-	-
-2.00	4.14a	5.00	5.00	5.00	4.71	3.65	2.97	2.50	2.15	1.88	1.67	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.84	3.74	3.03	2.55	2.19	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3BL (Maximum Loads)	Hitch	CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13	3.42	2.86	2.41	-	-	-	-	-
6.00	-	-	-	-	-	-	4.08	3.40	2.89	2.46	2.09	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	3.99	3.34	2.85	2.47	2.11	1.80	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.78	3.89	3.27	2.80	2.45	2.10	1.79	1.55	-	-
3.00	-	5.00	5.00	5.00	5.00	4.65	3.81	3.21	2.76	2.43	2.07	1.77	1.52	1.32	-
2.00	1.91a	5.00	5.00	5.00	5.00	4.58	3.75	3.17	2.75	2.38	2.02	1.72	1.48	1.29	-
1.00	2.60a	5.00	5.00	5.00	5.00	4.52	3.69	3.09	2.65	2.29	1.93	1.66	1.44	1.25	-
0.00	3.72a	5.00	5.00	5.00	5.00	4.32	3.54	2.97	2.54	2.17	1.85	1.60	1.38	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	4.19	3.42	2.89	2.42	2.05	1.77	1.53	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.13	3.33	2.73	2.30	1.97	1.71	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	3.98	3.20	2.65	2.24	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Minimum Loads)	Tool Pin	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.17	3.38	2.80	2.34	-	-	-	-	-	-
6.00	-	-	-	-	-	4.11	3.34	2.78	2.35	2.00	-	-	-	-	-
5.00	-	-	6.02a	6.07a	4.99	3.94	3.22	2.69	2.29	1.97	1.71	1.48	-	-	-
4.00	-	-	-	6.24	4.57	3.69	3.04	2.57	2.20	1.90	1.66	1.46	-	-	-
3.00	-	-	6.48a	5.98	4.36	3.38	2.84	2.42	2.09	1.82	1.60	1.42	1.25	-	-
2.00	-	-	3.75a	3.90a	4.15	3.22	2.68	2.30	1.99	1.75	1.54	1.37	1.22	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.10	2.59	2.22	1.93	1.69	1.50	1.34	1.20	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	3.09	2.56	2.18	1.89	1.66	1.47	1.32	-	-	-
-1.00	6.84a	6.24a	5.95a	5.25	3.92	3.11	2.56	2.17	1.88	1.65	1.47	1.32	-	-	-
-2.00	10.00	10.00	7.76	5.31	3.98	3.15	2.59	2.19	1.90	1.67	-	-	-	-	-
-3.00	10.00	10.00	7.97	5.47	4.11	3.27	2.70	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Maximum Loads)	Tool Pin	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.18	3.42	2.82	2.35	-	-	-	-	-	-
6.00	-	-	-	-	-	4.14	3.40	2.86	2.41	2.03	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.09	4.06	3.35	2.83	2.43	2.06	1.75	1.49	-	-	-
4.00	-	-	-	6.50	4.95	3.97	3.29	2.79	2.42	2.07	1.75	1.49	-	-	-
3.00	-	-	8.59a	6.36	4.85	3.90	3.24	2.76	2.40	2.04	1.73	1.48	1.27	-	-
2.00	-	-	9.04	6.31	4.81	3.87	3.23	2.73	2.34	1.99	1.69	1.45	1.24	-	-
1.00	-	5.10a	8.52	6.03	4.64	3.74	3.10	2.62	2.25	1.92	1.63	1.40	1.21	-	-
0.00	7.17a	8.50a	8.29	5.83	4.47	3.59	2.99	2.53	2.18	1.84	1.58	1.36	-	-	-
-1.00	10.00	10.00	8.20	5.73	4.37	3.51	2.92	2.46	2.06	1.76	1.52	1.32	-	-	-
-2.00	10.00	10.00	8.21	5.72	4.35	3.47	2.82	2.35	1.99	1.72	-	-	-	-	-
-3.00	10.00	10.00	8.28	5.66	4.26	3.36	2.76	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.09	3.31	2.73	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.02	3.27	2.71	2.29	1.95	-	-	-	-	-
5.00	-	-	5.00	5.00	4.85	3.84	3.14	2.63	2.23	1.92	1.67	-	-	-	-
4.00	-	-	5.00	5.00	4.44	3.58	2.96	2.50	2.15	1.86	1.62	1.42	-	-	-
3.00	-	-	5.00	5.00	4.31	3.32	2.77	2.37	2.05	1.78	1.57	1.38	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.22	2.64	2.26	1.96	1.71	1.51	1.35	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.14	2.58	2.20	1.90	1.66	1.47	1.31	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	3.12	2.56	2.17	1.87	1.64	1.45	1.30	-	-	-
-1.00	5.00	5.00	5.00	5.00	3.97	3.13	2.57	2.17	1.87	1.64	1.45	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.02	3.17	2.60	2.19	1.89	1.67	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.17	3.32	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.12	3.34	2.74	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.08	3.35	2.81	2.34	1.96	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.00	3.30	2.79	2.36	1.99	1.68	-	-	-	-
4.00	-	-	5.00	5.00	4.88	3.92	3.25	2.76	2.36	1.99	1.68	1.43	-	-	-
3.00	-	-	5.00	5.00	4.81	3.86	3.21	2.74	2.34	1.96	1.66	1.41	-	-	-
2.00	-	-	5.00	5.00	4.78	3.84	3.17	2.67	2.28	1.91	1.62	1.39	-	-	-
1.00	-	5.00	5.00	5.00	4.55	3.67	3.04	2.57	2.19	1.84	1.57	1.35	-	-	-
0.00	5.00	5.00	5.00	5.00	4.42	3.54	2.94	2.48	2.08	1.77	1.51	1.31	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.33	3.48	2.86	2.36	1.99	1.70	1.48	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.28	3.38	2.75	2.29	1.94	1.67	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.20	3.32	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Minimum Loads)	Hitch	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.55	2.95	2.49	2.13	-	-	-	-	-
6.00	-	-	-	-	-	-	3.49	2.91	2.46	2.12	1.83	-	-	-	-
5.00	-	-	-	-	4.80a	4.11	3.36	2.81	2.39	2.06	1.79	1.57	-	-	-
4.00	-	5.00	5.00	5.00	4.81	3.84	3.16	2.66	2.28	1.97	1.73	1.52	1.35	-	-
3.00	-	4.06a	3.93a	4.47a	4.28	3.50	2.92	2.49	2.15	1.88	1.65	1.46	1.31	1.17	-
2.00	2.78a	2.62a	2.65a	2.91a	3.91	3.22	2.72	2.33	2.02	1.78	1.58	1.41	1.26	1.13	-
1.00	4.19a	3.17a	2.68a	2.66a	3.78	3.07	2.58	2.21	1.93	1.70	1.51	1.36	1.22	1.11	-
0.00	4.74a	3.98a	3.51a	4.25a	3.75	3.01	2.51	2.15	1.87	1.65	1.47	1.32	1.20	-	-
-1.00	5.00	5.00	5.00	5.00	3.76	3.00	2.49	2.12	1.84	1.63	1.45	1.31	-	-	-
-2.00	5.00	5.00	5.00	5.00	3.80	3.03	2.51	2.13	1.85	1.63	1.46	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	3.91	3.11	2.56	2.18	1.89	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3CL (Maximum Loads)	Hitch	CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.53	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.56	2.99	2.52	2.13	-	-	-	-	-
6.00	-	-	-	-	-	-	3.51	2.96	2.54	2.18	1.85	-	-	-	-
5.00	-	-	-	-	4.80a	4.15	3.43	2.90	2.50	2.19	1.87	1.60	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.03	3.34	2.84	2.46	2.16	1.87	1.59	1.37	-	-
3.00	-	5.00	5.00	5.00	4.86	3.91	3.26	2.79	2.42	2.14	1.83	1.57	1.35	1.17	-
2.00	3.93a	5.00	5.00	5.00	4.77	3.85	3.22	2.75	2.41	2.10	1.78	1.53	1.31	1.14	-
1.00	5.00	5.00	5.00	5.00	4.72	3.80	3.16	2.68	2.32	2.01	1.70	1.47	1.27	1.11	-
0.00	5.00	5.00	5.00	5.00	4.47	3.62	3.02	2.57	2.22	1.91	1.62	1.41	1.22	-	-
-1.00	5.00	5.00	5.00	5.00	4.34	3.50	2.91	2.49	2.11	1.79	1.55	1.35	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.28	3.45	2.83	2.35	1.99	1.72	1.49	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.19	3.31	2.71	2.27	1.94	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Minimum Loads)	Tool Pin	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.41	3.69	3.14	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.38	3.68	3.15	2.72	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.21	4.28	3.61	3.10	2.70	2.37	2.09	-	-	-
4.00	-	-	-	8.13b	6.22	4.99	4.13	3.50	3.02	2.64	2.33	2.07	-	-	-
3.00	-	-	6.48a	6.32a	6.03	4.72	3.95	3.37	2.93	2.57	2.28	2.04	1.83	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.58	3.81	3.27	2.84	2.50	2.23	2.00	1.80	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.97a	3.74	3.20	2.78	2.46	2.19	1.97	1.78	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.55a	4.47	3.71	3.17	2.75	2.43	2.17	1.95	-	-	-
-1.00	6.84a	6.24a	5.95a	6.08a	5.64	4.48	3.71	3.16	2.74	2.42	2.16	1.95	-	-	-
-2.00	10.00	10.00	10.00	7.61	5.69	4.52	3.74	3.18	2.76	2.44	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.76	5.81	4.63	3.83	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Maximum Loads)	Tool Pin	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	4.45	3.71	3.14	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	4.43	3.75	3.20	2.74	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	5.31	4.39	3.72	3.22	2.77	2.40	2.10	-	-	-
4.00	-	-	-	8.62	6.54	5.23	4.34	3.69	3.20	2.78	2.40	2.10	-	-	-
3.00	-	-	8.59a	8.49	6.45	5.17	4.30	3.67	3.19	2.75	2.39	2.09	1.84	-	-
2.00	-	-	10.00	8.45	6.41	5.15	4.28	3.64	3.14	2.71	2.35	2.06	1.82	-	-
1.00	-	5.10a	8.87a	8.25	6.27	5.03	4.18	3.54	3.06	2.65	2.31	2.02	1.79	-	-
0.00	7.17a	8.50a	10.00	8.07	6.12	4.90	4.08	3.47	3.00	2.58	2.26	1.99	-	-	-
-1.00	10.00	10.00	10.00	7.98	6.04	4.84	4.02	3.41	2.90	2.51	2.21	1.96	-	-	-
-2.00	10.00	10.00	10.00	7.98	6.02	4.80	3.94	3.31	2.84	2.48	-	-	-	-	-
-3.00	10.00	10.00	10.00	7.92	5.94	4.70	3.88	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.35	3.64	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.32	3.62	3.10	2.68	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.21	3.55	3.05	2.65	2.33	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.90	4.06	3.44	2.97	2.60	2.29	2.04	-	-	-
3.00	-	-	5.00	5.00	5.00	4.67	3.89	3.33	2.89	2.53	2.25	2.01	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.58	3.78	3.24	2.81	2.48	2.20	1.98	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	4.09a	3.73	3.18	2.76	2.43	2.17	1.95	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.83a	4.50	3.71	3.15	2.74	2.41	2.15	1.94	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.50	3.72	3.16	2.73	2.41	2.15	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.54	3.74	3.18	2.76	2.44	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.67	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.38	3.64	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.39	3.70	3.14	2.68	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.35	3.69	3.16	2.71	2.34	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.30	3.66	3.16	2.71	2.34	2.05	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.27	3.64	3.14	2.68	2.33	2.03	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	4.24	3.58	3.09	2.64	2.29	2.01	-	-	-
1.00	-	5.00	5.00	5.00	5.00	4.97	4.12	3.50	3.01	2.58	2.25	1.98	-	-	-
0.00	5.00	5.00	5.00	5.00	5.00	4.86	4.04	3.43	2.92	2.52	2.20	1.95	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.80	3.97	3.32	2.84	2.47	2.17	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.73	3.87	3.26	2.80	2.44	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	4.67	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Minimum Loads)	Hitch	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	3.79	3.24	2.54a	2.47	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.39	3.71	3.18	2.77	2.44	2.17	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.22	3.58	3.08	2.70	2.39	2.13	1.91	-	-
3.00	-	4.06a	3.93a	4.47a	5.00	4.83	4.02	3.43	2.97	2.62	2.32	2.08	1.87	1.70	-
2.00	2.78a	2.62a	2.65a	2.91a	4.44a	4.58	3.85	3.30	2.87	2.53	2.26	2.03	1.84	1.67	-
1.00	4.19a	3.17a	2.68a	2.66a	4.46a	4.45	3.73	3.19	2.79	2.47	2.20	1.98	1.80	1.64	-
0.00	4.74a	3.98a	3.51a	4.25a	5.00	4.40	3.67	3.14	2.74	2.42	2.17	1.96	1.78	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.39	3.65	3.12	2.71	2.40	2.15	1.94	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.42	3.66	3.12	2.72	2.40	2.16	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.48	3.71	3.16	2.76	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3DL (Maximum Loads)	Hitch	CANT	+/- 135° - +/- 160° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	3.84	3.28	2.83	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	3.83	3.31	2.86	2.49	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	4.46	3.79	3.28	2.88	2.51	2.19	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.38	3.73	3.24	2.86	2.50	2.19	1.93	-	-
3.00	-	5.00	5.00	5.00	5.00	5.00	4.31	3.68	3.21	2.84	2.47	2.17	1.91	1.70	-
2.00	3.93a	5.00	5.00	5.00	5.00	5.00	4.27	3.66	3.20	2.80	2.43	2.13	1.88	1.68	-
1.00	5.00	5.00	5.00	5.00	5.00	5.00	4.22	3.60	3.12	2.73	2.37	2.08	1.84	1.64	-
0.00	5.00	5.00	5.00	5.00	5.00	4.93	4.11	3.50	3.04	2.64	2.30	2.03	1.80	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	4.83	4.01	3.43	2.94	2.54	2.23	1.98	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	4.78	3.94	3.31	2.84	2.48	2.19	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	4.66	3.84	3.24	2.80	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Minimum Loads)	Tool Pin	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.50a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.29a	4.77b	3.95a	3.64a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.21a	4.75b	4.07b	3.44a	3.50a	-	-	-	-	-
5.00	-	-	6.02a	6.07a	6.14a	5.54b	4.68b	4.03b	3.51b	3.43a	3.18a	3.34a	-	-	-
4.00	-	-	-	8.13b	6.53b	5.41b	4.59b	3.97b	3.48b	3.26a	3.66a	3.19a	-	-	-
3.00	-	-	6.48a	6.32a	6.39b	5.31b	4.53b	3.93b	3.46b	3.73a	3.48a	3.28a	3.68a	-	-
2.00	-	-	3.75a	3.90a	4.25a	4.65a	4.50b	4.24b	4.32b	3.96a	4.12a	3.58a	3.85a	-	-
1.00	-	1.55a	3.30a	3.36a	3.58a	3.97a	6.19b	5.79b	5.55b	5.00a	4.40a	4.54a	4.28a	-	-
0.00	2.22a	1.75a	3.52a	3.39a	3.55a	6.61a	7.96b	7.20b	5.23a	5.07a	4.79a	4.67a	-	-	-
-1.00	3.33a	3.03a	5.95a	6.08a	7.13a	9.61b	8.64b	7.50a	6.96b	6.30b	5.61b	4.91b	-	-	-
-2.00	5.11a	5.07a	10.00	10.00	10.00	8.42b	7.49b	6.78b	6.11b	5.38b	-	-	-	-	-
-3.00	8.35a	8.90a	10.00	10.00	10.00	8.59b	7.35b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Maximum Loads)	Tool Pin	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	5.24a	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.31a	5.29a	5.07a	4.33a	-	-	-	-	-	-
6.00	-	-	-	-	-	5.27a	5.41a	5.44a	5.32a	4.91a	-	-	-	-	-
5.00	-	-	6.02a	6.25a	6.36a	6.38a	6.36a	6.11b	5.70b	5.42b	5.19a	3.76a	-	-	-
4.00	-	-	-	10.00	10.00	8.68b	7.62b	6.81b	6.23b	5.81b	5.45b	5.20b	-	-	-
3.00	-	-	8.59a	10.00	10.00	10.00	8.76b	7.66b	6.85b	6.23b	5.75b	5.37b	4.73a	-	-
2.00	-	-	10.00	10.00	10.00	10.00	9.53b	8.24b	7.32b	6.60b	6.02b	5.46	4.88	-	-
1.00	-	2.44a	8.87a	10.00	10.00	10.00	9.71b	8.49b	7.53b	6.76b	6.10	5.45	4.86	-	-
0.00	3.52a	4.22a	10.00	10.00	10.00	10.00	9.76b	8.52b	7.56b	6.79b	6.13	5.41	-	-	-
-1.00	5.40a	6.44a	10.00	10.00	10.00	10.00	9.85b	8.62b	7.67b	6.89b	6.04b	4.98b	-	-	-
-2.00	7.75a	9.33a	10.00	10.00	10.00	10.00	10.00	8.58b	7.29b	6.04b	-	-	-	-	-
-3.00	10.00	10.00	10.00	10.00	10.00	9.96b	8.15b	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Minimum Loads)	AUX LIFTING POINT	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	4.48a	4.39a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	4.68b	4.09a	3.80a	3.90a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	4.61b	3.97b	3.98a	3.89a	3.83a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	4.53b	3.92b	3.84b	3.84a	4.14a	3.75a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	4.47b	3.88b	4.01b	4.27a	4.16a	4.29a	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	4.62a	4.84b	4.75b	4.60a	4.53a	4.93a	4.08a	-	-	-
1.00	-	2.12a	4.10a	3.85a	3.84a	4.09a	5.00	5.00	5.00	5.00	5.00	5.00a	-	-	-
0.00	3.55a	2.55a	4.55a	4.04a	3.83a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	4.45a	4.07a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.97b	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Maximum Loads)	AUX LIFTING POINT	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	5.00	5.00	4.71a	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	5.00	5.00	5.00	5.00	4.28a	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.86a	-	-	-	-
4.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.61a	-	-	-
3.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
2.00	-	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
1.00	-	2.45a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
0.00	4.29a	4.90a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-1.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Minimum Loads)	Hitch	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.13a	3.65a	2.83a	2.70a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.34a	4.21b	3.60a	2.54a	2.55a	-	-	-	-
5.00	-	-	-	-	4.80a	4.92a	4.79b	4.13b	3.61b	2.85a	2.61a	2.51a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	4.66b	4.04b	3.55b	3.15b	2.54a	2.70a	2.49a	-	-
3.00	-	2.02a	3.93a	4.47a	5.00	5.00	4.55b	3.96b	3.49b	3.12b	2.86a	2.77a	2.66a	2.73a	-
2.00	1.26a	1.20a	2.65a	2.91a	4.44a	5.00	4.48b	3.91b	3.47b	3.28a	3.00a	3.04a	3.07a	2.74a	-
1.00	1.98a	1.44a	2.68a	2.66a	4.46a	5.00	5.00	4.76b	4.60b	3.56a	3.72a	3.31a	3.20a	3.23a	-
0.00	2.27a	1.89a	3.51a	4.25a	5.00	5.00	5.00	5.00	5.00	4.20a	4.29a	3.78a	3.84a	-	-
-1.00	3.02a	2.88a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.75a	-	-	-
-2.00	4.14a	4.19a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
3EL (Maximum Loads)	Hitch	CANT	+/- 160° - +/- 180° Over Fixed End		75%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.68a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	4.15a	4.00a	3.64a	2.88a	-	-	-	-	-
6.00	-	-	-	-	-	-	4.35a	4.35a	4.25a	3.95a	3.42a	-	-	-	-
5.00	-	-	-	-	4.80a	4.95a	5.00	4.99a	4.88a	4.66a	4.26a	3.58a	-	-	-
4.00	-	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.53a	3.56a	-	-
3.00	-	3.78a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.31a	2.73a	-
2.00	1.91a	4.14a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.92	3.25a	-
1.00	2.60a	3.96a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.89	3.23a	-
0.00	3.72a	4.66a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	4.85	-	-
-1.00	4.93a	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-
-2.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Minimum Loads)	Tool Pin	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.30	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.35	2.74	2.29	1.93	-	-	-	-	-	-
6.00	-	-	-	-	-	3.30	2.71	2.27	1.94	1.67	-	-	-	-	-
5.00	-	-	6.02a	5.23	3.99	3.18	2.63	2.21	1.90	1.64	1.44	1.26	-	-	-
4.00	-	-	-	4.94	3.69	3.00	2.50	2.12	1.83	1.59	1.40	1.24	-	-	-
3.00	-	-	6.48a	4.76	3.54	2.78	2.35	2.02	1.75	1.54	1.36	1.21	1.08	-	-
2.00	-	-	3.75a	3.90a	3.39	2.66	2.24	1.93	1.68	1.48	1.31	1.17	1.05	-	-
1.00	-	3.43a	3.30a	3.36a	3.26	2.58	2.17	1.87	1.63	1.44	1.28	1.15	1.04	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.21	2.58	2.15	1.84	1.60	1.42	1.26	1.13	-	-	-
-1.00	6.84a	6.24a	5.95a	4.24	3.22	2.58	2.15	1.84	1.60	1.41	1.26	1.13	-	-	-
-2.00	10.00	10.00	6.09	4.28	3.26	2.61	2.17	1.85	1.61	1.42	-	-	-	-	-
-3.00	10.00	10.00	6.24	4.39	3.36	2.70	2.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Maximum Loads)	Tool Pin	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.31	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.36	2.77	2.30	1.94	-	-	-	-	-	-
6.00	-	-	-	-	-	3.33	2.76	2.33	1.98	1.69	-	-	-	-	-
5.00	-	-	6.02a	5.28	4.06	3.27	2.72	2.31	2.00	1.71	1.46	1.26	-	-	-
4.00	-	-	-	5.12	3.96	3.21	2.68	2.29	1.99	1.71	1.46	1.26	-	-	-
3.00	-	-	7.01	5.02	3.89	3.16	2.64	2.26	1.98	1.69	1.45	1.25	1.09	-	-
2.00	-	-	6.98	4.98	3.86	3.13	2.63	2.24	1.93	1.66	1.42	1.23	1.07	-	-
1.00	-	5.10a	6.61	4.79	3.73	3.04	2.54	2.16	1.87	1.60	1.38	1.20	1.05	-	-
0.00	7.17a	8.50a	6.46	4.65	3.61	2.93	2.46	2.10	1.81	1.55	1.34	1.17	-	-	-
-1.00	10.00	10.00	6.40	4.58	3.54	2.88	2.41	2.05	1.73	1.49	1.30	1.14	-	-	-
-2.00	10.00	10.00	6.41	4.57	3.53	2.84	2.34	1.96	1.68	1.46	-	-	-	-	-
-3.00	10.00	10.00	6.45	4.53	3.46	2.76	2.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.29	2.69	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.07	3.24	2.66	2.23	1.90	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	3.89	3.11	2.57	2.17	1.85	1.61	1.40	-	-	-	-
4.00	-	-	5.00	4.84	3.59	2.93	2.44	2.07	1.79	1.56	1.37	1.21	-	-	-
3.00	-	-	5.00	4.70	3.50	2.74	2.30	1.98	1.72	1.51	1.33	1.18	-	-	-
2.00	-	-	3.90a	4.00a	3.39	2.66	2.21	1.90	1.66	1.46	1.29	1.16	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.31	2.60	2.16	1.85	1.61	1.42	1.26	1.13	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.27	2.59	2.15	1.83	1.59	1.40	1.25	1.12	-	-	-
-1.00	5.00	5.00	5.00	4.31	3.26	2.60	2.15	1.83	1.59	1.40	1.25	-	-	-	-
-2.00	5.00	5.00	5.00	4.33	3.29	2.63	2.18	1.85	1.61	1.42	-	-	-	-	-
-3.00	-	5.00	5.00	4.45	3.40	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.31	2.71	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.08	3.28	2.72	2.30	1.93	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	4.00	3.22	2.68	2.29	1.95	1.65	1.41	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.17	2.64	2.26	1.95	1.66	1.41	1.22	-	-	-
3.00	-	-	5.00	4.99	3.85	3.13	2.62	2.24	1.93	1.64	1.40	1.20	-	-	-
2.00	-	-	5.00	4.95	3.84	3.11	2.59	2.20	1.89	1.60	1.37	1.19	-	-	-
1.00	-	5.00	5.00	4.72	3.67	2.99	2.50	2.12	1.82	1.55	1.33	1.16	-	-	-
0.00	5.00	5.00	5.00	4.61	3.58	2.89	2.42	2.06	1.74	1.49	1.29	1.13	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.52	2.85	2.37	1.97	1.68	1.45	1.26	-	-	-	-
-2.00	5.00	5.00	5.00	4.55	3.48	2.78	2.29	1.92	1.64	1.43	-	-	-	-	-
-3.00	-	5.00	5.00	4.48	3.42	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Minimum Loads)	Hitch	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.85	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.86	2.40	2.04	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.82	2.37	2.02	1.75	1.52	-	-	-	-
5.00	-	-	-	-	4.14	3.31	2.72	2.30	1.97	1.71	1.50	1.32	-	-	-
4.00	-	5.00	5.00	5.00	3.85	3.11	2.58	2.19	1.89	1.64	1.45	1.29	1.15	-	-
3.00	-	4.06a	3.93a	4.44	3.48	2.87	2.41	2.06	1.79	1.58	1.39	1.24	1.12	1.00	-
2.00	2.78a	2.62a	2.65a	2.91a	3.21	2.66	2.26	1.95	1.70	1.50	1.34	1.20	1.08	0.98	-
1.00	4.19a	3.17a	2.68a	2.66a	3.12	2.56	2.16	1.86	1.63	1.45	1.29	1.16	1.05	0.96	-
0.00	4.74a	3.98a	3.51a	4.06	3.10	2.52	2.11	1.82	1.59	1.41	1.26	1.14	1.03	-	-
-1.00	5.00	5.00	5.00	4.07	3.11	2.51	2.10	1.80	1.57	1.39	1.25	1.13	-	-	-
-2.00	5.00	5.00	5.00	4.11	3.14	2.53	2.11	1.81	1.58	1.39	1.25	-	-	-	-
-3.00	5.00	5.00	5.00	4.20	3.21	2.58	2.15	1.84	1.61	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AU (Maximum Loads)	Hitch	SUPER CANT	+/- 10° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.86	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.87	2.42	2.06	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.83	2.41	2.08	1.79	1.54	-	-	-	-
5.00	-	-	-	-	4.14	3.34	2.78	2.37	2.05	1.80	1.55	1.34	-	-	-
4.00	-	5.00	5.00	5.00	4.00	3.24	2.71	2.32	2.02	1.78	1.55	1.34	1.16	-	-
3.00	-	5.00	5.00	5.00	3.89	3.16	2.66	2.28	1.99	1.77	1.53	1.32	1.15	1.00	-
2.00	3.93a	5.00	5.00	4.93	3.83	3.12	2.62	2.26	1.98	1.74	1.49	1.29	1.12	0.99	-
1.00	5.00	5.00	5.00	4.86	3.79	3.08	2.58	2.20	1.92	1.67	1.43	1.25	1.09	0.96	-
0.00	5.00	5.00	5.00	4.64	3.62	2.95	2.48	2.12	1.85	1.60	1.37	1.20	1.05	-	-
-1.00	5.00	5.00	5.00	4.53	3.52	2.87	2.40	2.07	1.76	1.51	1.32	1.16	-	-	-
-2.00	5.00	5.00	5.00	4.49	3.48	2.83	2.35	1.96	1.68	1.46	1.28	-	-	-	-
-3.00	5.00	5.00	5.00	4.47	3.42	2.73	2.26	1.91	1.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Minimum Loads)	Tool Pin	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.30	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.35	2.74	2.29	1.93	-	-	-	-	-	-
6.00	-	-	-	-	-	3.30	2.71	2.27	1.94	1.67	-	-	-	-	-
5.00	-	-	6.02a	5.23	3.99	3.18	2.63	2.21	1.90	1.64	1.44	1.26	-	-	-
4.00	-	-	-	4.94	3.69	3.00	2.50	2.12	1.83	1.59	1.40	1.24	-	-	-
3.00	-	-	6.48a	4.76	3.54	2.78	2.35	2.02	1.75	1.54	1.36	1.21	1.08	-	-
2.00	-	-	3.75a	3.90a	3.39	2.66	2.24	1.93	1.68	1.48	1.31	1.17	1.05	-	-
1.00	-	3.43a	3.30a	3.36a	3.26	2.58	2.17	1.87	1.63	1.44	1.28	1.15	1.04	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.21	2.58	2.15	1.84	1.60	1.42	1.26	1.13	-	-	-
-1.00	6.84a	6.24a	5.95a	4.24	3.22	2.58	2.15	1.84	1.60	1.41	1.26	1.13	-	-	-
-2.00	10.00	10.00	6.09	4.28	3.26	2.61	2.17	1.85	1.61	1.42	-	-	-	-	-
-3.00	10.00	10.00	6.24	4.39	3.36	2.70	2.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Maximum Loads)	Tool Pin	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.31	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.36	2.77	2.30	1.94	-	-	-	-	-	-
6.00	-	-	-	-	-	3.33	2.76	2.33	1.98	1.69	-	-	-	-	-
5.00	-	-	6.02a	5.28	4.06	3.27	2.72	2.31	2.00	1.71	1.46	1.26	-	-	-
4.00	-	-	-	5.12	3.96	3.21	2.68	2.29	1.99	1.71	1.46	1.26	-	-	-
3.00	-	-	7.01	5.02	3.89	3.16	2.64	2.26	1.98	1.69	1.45	1.25	1.09	-	-
2.00	-	-	6.98	4.98	3.86	3.13	2.63	2.24	1.93	1.66	1.42	1.23	1.07	-	-
1.00	-	5.10a	6.61	4.79	3.73	3.04	2.54	2.16	1.87	1.60	1.38	1.20	1.05	-	-
0.00	7.17a	8.50a	6.46	4.65	3.61	2.93	2.46	2.10	1.81	1.55	1.34	1.17	-	-	-
-1.00	10.00	10.00	6.40	4.58	3.54	2.88	2.41	2.05	1.73	1.49	1.30	1.14	-	-	-
-2.00	10.00	10.00	6.41	4.57	3.53	2.84	2.34	1.96	1.68	1.46	-	-	-	-	-
-3.00	10.00	10.00	6.45	4.53	3.46	2.76	2.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.29	2.69	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.07	3.24	2.66	2.23	1.90	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	3.89	3.11	2.57	2.17	1.85	1.61	1.40	-	-	-	-
4.00	-	-	5.00	4.84	3.59	2.93	2.44	2.07	1.79	1.56	1.37	1.21	-	-	-
3.00	-	-	5.00	4.70	3.50	2.74	2.30	1.98	1.72	1.51	1.33	1.18	-	-	-
2.00	-	-	3.90a	4.00a	3.39	2.66	2.21	1.90	1.66	1.46	1.29	1.16	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.31	2.60	2.16	1.85	1.61	1.42	1.26	1.13	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.27	2.59	2.15	1.83	1.59	1.40	1.25	1.12	-	-	-
-1.00	5.00	5.00	5.00	4.31	3.26	2.60	2.15	1.83	1.59	1.40	1.25	-	-	-	-
-2.00	5.00	5.00	5.00	4.33	3.29	2.63	2.18	1.85	1.61	1.42	-	-	-	-	-
-3.00	-	5.00	5.00	4.45	3.40	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.31	2.71	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.08	3.28	2.72	2.30	1.93	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	4.00	3.22	2.68	2.29	1.95	1.65	1.41	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.17	2.64	2.26	1.95	1.66	1.41	1.22	-	-	-
3.00	-	-	5.00	4.99	3.85	3.13	2.62	2.24	1.93	1.64	1.40	1.20	-	-	-
2.00	-	-	5.00	4.95	3.84	3.11	2.59	2.20	1.89	1.60	1.37	1.19	-	-	-
1.00	-	5.00	5.00	4.72	3.67	2.99	2.50	2.12	1.82	1.55	1.33	1.16	-	-	-
0.00	5.00	5.00	5.00	4.61	3.58	2.89	2.42	2.06	1.74	1.49	1.29	1.13	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.52	2.85	2.37	1.97	1.68	1.45	1.26	-	-	-	-
-2.00	5.00	5.00	5.00	4.55	3.48	2.78	2.29	1.92	1.64	1.43	-	-	-	-	-
-3.00	-	5.00	5.00	4.48	3.42	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Minimum Loads)	Hitch	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.85	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.86	2.40	2.04	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.82	2.37	2.02	1.75	1.52	-	-	-	-
5.00	-	-	-	-	4.14	3.31	2.72	2.30	1.97	1.71	1.50	1.32	-	-	-
4.00	-	5.00	5.00	5.00	3.85	3.11	2.58	2.19	1.89	1.64	1.45	1.29	1.15	-	-
3.00	-	4.06a	3.93a	4.44	3.48	2.87	2.41	2.06	1.79	1.58	1.39	1.24	1.12	1.00	-
2.00	2.78a	2.62a	2.65a	2.91a	3.21	2.66	2.26	1.95	1.70	1.50	1.34	1.20	1.08	0.98	-
1.00	4.19a	3.17a	2.68a	2.66a	3.12	2.56	2.16	1.86	1.63	1.45	1.29	1.16	1.05	0.96	-
0.00	4.74a	3.98a	3.51a	4.06	3.10	2.52	2.11	1.82	1.59	1.41	1.26	1.14	1.03	-	-
-1.00	5.00	5.00	5.00	4.07	3.11	2.51	2.10	1.80	1.57	1.39	1.25	1.13	-	-	-
-2.00	5.00	5.00	5.00	4.11	3.14	2.53	2.11	1.81	1.58	1.39	1.25	-	-	-	-
-3.00	5.00	5.00	5.00	4.20	3.21	2.58	2.15	1.84	1.61	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BU (Maximum Loads)	Hitch	SUPER CANT	+/- 10° - +/- 45° Over Osc End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.86	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.87	2.42	2.06	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.83	2.41	2.08	1.79	1.54	-	-	-	-
5.00	-	-	-	-	4.14	3.34	2.78	2.37	2.05	1.80	1.55	1.34	-	-	-
4.00	-	5.00	5.00	5.00	4.00	3.24	2.71	2.32	2.02	1.78	1.55	1.34	1.16	-	-
3.00	-	5.00	5.00	5.00	3.89	3.16	2.66	2.28	1.99	1.77	1.53	1.32	1.15	1.00	-
2.00	3.93a	5.00	5.00	4.93	3.83	3.12	2.62	2.26	1.98	1.74	1.49	1.29	1.12	0.99	-
1.00	5.00	5.00	5.00	4.86	3.79	3.08	2.58	2.20	1.92	1.67	1.43	1.25	1.09	0.96	-
0.00	5.00	5.00	5.00	4.64	3.62	2.95	2.48	2.12	1.85	1.60	1.37	1.20	1.05	-	-
-1.00	5.00	5.00	5.00	4.53	3.52	2.87	2.40	2.07	1.76	1.51	1.32	1.16	-	-	-
-2.00	5.00	5.00	5.00	4.49	3.48	2.83	2.35	1.96	1.68	1.46	1.28	-	-	-	-
-3.00	5.00	5.00	5.00	4.47	3.42	2.73	2.26	1.91	1.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Minimum Loads)	Tool Pin	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.30	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.35	2.74	2.29	1.93	-	-	-	-	-	-
6.00	-	-	-	-	-	3.30	2.71	2.27	1.94	1.67	-	-	-	-	-
5.00	-	-	6.02a	5.23	3.99	3.18	2.63	2.21	1.90	1.64	1.44	1.26	-	-	-
4.00	-	-	-	4.94	3.69	3.00	2.50	2.12	1.83	1.59	1.40	1.24	-	-	-
3.00	-	-	6.48a	4.76	3.54	2.78	2.35	2.02	1.75	1.54	1.36	1.21	1.08	-	-
2.00	-	-	3.75a	3.90a	3.39	2.66	2.24	1.93	1.68	1.48	1.31	1.17	1.05	-	-
1.00	-	3.43a	3.30a	3.36a	3.26	2.58	2.17	1.87	1.63	1.44	1.28	1.15	1.04	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.21	2.58	2.15	1.84	1.60	1.42	1.26	1.13	-	-	-
-1.00	6.84a	6.24a	5.95a	4.24	3.22	2.58	2.15	1.84	1.60	1.41	1.26	1.13	-	-	-
-2.00	10.00	10.00	6.09	4.28	3.26	2.61	2.17	1.85	1.61	1.42	-	-	-	-	-
-3.00	10.00	10.00	6.24	4.39	3.36	2.70	2.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Maximum Loads)	Tool Pin	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.31	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.36	2.77	2.30	1.94	-	-	-	-	-	-
6.00	-	-	-	-	-	3.33	2.76	2.33	1.98	1.69	-	-	-	-	-
5.00	-	-	6.02a	5.28	4.06	3.27	2.72	2.31	2.00	1.71	1.46	1.26	-	-	-
4.00	-	-	-	5.12	3.96	3.21	2.68	2.29	1.99	1.71	1.46	1.26	-	-	-
3.00	-	-	7.01	5.02	3.89	3.16	2.64	2.26	1.98	1.69	1.45	1.25	1.09	-	-
2.00	-	-	6.98	4.98	3.86	3.13	2.63	2.24	1.93	1.66	1.42	1.23	1.07	-	-
1.00	-	5.10a	6.61	4.79	3.73	3.04	2.54	2.16	1.87	1.60	1.38	1.20	1.05	-	-
0.00	7.17a	8.50a	6.46	4.65	3.61	2.93	2.46	2.10	1.81	1.55	1.34	1.17	-	-	-
-1.00	10.00	10.00	6.40	4.58	3.54	2.88	2.41	2.05	1.73	1.49	1.30	1.14	-	-	-
-2.00	10.00	10.00	6.41	4.57	3.53	2.84	2.34	1.96	1.68	1.46	-	-	-	-	-
-3.00	10.00	10.00	6.45	4.53	3.46	2.76	2.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.29	2.69	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.07	3.24	2.66	2.23	1.90	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	3.89	3.11	2.57	2.17	1.85	1.61	1.40	-	-	-	-
4.00	-	-	5.00	4.84	3.59	2.93	2.44	2.07	1.79	1.56	1.37	1.21	-	-	-
3.00	-	-	5.00	4.70	3.50	2.74	2.30	1.98	1.72	1.51	1.33	1.18	-	-	-
2.00	-	-	3.90a	4.00a	3.39	2.66	2.21	1.90	1.66	1.46	1.29	1.16	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.31	2.60	2.16	1.85	1.61	1.42	1.26	1.13	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.27	2.59	2.15	1.83	1.59	1.40	1.25	1.12	-	-	-
-1.00	5.00	5.00	5.00	4.31	3.26	2.60	2.15	1.83	1.59	1.40	1.25	-	-	-	-
-2.00	5.00	5.00	5.00	4.33	3.29	2.63	2.18	1.85	1.61	1.42	-	-	-	-	-
-3.00	-	5.00	5.00	4.45	3.40	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.31	2.71	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.08	3.28	2.72	2.30	1.93	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	4.00	3.22	2.68	2.29	1.95	1.65	1.41	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.17	2.64	2.26	1.95	1.66	1.41	1.22	-	-	-
3.00	-	-	5.00	4.99	3.85	3.13	2.62	2.24	1.93	1.64	1.40	1.20	-	-	-
2.00	-	-	5.00	4.95	3.84	3.11	2.59	2.20	1.89	1.60	1.37	1.19	-	-	-
1.00	-	5.00	5.00	4.72	3.67	2.99	2.50	2.12	1.82	1.55	1.33	1.16	-	-	-
0.00	5.00	5.00	5.00	4.61	3.58	2.89	2.42	2.06	1.74	1.49	1.29	1.13	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.52	2.85	2.37	1.97	1.68	1.45	1.26	-	-	-	-
-2.00	5.00	5.00	5.00	4.55	3.48	2.78	2.29	1.92	1.64	1.43	-	-	-	-	-
-3.00	-	5.00	5.00	4.48	3.42	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Minimum Loads)	Hitch	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.85	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.86	2.40	2.04	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.82	2.37	2.02	1.75	1.52	-	-	-	-
5.00	-	-	-	-	4.14	3.31	2.72	2.30	1.97	1.71	1.50	1.32	-	-	-
4.00	-	5.00	5.00	5.00	3.85	3.11	2.58	2.19	1.89	1.64	1.45	1.29	1.15	-	-
3.00	-	4.06a	3.93a	4.44	3.48	2.87	2.41	2.06	1.79	1.58	1.39	1.24	1.12	1.00	-
2.00	2.78a	2.62a	2.65a	2.91a	3.21	2.66	2.26	1.95	1.70	1.50	1.34	1.20	1.08	0.98	-
1.00	4.19a	3.17a	2.68a	2.66a	3.12	2.56	2.16	1.86	1.63	1.45	1.29	1.16	1.05	0.96	-
0.00	4.74a	3.98a	3.51a	4.06	3.10	2.52	2.11	1.82	1.59	1.41	1.26	1.14	1.03	-	-
-1.00	5.00	5.00	5.00	4.07	3.11	2.51	2.10	1.80	1.57	1.39	1.25	1.13	-	-	-
-2.00	5.00	5.00	5.00	4.11	3.14	2.53	2.11	1.81	1.58	1.39	1.25	-	-	-	-
-3.00	5.00	5.00	5.00	4.20	3.21	2.58	2.15	1.84	1.61	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CU (Maximum Loads)	Hitch	SUPER CANT	+/- 45° - +/- 135°		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.86	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.87	2.42	2.06	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.83	2.41	2.08	1.79	1.54	-	-	-	-
5.00	-	-	-	-	4.14	3.34	2.78	2.37	2.05	1.80	1.55	1.34	-	-	-
4.00	-	5.00	5.00	5.00	4.00	3.24	2.71	2.32	2.02	1.78	1.55	1.34	1.16	-	-
3.00	-	5.00	5.00	5.00	3.89	3.16	2.66	2.28	1.99	1.77	1.53	1.32	1.15	1.00	-
2.00	3.93a	5.00	5.00	4.93	3.83	3.12	2.62	2.26	1.98	1.74	1.49	1.29	1.12	0.99	-
1.00	5.00	5.00	5.00	4.86	3.79	3.08	2.58	2.20	1.92	1.67	1.43	1.25	1.09	0.96	-
0.00	5.00	5.00	5.00	4.64	3.62	2.95	2.48	2.12	1.85	1.60	1.37	1.20	1.05	-	-
-1.00	5.00	5.00	5.00	4.53	3.52	2.87	2.40	2.07	1.76	1.51	1.32	1.16	-	-	-
-2.00	5.00	5.00	5.00	4.49	3.48	2.83	2.35	1.96	1.68	1.46	1.28	-	-	-	-
-3.00	5.00	5.00	5.00	4.47	3.42	2.73	2.26	1.91	1.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Minimum Loads)	Tool Pin	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.30	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.35	2.74	2.29	1.93	-	-	-	-	-	-
6.00	-	-	-	-	-	3.30	2.71	2.27	1.94	1.67	-	-	-	-	-
5.00	-	-	6.02a	5.23	3.99	3.18	2.63	2.21	1.90	1.64	1.44	1.26	-	-	-
4.00	-	-	-	4.94	3.69	3.00	2.50	2.12	1.83	1.59	1.40	1.24	-	-	-
3.00	-	-	6.48a	4.76	3.54	2.78	2.35	2.02	1.75	1.54	1.36	1.21	1.08	-	-
2.00	-	-	3.75a	3.90a	3.39	2.66	2.24	1.93	1.68	1.48	1.31	1.17	1.05	-	-
1.00	-	3.43a	3.30a	3.36a	3.26	2.58	2.17	1.87	1.63	1.44	1.28	1.15	1.04	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.21	2.58	2.15	1.84	1.60	1.42	1.26	1.13	-	-	-
-1.00	6.84a	6.24a	5.95a	4.24	3.22	2.58	2.15	1.84	1.60	1.41	1.26	1.13	-	-	-
-2.00	10.00	10.00	6.09	4.28	3.26	2.61	2.17	1.85	1.61	1.42	-	-	-	-	-
-3.00	10.00	10.00	6.24	4.39	3.36	2.70	2.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Maximum Loads)	Tool Pin	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.31	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.36	2.77	2.30	1.94	-	-	-	-	-	-
6.00	-	-	-	-	-	3.33	2.76	2.33	1.98	1.69	-	-	-	-	-
5.00	-	-	6.02a	5.28	4.06	3.27	2.72	2.31	2.00	1.71	1.46	1.26	-	-	-
4.00	-	-	-	5.12	3.96	3.21	2.68	2.29	1.99	1.71	1.46	1.26	-	-	-
3.00	-	-	7.01	5.02	3.89	3.16	2.64	2.26	1.98	1.69	1.45	1.25	1.09	-	-
2.00	-	-	6.98	4.98	3.86	3.13	2.63	2.24	1.93	1.66	1.42	1.23	1.07	-	-
1.00	-	5.10a	6.61	4.79	3.73	3.04	2.54	2.16	1.87	1.60	1.38	1.20	1.05	-	-
0.00	7.17a	8.50a	6.46	4.65	3.61	2.93	2.46	2.10	1.81	1.55	1.34	1.17	-	-	-
-1.00	10.00	10.00	6.40	4.58	3.54	2.88	2.41	2.05	1.73	1.49	1.30	1.14	-	-	-
-2.00	10.00	10.00	6.41	4.57	3.53	2.84	2.34	1.96	1.68	1.46	-	-	-	-	-
-3.00	10.00	10.00	6.45	4.53	3.46	2.76	2.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.29	2.69	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.07	3.24	2.66	2.23	1.90	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	3.89	3.11	2.57	2.17	1.85	1.61	1.40	-	-	-	-
4.00	-	-	5.00	4.84	3.59	2.93	2.44	2.07	1.79	1.56	1.37	1.21	-	-	-
3.00	-	-	5.00	4.70	3.50	2.74	2.30	1.98	1.72	1.51	1.33	1.18	-	-	-
2.00	-	-	3.90a	4.00a	3.39	2.66	2.21	1.90	1.66	1.46	1.29	1.16	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.31	2.60	2.16	1.85	1.61	1.42	1.26	1.13	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.27	2.59	2.15	1.83	1.59	1.40	1.25	1.12	-	-	-
-1.00	5.00	5.00	5.00	4.31	3.26	2.60	2.15	1.83	1.59	1.40	1.25	-	-	-	-
-2.00	5.00	5.00	5.00	4.33	3.29	2.63	2.18	1.85	1.61	1.42	-	-	-	-	-
-3.00	-	5.00	5.00	4.45	3.40	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.31	2.71	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.08	3.28	2.72	2.30	1.93	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	4.00	3.22	2.68	2.29	1.95	1.65	1.41	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.17	2.64	2.26	1.95	1.66	1.41	1.22	-	-	-
3.00	-	-	5.00	4.99	3.85	3.13	2.62	2.24	1.93	1.64	1.40	1.20	-	-	-
2.00	-	-	5.00	4.95	3.84	3.11	2.59	2.20	1.89	1.60	1.37	1.19	-	-	-
1.00	-	5.00	5.00	4.72	3.67	2.99	2.50	2.12	1.82	1.55	1.33	1.16	-	-	-
0.00	5.00	5.00	5.00	4.61	3.58	2.89	2.42	2.06	1.74	1.49	1.29	1.13	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.52	2.85	2.37	1.97	1.68	1.45	1.26	-	-	-	-
-2.00	5.00	5.00	5.00	4.55	3.48	2.78	2.29	1.92	1.64	1.43	-	-	-	-	-
-3.00	-	5.00	5.00	4.48	3.42	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Minimum Loads)	Hitch	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.85	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.86	2.40	2.04	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.82	2.37	2.02	1.75	1.52	-	-	-	-
5.00	-	-	-	-	4.14	3.31	2.72	2.30	1.97	1.71	1.50	1.32	-	-	-
4.00	-	5.00	5.00	5.00	3.85	3.11	2.58	2.19	1.89	1.64	1.45	1.29	1.15	-	-
3.00	-	4.06a	3.93a	4.44	3.48	2.87	2.41	2.06	1.79	1.58	1.39	1.24	1.12	1.00	-
2.00	2.78a	2.62a	2.65a	2.91a	3.21	2.66	2.26	1.95	1.70	1.50	1.34	1.20	1.08	0.98	-
1.00	4.19a	3.17a	2.68a	2.66a	3.12	2.56	2.16	1.86	1.63	1.45	1.29	1.16	1.05	0.96	-
0.00	4.74a	3.98a	3.51a	4.06	3.10	2.52	2.11	1.82	1.59	1.41	1.26	1.14	1.03	-	-
-1.00	5.00	5.00	5.00	4.07	3.11	2.51	2.10	1.80	1.57	1.39	1.25	1.13	-	-	-
-2.00	5.00	5.00	5.00	4.11	3.14	2.53	2.11	1.81	1.58	1.39	1.25	-	-	-	-
-3.00	5.00	5.00	5.00	4.20	3.21	2.58	2.15	1.84	1.61	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DU (Maximum Loads)	Hitch	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.86	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.87	2.42	2.06	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.83	2.41	2.08	1.79	1.54	-	-	-	-
5.00	-	-	-	-	4.14	3.34	2.78	2.37	2.05	1.80	1.55	1.34	-	-	-
4.00	-	5.00	5.00	5.00	4.00	3.24	2.71	2.32	2.02	1.78	1.55	1.34	1.16	-	-
3.00	-	5.00	5.00	5.00	3.89	3.16	2.66	2.28	1.99	1.77	1.53	1.32	1.15	1.00	-
2.00	3.93a	5.00	5.00	4.93	3.83	3.12	2.62	2.26	1.98	1.74	1.49	1.29	1.12	0.99	-
1.00	5.00	5.00	5.00	4.86	3.79	3.08	2.58	2.20	1.92	1.67	1.43	1.25	1.09	0.96	-
0.00	5.00	5.00	5.00	4.64	3.62	2.95	2.48	2.12	1.85	1.60	1.37	1.20	1.05	-	-
-1.00	5.00	5.00	5.00	4.53	3.52	2.87	2.40	2.07	1.76	1.51	1.32	1.16	-	-	-
-2.00	5.00	5.00	5.00	4.49	3.48	2.83	2.35	1.96	1.68	1.46	1.28	-	-	-	-
-3.00	5.00	5.00	5.00	4.47	3.42	2.73	2.26	1.91	1.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Minimum Loads)	Tool Pin	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.30	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.35	2.74	2.29	1.93	-	-	-	-	-	-
6.00	-	-	-	-	-	3.30	2.71	2.27	1.94	1.67	-	-	-	-	-
5.00	-	-	6.02a	5.23	3.99	3.18	2.63	2.21	1.90	1.64	1.44	1.26	-	-	-
4.00	-	-	-	4.94	3.69	3.00	2.50	2.12	1.83	1.59	1.40	1.24	-	-	-
3.00	-	-	6.48a	4.76	3.54	2.78	2.35	2.02	1.75	1.54	1.36	1.21	1.08	-	-
2.00	-	-	3.75a	3.90a	3.39	2.66	2.24	1.93	1.68	1.48	1.31	1.17	1.05	-	-
1.00	-	3.43a	3.30a	3.36a	3.26	2.58	2.17	1.87	1.63	1.44	1.28	1.15	1.04	-	-
0.00	4.75a	3.83a	3.52a	3.39a	3.21	2.58	2.15	1.84	1.60	1.42	1.26	1.13	-	-	-
-1.00	6.84a	6.24a	5.95a	4.24	3.22	2.58	2.15	1.84	1.60	1.41	1.26	1.13	-	-	-
-2.00	10.00	10.00	6.09	4.28	3.26	2.61	2.17	1.85	1.61	1.42	-	-	-	-	-
-3.00	10.00	10.00	6.24	4.39	3.36	2.70	2.25	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Maximum Loads)	Tool Pin	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	3.31	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.36	2.77	2.30	1.94	-	-	-	-	-	-
6.00	-	-	-	-	-	3.33	2.76	2.33	1.98	1.69	-	-	-	-	-
5.00	-	-	6.02a	5.28	4.06	3.27	2.72	2.31	2.00	1.71	1.46	1.26	-	-	-
4.00	-	-	-	5.12	3.96	3.21	2.68	2.29	1.99	1.71	1.46	1.26	-	-	-
3.00	-	-	7.01	5.02	3.89	3.16	2.64	2.26	1.98	1.69	1.45	1.25	1.09	-	-
2.00	-	-	6.98	4.98	3.86	3.13	2.63	2.24	1.93	1.66	1.42	1.23	1.07	-	-
1.00	-	5.10a	6.61	4.79	3.73	3.04	2.54	2.16	1.87	1.60	1.38	1.20	1.05	-	-
0.00	7.17a	8.50a	6.46	4.65	3.61	2.93	2.46	2.10	1.81	1.55	1.34	1.17	-	-	-
-1.00	10.00	10.00	6.40	4.58	3.54	2.88	2.41	2.05	1.73	1.49	1.30	1.14	-	-	-
-2.00	10.00	10.00	6.41	4.57	3.53	2.84	2.34	1.96	1.68	1.46	-	-	-	-	-
-3.00	10.00	10.00	6.45	4.53	3.46	2.76	2.30	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.29	2.69	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.07	3.24	2.66	2.23	1.90	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	3.89	3.11	2.57	2.17	1.85	1.61	1.40	-	-	-	-
4.00	-	-	5.00	4.84	3.59	2.93	2.44	2.07	1.79	1.56	1.37	1.21	-	-	-
3.00	-	-	5.00	4.70	3.50	2.74	2.30	1.98	1.72	1.51	1.33	1.18	-	-	-
2.00	-	-	3.90a	4.00a	3.39	2.66	2.21	1.90	1.66	1.46	1.29	1.16	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.31	2.60	2.16	1.85	1.61	1.42	1.26	1.13	-	-	-
0.00	5.00	5.00	4.55a	4.04a	3.27	2.59	2.15	1.83	1.59	1.40	1.25	1.12	-	-	-
-1.00	5.00	5.00	5.00	4.31	3.26	2.60	2.15	1.83	1.59	1.40	1.25	-	-	-	-
-2.00	5.00	5.00	5.00	4.33	3.29	2.63	2.18	1.85	1.61	1.42	-	-	-	-	-
-3.00	-	5.00	5.00	4.45	3.40	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	4.11	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	3.31	2.71	2.24	-	-	-	-	-	-	-
6.00	-	-	-	-	4.08	3.28	2.72	2.30	1.93	1.63	-	-	-	-	-
5.00	-	-	5.00	5.00	4.00	3.22	2.68	2.29	1.95	1.65	1.41	-	-	-	-
4.00	-	-	5.00	5.00	3.91	3.17	2.64	2.26	1.95	1.66	1.41	1.22	-	-	-
3.00	-	-	5.00	4.99	3.85	3.13	2.62	2.24	1.93	1.64	1.40	1.20	-	-	-
2.00	-	-	5.00	4.95	3.84	3.11	2.59	2.20	1.89	1.60	1.37	1.19	-	-	-
1.00	-	5.00	5.00	4.72	3.67	2.99	2.50	2.12	1.82	1.55	1.33	1.16	-	-	-
0.00	5.00	5.00	5.00	4.61	3.58	2.89	2.42	2.06	1.74	1.49	1.29	1.13	-	-	-
-1.00	5.00	5.00	5.00	4.55	3.52	2.85	2.37	1.97	1.68	1.45	1.26	-	-	-	-
-2.00	5.00	5.00	5.00	4.55	3.48	2.78	2.29	1.92	1.64	1.43	-	-	-	-	-
-3.00	-	5.00	5.00	4.48	3.42	2.74	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Minimum Loads)	Hitch	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.85	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.86	2.40	2.04	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.82	2.37	2.02	1.75	1.52	-	-	-	-
5.00	-	-	-	-	4.14	3.31	2.72	2.30	1.97	1.71	1.50	1.32	-	-	-
4.00	-	5.00	5.00	5.00	3.85	3.11	2.58	2.19	1.89	1.64	1.45	1.29	1.15	-	-
3.00	-	4.06a	3.93a	4.44	3.48	2.87	2.41	2.06	1.79	1.58	1.39	1.24	1.12	1.00	-
2.00	2.78a	2.62a	2.65a	2.91a	3.21	2.66	2.26	1.95	1.70	1.50	1.34	1.20	1.08	0.98	-
1.00	4.19a	3.17a	2.68a	2.66a	3.12	2.56	2.16	1.86	1.63	1.45	1.29	1.16	1.05	0.96	-
0.00	4.74a	3.98a	3.51a	4.06	3.10	2.52	2.11	1.82	1.59	1.41	1.26	1.14	1.03	-	-
-1.00	5.00	5.00	5.00	4.07	3.11	2.51	2.10	1.80	1.57	1.39	1.25	1.13	-	-	-
-2.00	5.00	5.00	5.00	4.11	3.14	2.53	2.11	1.81	1.58	1.39	1.25	-	-	-	-
-3.00	5.00	5.00	5.00	4.20	3.21	2.58	2.15	1.84	1.61	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EU (Maximum Loads)	Hitch	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		67%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	2.86	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	2.87	2.42	2.06	1.76	-	-	-	-	-
6.00	-	-	-	-	-	-	2.83	2.41	2.08	1.79	1.54	-	-	-	-
5.00	-	-	-	-	4.14	3.34	2.78	2.37	2.05	1.80	1.55	1.34	-	-	-
4.00	-	5.00	5.00	5.00	4.00	3.24	2.71	2.32	2.02	1.78	1.55	1.34	1.16	-	-
3.00	-	5.00	5.00	5.00	3.89	3.16	2.66	2.28	1.99	1.77	1.53	1.32	1.15	1.00	-
2.00	3.93a	5.00	5.00	4.93	3.83	3.12	2.62	2.26	1.98	1.74	1.49	1.29	1.12	0.99	-
1.00	5.00	5.00	5.00	4.86	3.79	3.08	2.58	2.20	1.92	1.67	1.43	1.25	1.09	0.96	-
0.00	5.00	5.00	5.00	4.64	3.62	2.95	2.48	2.12	1.85	1.60	1.37	1.20	1.05	-	-
-1.00	5.00	5.00	5.00	4.53	3.52	2.87	2.40	2.07	1.76	1.51	1.32	1.16	-	-	-
-2.00	5.00	5.00	5.00	4.49	3.48	2.83	2.35	1.96	1.68	1.46	1.28	-	-	-	-
-3.00	5.00	5.00	5.00	4.47	3.42	2.73	2.26	1.91	1.64	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Minimum Loads)	Tool Pin	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.32	3.42	2.78	2.29	-	-	-	-	-	-
6.00	-	-	-	-	-	4.25	3.38	2.76	2.30	1.94	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.31	4.06	3.25	2.67	2.24	1.90	1.63	1.40	-	-	-
4.00	-	-	-	6.93	4.83	3.78	3.05	2.53	2.14	1.83	1.58	1.37	-	-	-
3.00	-	-	6.48a	6.32a	4.58	3.43	2.83	2.37	2.02	1.75	1.52	1.33	1.17	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.25	2.65	2.24	1.92	1.66	1.46	1.28	1.14	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.12	2.55	2.15	1.84	1.60	1.41	1.24	1.11	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.11	2.52	2.11	1.81	1.57	1.38	1.22	-	-	-
-1.00	3.33a	6.24a	5.95a	5.73	4.06	3.12	2.52	2.10	1.79	1.56	1.37	1.23	-	-	-
-2.00	5.11a	10.00	9.34	5.80	4.13	3.17	2.55	2.13	1.82	1.58	-	-	-	-	-
-3.00	8.35a	10.00	9.62	6.00	4.29	3.30	2.67	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Maximum Loads)	Tool Pin	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.33	3.46	2.81	2.30	-	-	-	-	-	-
6.00	-	-	-	-	-	4.29	3.45	2.85	2.37	1.97	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.42	4.20	3.39	2.82	2.39	2.00	1.67	1.40	-	-	-
4.00	-	-	-	7.25	5.27	4.10	3.32	2.78	2.37	2.00	1.67	1.41	-	-	-
3.00	-	-	8.59a	7.08	5.15	4.02	3.27	2.75	2.36	1.98	1.66	1.40	1.18	-	-
2.00	-	-	10.00	7.02	5.10	3.98	3.25	2.71	2.29	1.93	1.61	1.36	1.16	-	-
1.00	-	5.10a	8.87a	6.68	4.90	3.83	3.12	2.59	2.20	1.84	1.55	1.31	1.12	-	-
0.00	3.52a	8.50a	10.00	6.44	4.70	3.67	2.99	2.50	2.12	1.76	1.49	1.27	-	-	-
-1.00	5.40a	10.00	9.93	6.31	4.59	3.58	2.91	2.42	1.99	1.68	1.43	1.23	-	-	-
-2.00	7.75a	10.00	9.95	6.30	4.57	3.53	2.81	2.30	1.91	1.63	-	-	-	-	-
-3.00	10.00	10.00	10.00	6.23	4.46	3.41	2.74	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.22	3.34	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.14	3.29	2.69	2.24	1.88	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	3.95	3.16	2.60	2.18	1.85	1.59	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.66	2.96	2.46	2.08	1.78	1.54	1.34	-	-	-
3.00	-	-	5.00	5.00	4.53	3.36	2.75	2.32	1.97	1.70	1.48	1.29	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.25	2.61	2.20	1.88	1.63	1.42	1.25	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.15	2.54	2.13	1.82	1.57	1.38	1.22	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.14	2.52	2.09	1.78	1.55	1.36	1.21	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.13	3.15	2.53	2.10	1.78	1.54	1.36	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.18	3.20	2.56	2.12	1.81	1.58	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.36	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.38	2.72	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.21	3.39	2.79	2.29	1.89	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.12	3.33	2.78	2.32	1.92	1.60	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.03	3.27	2.74	2.32	1.92	1.60	1.35	-	-	-
3.00	-	-	5.00	5.00	5.00	3.97	3.23	2.72	2.29	1.89	1.58	1.33	-	-	-
2.00	-	-	5.00	5.00	5.00	3.95	3.19	2.64	2.23	1.84	1.53	1.30	-	-	-
1.00	-	5.00	5.00	5.00	4.80	3.75	3.05	2.53	2.13	1.76	1.48	1.26	-	-	-
0.00	4.29a	5.00	5.00	5.00	4.64	3.61	2.94	2.44	2.01	1.68	1.43	1.22	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.55	3.54	2.85	2.31	1.92	1.61	1.38	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.43	2.73	2.23	1.86	1.59	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.39	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Minimum Loads)	Hitch	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.61	2.95	2.46	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.54	2.90	2.42	2.06	1.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.26	3.39	2.80	2.34	2.00	1.72	1.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	3.94	3.18	2.63	2.22	1.90	1.65	1.44	1.27	-	-
3.00	-	4.06a	3.93a	4.47a	4.49	3.56	2.92	2.44	2.08	1.80	1.57	1.38	1.22	1.08	-
2.00	1.26a	2.62a	2.65a	2.91a	4.05	3.25	2.69	2.28	1.95	1.70	1.49	1.32	1.17	1.05	-
1.00	1.98a	3.17a	2.68a	2.66a	3.90	3.08	2.54	2.14	1.85	1.62	1.42	1.26	1.13	1.02	-
0.00	2.27a	3.98a	3.51a	4.25a	3.87	3.02	2.46	2.07	1.78	1.56	1.38	1.23	1.10	-	-
-1.00	3.02a	5.00	5.00	5.00	3.88	3.00	2.44	2.05	1.76	1.53	1.36	1.21	-	-	-
-2.00	4.14a	5.00	5.00	5.00	3.93	3.03	2.46	2.06	1.76	1.54	1.37	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.05	3.12	2.52	2.11	1.81	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4AL (Maximum Loads)	Hitch	SUPER CANT	+/- 10° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.58	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.62	2.99	2.49	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.57	2.96	2.51	2.12	1.79	-	-	-	-
5.00	-	-	-	-	4.80a	4.30	3.48	2.90	2.47	2.14	1.80	1.53	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.16	3.38	2.83	2.42	2.11	1.80	1.52	1.29	-	-
3.00	-	5.00	5.00	5.00	5.00	4.03	3.29	2.77	2.38	2.09	1.76	1.49	1.27	1.08	-
2.00	1.91a	5.00	5.00	5.00	5.00	3.96	3.24	2.73	2.36	2.04	1.71	1.44	1.23	1.06	-
1.00	2.60a	5.00	5.00	5.00	5.00	3.90	3.17	2.66	2.27	1.95	1.63	1.39	1.18	1.02	-
0.00	3.72a	5.00	5.00	5.00	4.71	3.69	3.03	2.53	2.16	1.83	1.54	1.32	1.13	-	-
-1.00	4.93a	5.00	5.00	5.00	4.56	3.57	2.91	2.45	2.04	1.71	1.46	1.25	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.51	2.82	2.29	1.92	1.63	1.40	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.38	3.36	2.68	2.21	1.86	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Minimum Loads)	Tool Pin	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.32	3.42	2.78	2.29	-	-	-	-	-	-
6.00	-	-	-	-	-	4.25	3.38	2.76	2.30	1.94	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.31	4.06	3.25	2.67	2.24	1.90	1.63	1.40	-	-	-
4.00	-	-	-	6.93	4.83	3.78	3.05	2.53	2.14	1.83	1.58	1.37	-	-	-
3.00	-	-	6.48a	6.32a	4.58	3.43	2.83	2.37	2.02	1.75	1.52	1.33	1.17	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.25	2.65	2.24	1.92	1.66	1.46	1.28	1.14	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.12	2.55	2.15	1.84	1.60	1.41	1.24	1.11	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.11	2.52	2.11	1.81	1.57	1.38	1.22	-	-	-
-1.00	3.33a	6.24a	5.95a	5.73	4.06	3.12	2.52	2.10	1.79	1.56	1.37	1.23	-	-	-
-2.00	5.11a	10.00	9.34	5.80	4.13	3.17	2.55	2.13	1.82	1.58	-	-	-	-	-
-3.00	8.35a	10.00	9.62	6.00	4.29	3.30	2.67	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Maximum Loads)	Tool Pin	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.33	3.46	2.81	2.30	-	-	-	-	-	-
6.00	-	-	-	-	-	4.29	3.45	2.85	2.37	1.97	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.42	4.20	3.39	2.82	2.39	2.00	1.67	1.40	-	-	-
4.00	-	-	-	7.25	5.27	4.10	3.32	2.78	2.37	2.00	1.67	1.41	-	-	-
3.00	-	-	8.59a	7.08	5.15	4.02	3.27	2.75	2.36	1.98	1.66	1.40	1.18	-	-
2.00	-	-	10.00	7.02	5.10	3.98	3.25	2.71	2.29	1.93	1.61	1.36	1.16	-	-
1.00	-	5.10a	8.87a	6.68	4.90	3.83	3.12	2.59	2.20	1.84	1.55	1.31	1.12	-	-
0.00	3.52a	8.50a	10.00	6.44	4.70	3.67	2.99	2.50	2.12	1.76	1.49	1.27	-	-	-
-1.00	5.40a	10.00	9.93	6.31	4.59	3.58	2.91	2.42	1.99	1.68	1.43	1.23	-	-	-
-2.00	7.75a	10.00	9.95	6.30	4.57	3.53	2.81	2.30	1.91	1.63	-	-	-	-	-
-3.00	10.00	10.00	10.00	6.23	4.46	3.41	2.74	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.22	3.34	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.14	3.29	2.69	2.24	1.88	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	3.95	3.16	2.60	2.18	1.85	1.59	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.66	2.96	2.46	2.08	1.78	1.54	1.34	-	-	-
3.00	-	-	5.00	5.00	4.53	3.36	2.75	2.32	1.97	1.70	1.48	1.29	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.25	2.61	2.20	1.88	1.63	1.42	1.25	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.15	2.54	2.13	1.82	1.57	1.38	1.22	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.14	2.52	2.09	1.78	1.55	1.36	1.21	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.13	3.15	2.53	2.10	1.78	1.54	1.36	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.18	3.20	2.56	2.12	1.81	1.58	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.36	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.38	2.72	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.21	3.39	2.79	2.29	1.89	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.12	3.33	2.78	2.32	1.92	1.60	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.03	3.27	2.74	2.32	1.92	1.60	1.35	-	-	-
3.00	-	-	5.00	5.00	5.00	3.97	3.23	2.72	2.29	1.89	1.58	1.33	-	-	-
2.00	-	-	5.00	5.00	5.00	3.95	3.19	2.64	2.23	1.84	1.53	1.30	-	-	-
1.00	-	5.00	5.00	5.00	4.80	3.75	3.05	2.53	2.13	1.76	1.48	1.26	-	-	-
0.00	4.29a	5.00	5.00	5.00	4.64	3.61	2.94	2.44	2.01	1.68	1.43	1.22	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.55	3.54	2.85	2.31	1.92	1.61	1.38	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.43	2.73	2.23	1.86	1.59	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.39	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Minimum Loads)	Hitch	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.61	2.95	2.46	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.54	2.90	2.42	2.06	1.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.26	3.39	2.80	2.34	2.00	1.72	1.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	3.94	3.18	2.63	2.22	1.90	1.65	1.44	1.27	-	-
3.00	-	4.06a	3.93a	4.47a	4.49	3.56	2.92	2.44	2.08	1.80	1.57	1.38	1.22	1.08	-
2.00	1.26a	2.62a	2.65a	2.91a	4.05	3.25	2.69	2.28	1.95	1.70	1.49	1.32	1.17	1.05	-
1.00	1.98a	3.17a	2.68a	2.66a	3.90	3.08	2.54	2.14	1.85	1.62	1.42	1.26	1.13	1.02	-
0.00	2.27a	3.98a	3.51a	4.25a	3.87	3.02	2.46	2.07	1.78	1.56	1.38	1.23	1.10	-	-
-1.00	3.02a	5.00	5.00	5.00	3.88	3.00	2.44	2.05	1.76	1.53	1.36	1.21	-	-	-
-2.00	4.14a	5.00	5.00	5.00	3.93	3.03	2.46	2.06	1.76	1.54	1.37	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.05	3.12	2.52	2.11	1.81	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4BL (Maximum Loads)	Hitch	SUPER CANT	+/- 10° - +/- 45° Over Osc End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.58	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.62	2.99	2.49	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.57	2.96	2.51	2.12	1.79	-	-	-	-
5.00	-	-	-	-	4.80a	4.30	3.48	2.90	2.47	2.14	1.80	1.53	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.16	3.38	2.83	2.42	2.11	1.80	1.52	1.29	-	-
3.00	-	5.00	5.00	5.00	5.00	4.03	3.29	2.77	2.38	2.09	1.76	1.49	1.27	1.08	-
2.00	1.91a	5.00	5.00	5.00	5.00	3.96	3.24	2.73	2.36	2.04	1.71	1.44	1.23	1.06	-
1.00	2.60a	5.00	5.00	5.00	5.00	3.90	3.17	2.66	2.27	1.95	1.63	1.39	1.18	1.02	-
0.00	3.72a	5.00	5.00	5.00	4.71	3.69	3.03	2.53	2.16	1.83	1.54	1.32	1.13	-	-
-1.00	4.93a	5.00	5.00	5.00	4.56	3.57	2.91	2.45	2.04	1.71	1.46	1.25	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.51	2.82	2.29	1.92	1.63	1.40	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.38	3.36	2.68	2.21	1.86	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Minimum Loads)	Tool Pin	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.32	3.42	2.78	2.29	-	-	-	-	-	-
6.00	-	-	-	-	-	4.25	3.38	2.76	2.30	1.94	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.31	4.06	3.25	2.67	2.24	1.90	1.63	1.40	-	-	-
4.00	-	-	-	6.93	4.83	3.78	3.05	2.53	2.14	1.83	1.58	1.37	-	-	-
3.00	-	-	6.48a	6.32a	4.58	3.43	2.83	2.37	2.02	1.75	1.52	1.33	1.17	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.25	2.65	2.24	1.92	1.66	1.46	1.28	1.14	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.12	2.55	2.15	1.84	1.60	1.41	1.24	1.11	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.11	2.52	2.11	1.81	1.57	1.38	1.22	-	-	-
-1.00	3.33a	6.24a	5.95a	5.73	4.06	3.12	2.52	2.10	1.79	1.56	1.37	1.23	-	-	-
-2.00	5.11a	10.00	9.34	5.80	4.13	3.17	2.55	2.13	1.82	1.58	-	-	-	-	-
-3.00	8.35a	10.00	9.62	6.00	4.29	3.30	2.67	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Maximum Loads)	Tool Pin	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.33	3.46	2.81	2.30	-	-	-	-	-	-
6.00	-	-	-	-	-	4.29	3.45	2.85	2.37	1.97	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.42	4.20	3.39	2.82	2.39	2.00	1.67	1.40	-	-	-
4.00	-	-	-	7.25	5.27	4.10	3.32	2.78	2.37	2.00	1.67	1.41	-	-	-
3.00	-	-	8.59a	7.08	5.15	4.02	3.27	2.75	2.36	1.98	1.66	1.40	1.18	-	-
2.00	-	-	10.00	7.02	5.10	3.98	3.25	2.71	2.29	1.93	1.61	1.36	1.16	-	-
1.00	-	5.10a	8.87a	6.68	4.90	3.83	3.12	2.59	2.20	1.84	1.55	1.31	1.12	-	-
0.00	3.52a	8.50a	10.00	6.44	4.70	3.67	2.99	2.50	2.12	1.76	1.49	1.27	-	-	-
-1.00	5.40a	10.00	9.93	6.31	4.59	3.58	2.91	2.42	1.99	1.68	1.43	1.23	-	-	-
-2.00	7.75a	10.00	9.95	6.30	4.57	3.53	2.81	2.30	1.91	1.63	-	-	-	-	-
-3.00	10.00	10.00	10.00	6.23	4.46	3.41	2.74	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.22	3.34	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.14	3.29	2.69	2.24	1.88	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	3.95	3.16	2.60	2.18	1.85	1.59	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.66	2.96	2.46	2.08	1.78	1.54	1.34	-	-	-
3.00	-	-	5.00	5.00	4.53	3.36	2.75	2.32	1.97	1.70	1.48	1.29	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.25	2.61	2.20	1.88	1.63	1.42	1.25	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.15	2.54	2.13	1.82	1.57	1.38	1.22	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.14	2.52	2.09	1.78	1.55	1.36	1.21	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.13	3.15	2.53	2.10	1.78	1.54	1.36	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.18	3.20	2.56	2.12	1.81	1.58	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.36	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.38	2.72	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.21	3.39	2.79	2.29	1.89	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.12	3.33	2.78	2.32	1.92	1.60	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.03	3.27	2.74	2.32	1.92	1.60	1.35	-	-	-
3.00	-	-	5.00	5.00	5.00	3.97	3.23	2.72	2.29	1.89	1.58	1.33	-	-	-
2.00	-	-	5.00	5.00	5.00	3.95	3.19	2.64	2.23	1.84	1.53	1.30	-	-	-
1.00	-	5.00	5.00	5.00	4.80	3.75	3.05	2.53	2.13	1.76	1.48	1.26	-	-	-
0.00	4.29a	5.00	5.00	5.00	4.64	3.61	2.94	2.44	2.01	1.68	1.43	1.22	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.55	3.54	2.85	2.31	1.92	1.61	1.38	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.43	2.73	2.23	1.86	1.59	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.39	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Minimum Loads)	Hitch	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.61	2.95	2.46	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.54	2.90	2.42	2.06	1.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.26	3.39	2.80	2.34	2.00	1.72	1.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	3.94	3.18	2.63	2.22	1.90	1.65	1.44	1.27	-	-
3.00	-	4.06a	3.93a	4.47a	4.49	3.56	2.92	2.44	2.08	1.80	1.57	1.38	1.22	1.08	-
2.00	1.26a	2.62a	2.65a	2.91a	4.05	3.25	2.69	2.28	1.95	1.70	1.49	1.32	1.17	1.05	-
1.00	1.98a	3.17a	2.68a	2.66a	3.90	3.08	2.54	2.14	1.85	1.62	1.42	1.26	1.13	1.02	-
0.00	2.27a	3.98a	3.51a	4.25a	3.87	3.02	2.46	2.07	1.78	1.56	1.38	1.23	1.10	-	-
-1.00	3.02a	5.00	5.00	5.00	3.88	3.00	2.44	2.05	1.76	1.53	1.36	1.21	-	-	-
-2.00	4.14a	5.00	5.00	5.00	3.93	3.03	2.46	2.06	1.76	1.54	1.37	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.05	3.12	2.52	2.11	1.81	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4CL (Maximum Loads)	Hitch	SUPER CANT	+/- 45° - +/- 135°		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.58	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.62	2.99	2.49	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.57	2.96	2.51	2.12	1.79	-	-	-	-
5.00	-	-	-	-	4.80a	4.30	3.48	2.90	2.47	2.14	1.80	1.53	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.16	3.38	2.83	2.42	2.11	1.80	1.52	1.29	-	-
3.00	-	5.00	5.00	5.00	5.00	4.03	3.29	2.77	2.38	2.09	1.76	1.49	1.27	1.08	-
2.00	1.91a	5.00	5.00	5.00	5.00	3.96	3.24	2.73	2.36	2.04	1.71	1.44	1.23	1.06	-
1.00	2.60a	5.00	5.00	5.00	5.00	3.90	3.17	2.66	2.27	1.95	1.63	1.39	1.18	1.02	-
0.00	3.72a	5.00	5.00	5.00	4.71	3.69	3.03	2.53	2.16	1.83	1.54	1.32	1.13	-	-
-1.00	4.93a	5.00	5.00	5.00	4.56	3.57	2.91	2.45	2.04	1.71	1.46	1.25	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.51	2.82	2.29	1.92	1.63	1.40	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.38	3.36	2.68	2.21	1.86	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Minimum Loads)	Tool Pin	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.32	3.42	2.78	2.29	-	-	-	-	-	-
6.00	-	-	-	-	-	4.25	3.38	2.76	2.30	1.94	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.31	4.06	3.25	2.67	2.24	1.90	1.63	1.40	-	-	-
4.00	-	-	-	6.93	4.83	3.78	3.05	2.53	2.14	1.83	1.58	1.37	-	-	-
3.00	-	-	6.48a	6.32a	4.58	3.43	2.83	2.37	2.02	1.75	1.52	1.33	1.17	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.25	2.65	2.24	1.92	1.66	1.46	1.28	1.14	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.12	2.55	2.15	1.84	1.60	1.41	1.24	1.11	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.11	2.52	2.11	1.81	1.57	1.38	1.22	-	-	-
-1.00	3.33a	6.24a	5.95a	5.73	4.06	3.12	2.52	2.10	1.79	1.56	1.37	1.23	-	-	-
-2.00	5.11a	10.00	9.34	5.80	4.13	3.17	2.55	2.13	1.82	1.58	-	-	-	-	-
-3.00	8.35a	10.00	9.62	6.00	4.29	3.30	2.67	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Maximum Loads)	Tool Pin	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.33	3.46	2.81	2.30	-	-	-	-	-	-
6.00	-	-	-	-	-	4.29	3.45	2.85	2.37	1.97	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.42	4.20	3.39	2.82	2.39	2.00	1.67	1.40	-	-	-
4.00	-	-	-	7.25	5.27	4.10	3.32	2.78	2.37	2.00	1.67	1.41	-	-	-
3.00	-	-	8.59a	7.08	5.15	4.02	3.27	2.75	2.36	1.98	1.66	1.40	1.18	-	-
2.00	-	-	10.00	7.02	5.10	3.98	3.25	2.71	2.29	1.93	1.61	1.36	1.16	-	-
1.00	-	5.10a	8.87a	6.68	4.90	3.83	3.12	2.59	2.20	1.84	1.55	1.31	1.12	-	-
0.00	3.52a	8.50a	10.00	6.44	4.70	3.67	2.99	2.50	2.12	1.76	1.49	1.27	-	-	-
-1.00	5.40a	10.00	9.93	6.31	4.59	3.58	2.91	2.42	1.99	1.68	1.43	1.23	-	-	-
-2.00	7.75a	10.00	9.95	6.30	4.57	3.53	2.81	2.30	1.91	1.63	-	-	-	-	-
-3.00	10.00	10.00	10.00	6.23	4.46	3.41	2.74	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.22	3.34	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.14	3.29	2.69	2.24	1.88	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	3.95	3.16	2.60	2.18	1.85	1.59	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.66	2.96	2.46	2.08	1.78	1.54	1.34	-	-	-
3.00	-	-	5.00	5.00	4.53	3.36	2.75	2.32	1.97	1.70	1.48	1.29	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.25	2.61	2.20	1.88	1.63	1.42	1.25	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.15	2.54	2.13	1.82	1.57	1.38	1.22	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.14	2.52	2.09	1.78	1.55	1.36	1.21	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.13	3.15	2.53	2.10	1.78	1.54	1.36	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.18	3.20	2.56	2.12	1.81	1.58	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.36	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.38	2.72	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.21	3.39	2.79	2.29	1.89	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.12	3.33	2.78	2.32	1.92	1.60	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.03	3.27	2.74	2.32	1.92	1.60	1.35	-	-	-
3.00	-	-	5.00	5.00	5.00	3.97	3.23	2.72	2.29	1.89	1.58	1.33	-	-	-
2.00	-	-	5.00	5.00	5.00	3.95	3.19	2.64	2.23	1.84	1.53	1.30	-	-	-
1.00	-	5.00	5.00	5.00	4.80	3.75	3.05	2.53	2.13	1.76	1.48	1.26	-	-	-
0.00	4.29a	5.00	5.00	5.00	4.64	3.61	2.94	2.44	2.01	1.68	1.43	1.22	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.55	3.54	2.85	2.31	1.92	1.61	1.38	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.43	2.73	2.23	1.86	1.59	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.39	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Minimum Loads)	Hitch	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.61	2.95	2.46	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.54	2.90	2.42	2.06	1.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.26	3.39	2.80	2.34	2.00	1.72	1.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	3.94	3.18	2.63	2.22	1.90	1.65	1.44	1.27	-	-
3.00	-	4.06a	3.93a	4.47a	4.49	3.56	2.92	2.44	2.08	1.80	1.57	1.38	1.22	1.08	-
2.00	1.26a	2.62a	2.65a	2.91a	4.05	3.25	2.69	2.28	1.95	1.70	1.49	1.32	1.17	1.05	-
1.00	1.98a	3.17a	2.68a	2.66a	3.90	3.08	2.54	2.14	1.85	1.62	1.42	1.26	1.13	1.02	-
0.00	2.27a	3.98a	3.51a	4.25a	3.87	3.02	2.46	2.07	1.78	1.56	1.38	1.23	1.10	-	-
-1.00	3.02a	5.00	5.00	5.00	3.88	3.00	2.44	2.05	1.76	1.53	1.36	1.21	-	-	-
-2.00	4.14a	5.00	5.00	5.00	3.93	3.03	2.46	2.06	1.76	1.54	1.37	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.05	3.12	2.52	2.11	1.81	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4DL (Maximum Loads)	Hitch	SUPER CANT	+/- 135° - +/- 160° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.58	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.62	2.99	2.49	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.57	2.96	2.51	2.12	1.79	-	-	-	-
5.00	-	-	-	-	4.80a	4.30	3.48	2.90	2.47	2.14	1.80	1.53	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.16	3.38	2.83	2.42	2.11	1.80	1.52	1.29	-	-
3.00	-	5.00	5.00	5.00	5.00	4.03	3.29	2.77	2.38	2.09	1.76	1.49	1.27	1.08	-
2.00	1.91a	5.00	5.00	5.00	5.00	3.96	3.24	2.73	2.36	2.04	1.71	1.44	1.23	1.06	-
1.00	2.60a	5.00	5.00	5.00	5.00	3.90	3.17	2.66	2.27	1.95	1.63	1.39	1.18	1.02	-
0.00	3.72a	5.00	5.00	5.00	4.71	3.69	3.03	2.53	2.16	1.83	1.54	1.32	1.13	-	-
-1.00	4.93a	5.00	5.00	5.00	4.56	3.57	2.91	2.45	2.04	1.71	1.46	1.25	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.51	2.82	2.29	1.92	1.63	1.40	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.38	3.36	2.68	2.21	1.86	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Minimum Loads)	Tool Pin	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.32	3.42	2.78	2.29	-	-	-	-	-	-
6.00	-	-	-	-	-	4.25	3.38	2.76	2.30	1.94	-	-	-	-	-
5.00	-	-	6.02a	6.07a	5.31	4.06	3.25	2.67	2.24	1.90	1.63	1.40	-	-	-
4.00	-	-	-	6.93	4.83	3.78	3.05	2.53	2.14	1.83	1.58	1.37	-	-	-
3.00	-	-	6.48a	6.32a	4.58	3.43	2.83	2.37	2.02	1.75	1.52	1.33	1.17	-	-
2.00	-	-	3.75a	3.90a	4.25a	3.25	2.65	2.24	1.92	1.66	1.46	1.28	1.14	-	-
1.00	-	3.43a	3.30a	3.36a	3.58a	3.12	2.55	2.15	1.84	1.60	1.41	1.24	1.11	-	-
0.00	2.22a	3.83a	3.52a	3.39a	3.55a	3.11	2.52	2.11	1.81	1.57	1.38	1.22	-	-	-
-1.00	3.33a	6.24a	5.95a	5.73	4.06	3.12	2.52	2.10	1.79	1.56	1.37	1.23	-	-	-
-2.00	5.11a	10.00	9.34	5.80	4.13	3.17	2.55	2.13	1.82	1.58	-	-	-	-	-
-3.00	8.35a	10.00	9.62	6.00	4.29	3.30	2.67	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Maximum Loads)	Tool Pin	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	4.25	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.33	3.46	2.81	2.30	-	-	-	-	-	-
6.00	-	-	-	-	-	4.29	3.45	2.85	2.37	1.97	-	-	-	-	-
5.00	-	-	6.02a	6.25a	5.42	4.20	3.39	2.82	2.39	2.00	1.67	1.40	-	-	-
4.00	-	-	-	7.25	5.27	4.10	3.32	2.78	2.37	2.00	1.67	1.41	-	-	-
3.00	-	-	8.59a	7.08	5.15	4.02	3.27	2.75	2.36	1.98	1.66	1.40	1.18	-	-
2.00	-	-	10.00	7.02	5.10	3.98	3.25	2.71	2.29	1.93	1.61	1.36	1.16	-	-
1.00	-	5.10a	8.87a	6.68	4.90	3.83	3.12	2.59	2.20	1.84	1.55	1.31	1.12	-	-
0.00	3.52a	8.50a	10.00	6.44	4.70	3.67	2.99	2.50	2.12	1.76	1.49	1.27	-	-	-
-1.00	5.40a	10.00	9.93	6.31	4.59	3.58	2.91	2.42	1.99	1.68	1.43	1.23	-	-	-
-2.00	7.75a	10.00	9.95	6.30	4.57	3.53	2.81	2.30	1.91	1.63	-	-	-	-	-
-3.00	10.00	10.00	10.00	6.23	4.46	3.41	2.74	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Minimum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.22	3.34	2.71	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.14	3.29	2.69	2.24	1.88	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	3.95	3.16	2.60	2.18	1.85	1.59	-	-	-	-
4.00	-	-	5.00	5.00	4.67	3.66	2.96	2.46	2.08	1.78	1.54	1.34	-	-	-
3.00	-	-	5.00	5.00	4.53	3.36	2.75	2.32	1.97	1.70	1.48	1.29	-	-	-
2.00	-	-	3.90a	4.00a	4.14a	3.25	2.61	2.20	1.88	1.63	1.42	1.25	-	-	-
1.00	-	4.64a	4.10a	3.85a	3.84a	3.15	2.54	2.13	1.82	1.57	1.38	1.22	-	-	-
0.00	3.55a	5.00	4.55a	4.04a	3.83a	3.14	2.52	2.09	1.78	1.55	1.36	1.21	-	-	-
-1.00	4.45a	5.00	5.00	5.00	4.13	3.15	2.53	2.10	1.78	1.54	1.36	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.18	3.20	2.56	2.12	1.81	1.58	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.36	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Maximum Loads)	AUX LIFTING POINT	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	5.00	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	4.26	3.38	2.72	-	-	-	-	-	-	-
6.00	-	-	-	-	5.00	4.21	3.39	2.79	2.29	1.89	-	-	-	-	-
5.00	-	-	5.00	5.00	5.00	4.12	3.33	2.78	2.32	1.92	1.60	-	-	-	-
4.00	-	-	5.00	5.00	5.00	4.03	3.27	2.74	2.32	1.92	1.60	1.35	-	-	-
3.00	-	-	5.00	5.00	5.00	3.97	3.23	2.72	2.29	1.89	1.58	1.33	-	-	-
2.00	-	-	5.00	5.00	5.00	3.95	3.19	2.64	2.23	1.84	1.53	1.30	-	-	-
1.00	-	5.00	5.00	5.00	4.80	3.75	3.05	2.53	2.13	1.76	1.48	1.26	-	-	-
0.00	4.29a	5.00	5.00	5.00	4.64	3.61	2.94	2.44	2.01	1.68	1.43	1.22	-	-	-
-1.00	5.00	5.00	5.00	5.00	4.55	3.54	2.85	2.31	1.92	1.61	1.38	-	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.43	2.73	2.23	1.86	1.59	-	-	-	-	-
-3.00	-	5.00	5.00	5.00	4.39	3.37	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Minimum Loads)	Hitch	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.16a	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.61	2.95	2.46	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.54	2.90	2.42	2.06	1.76	-	-	-	-
5.00	-	-	-	-	4.80a	4.26	3.39	2.80	2.34	2.00	1.72	1.49	-	-	-
4.00	-	5.00	5.00	5.00	5.00	3.94	3.18	2.63	2.22	1.90	1.65	1.44	1.27	-	-
3.00	-	4.06a	3.93a	4.47a	4.49	3.56	2.92	2.44	2.08	1.80	1.57	1.38	1.22	1.08	-
2.00	1.26a	2.62a	2.65a	2.91a	4.05	3.25	2.69	2.28	1.95	1.70	1.49	1.32	1.17	1.05	-
1.00	1.98a	3.17a	2.68a	2.66a	3.90	3.08	2.54	2.14	1.85	1.62	1.42	1.26	1.13	1.02	-
0.00	2.27a	3.98a	3.51a	4.25a	3.87	3.02	2.46	2.07	1.78	1.56	1.38	1.23	1.10	-	-
-1.00	3.02a	5.00	5.00	5.00	3.88	3.00	2.44	2.05	1.76	1.53	1.36	1.21	-	-	-
-2.00	4.14a	5.00	5.00	5.00	3.93	3.03	2.46	2.06	1.76	1.54	1.37	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.05	3.12	2.52	2.11	1.81	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Duty	Lift Point	Config	Sector	Osc Axle	Safety	Lift Mode	
4EL (Maximum Loads)	Hitch	SUPER CANT	+/- 160° - +/- 180° Over Fixed End		90%	Tandem	

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	3.58	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	3.62	2.99	2.49	2.07	-	-	-	-	-
6.00	-	-	-	-	-	-	3.57	2.96	2.51	2.12	1.79	-	-	-	-
5.00	-	-	-	-	4.80a	4.30	3.48	2.90	2.47	2.14	1.80	1.53	-	-	-
4.00	-	5.00	5.00	5.00	5.00	4.16	3.38	2.83	2.42	2.11	1.80	1.52	1.29	-	-
3.00	-	5.00	5.00	5.00	5.00	4.03	3.29	2.77	2.38	2.09	1.76	1.49	1.27	1.08	-
2.00	1.91a	5.00	5.00	5.00	5.00	3.96	3.24	2.73	2.36	2.04	1.71	1.44	1.23	1.06	-
1.00	2.60a	5.00	5.00	5.00	5.00	3.90	3.17	2.66	2.27	1.95	1.63	1.39	1.18	1.02	-
0.00	3.72a	5.00	5.00	5.00	4.71	3.69	3.03	2.53	2.16	1.83	1.54	1.32	1.13	-	-
-1.00	4.93a	5.00	5.00	5.00	4.56	3.57	2.91	2.45	2.04	1.71	1.46	1.25	-	-	-
-2.00	5.00	5.00	5.00	5.00	4.49	3.51	2.82	2.29	1.92	1.63	1.40	-	-	-	-
-3.00	5.00	5.00	5.00	5.00	4.38	3.36	2.68	2.21	1.86	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

NOTES

SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower).
 Radius/Height are given in metres. Loads are given in tonnes, and assume that the load is suspended vertically below the bucket pin with no other equipment attached.
 Loads marked 'b' boom, 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).